

Fundamentals of Evolutionary Multi-Objective Optimization

Carlos A. Coello Coello¹

CINVESTAV-IPN

Departamento de Computación

Evolutionary Computation Group

Av. IPN No. 2508, Col. San Pedro Zacatenco

México, D.F. 07360, MEXICO

email: `ccoello@cs.cinvestav.mx`

January 21, 2010

¹The author is also associated to the UMI-LAFMIA 3175 CNRS.

Chapter 1

Fundamentals of Evolutionary Multi-Objective Optimization

The solution of optimization problems having two or more (often conflicting) criteria has become relatively common in a wide variety of application areas. Such problems are called “multi-objective” and their solution has raised an important amount of research within Operations Research, particularly in the last 35 years [52]. In spite of the large number of mathematical programming methods available for solving multi-objective optimization problems, such methods tend to have a rather limited applicability (e.g., when dealing with differentiable objective functions, or with convex Pareto fronts). This has motivated the use of alternative solution approaches such as evolutionary algorithms.

The use of evolutionary algorithms for solving multi-objective optimization problems was originally hinted at the late 1960s [65], but the first actual implementation of a multi-objective evolutionary algorithm (MOEA) was not produced until 1985 [68]. However, this area, which is now called “evolutionary multi-objective optimization,” or EMO) has experienced a very important growth, mainly in the last 15 years [8, 15].

This chapter presents a basic introduction to EMO, focusing on its main concepts, the most popular algorithms in current use, and some of its applications. The remainder of this

chapter is organized as follows. In Section 1.1, we provide some basic concepts from multi-objective optimization. The use of evolutionary algorithms in multi-objective optimization is motivated in Section 1.2. Some of the main topics of research which are currently attracting a lot of attention in the EMO field are briefly discussed in Section 1.3. A set of sample applications of MOEAs is provided in Section 1.4. Some of the main topics of research in the EMO field that currently attract a lot of attention are briefly discussed in Section 1.5. Finally, some conclusions are provided in Section 1.6.

1.1 Basic Concepts

We are interested in the solution of multi-objective optimization problems (MOPs) of the form:

$$\text{minimize } [f_1(\vec{x}), f_2(\vec{x}), \dots, f_k(\vec{x})] \quad (1.1)$$

subject to the m inequality constraints:

$$g_i(\vec{x}) \leq 0 \quad i = 1, 2, \dots, m \quad (1.2)$$

and the p equality constraints:

$$h_i(\vec{x}) = 0 \quad i = 1, 2, \dots, p \quad (1.3)$$

where k is the number of objective functions $f_i : \mathbb{R}^n \rightarrow \mathbb{R}$. We call $\vec{x} = [x_1, x_2, \dots, x_n]^T$ the vector of decision variables. We wish to determine from among the set \mathcal{F} of all vectors which satisfy (1.2) and (1.3) the particular set of values $x_1^*, x_2^*, \dots, x_n^*$ which yield the optimum values of all the objective functions.

1.1.1 Pareto optimality

It is rarely the case that there is a single point that simultaneously optimizes all the objective functions.¹ Therefore, we normally look for “trade-offs”, rather than single solutions when dealing with multi-objective optimization problems. The notion of “optimality” normally adopted in this case is the one originally proposed by Francis Ysidro Edgeworth [20] and later generalized by Vilfredo Pareto [57]. Although some authors call this notion *Edgeworth-Pareto optimality*, we will use the most commonly adopted term: *Pareto optimality*.

We say that a vector of decision variables $\vec{x}^* \in \mathcal{F}$ is *Pareto optimal* if there does not exist another $\vec{x} \in \mathcal{F}$ such that $f_i(\vec{x}) \leq f_i(\vec{x}^*)$ for all $i = 1, \dots, k$ and $f_j(\vec{x}) < f_j(\vec{x}^*)$ for at least one j (assuming minimization).

In words, this definition says that \vec{x}^* is Pareto optimal if there exists no feasible vector of decision variables $\vec{x} \in \mathcal{F}$ which would decrease some criterion without causing a simultaneous increase in at least one other criterion. It is worth noting that the use of this concept normally produces a set of solutions called the *Pareto optimal set*. The vectors \vec{x}^* corresponding to the solutions included in the Pareto optimal set are called *nondominated*. The image of the Pareto optimal set under the objective functions is called *Pareto front*.

1.2 Use of Evolutionary Algorithms

The idea of using techniques based on the emulation of the mechanism of natural selection (described in Darwin’s evolutionary theory) to solve problems can be traced back to the early 1930s [25]. However, it was not until the 1960s that the three main techniques based on this notion were developed: genetic algorithms [35], evolution strategies [70] and evolutionary programming [26]. These approaches, which are now collectively denominated “evolutionary algorithms,” have been very effective for single-objective optimization [30, 71, 27].

¹In fact, this situation only arises when there is no conflict among the objectives, which would make unnecessary the development of special solution methods, since this single solution could be reached after the sequential optimization of all the objectives, considered separately.

The basic operation of an evolutionary algorithm (EA) is the following. First, they generate a set of possible solutions (called a “population”) to the problem at hand. Such a population is normally generated in a random manner. Each solution in the population (called an “individual”) encodes all the decision variables of the problem. In order to assess their suitability, a fitness function must be defined. Such a fitness function is a variation of the objective function of the problem that we wish to solve. Then, a selection mechanism must be applied in order to decide which individuals will “mate.” This selection process is normally based on the fitness contribution of each individual (i.e., the fittest individuals have a higher probability of being selected). Upon mating, a set of “offspring” are generated. Such offspring are “mutated” (this operator produces a small random change, with a low probability, on the contents of an individual), and constitute the population to be evaluated at the following iteration (called a “generation”). This process is repeated until reaching a stopping condition (normally, a maximum number of generations).

EAs are considered a good choice for solving multi-objective optimization problems because they adopt a population of solutions, which allows them (if properly manipulated) to find several elements of the Pareto optimal set in a single run. This contrasts with mathematical programming methods, which normally generate a single nondominated solution per execution. Additionally, EAs tend to be less susceptible to the discontinuity and the shape of the Pareto front, which is an important advantage over traditional mathematical programming methods [21].

Multi-objective Evolutionary Algorithms (MOEAs) extend a traditional evolutionary algorithm in two main aspects:

- The selection mechanism. In this case, the aim is to select nondominated solutions, and to consider all the nondominated solutions in a population as equally good.
- A diversity maintenance mechanism. This is necessary to avoid convergence to a single solution, which is something that will eventually happen with an EA (because of stochastic noise) if run for a sufficiently long time.

Regarding selection, although in their early days, several MOEAs relied on aggregating

functions [34] and relatively simple population-based approaches [68], today, most of them adopt some form of *Pareto ranking*. This approach was originally proposed by David E. Goldberg [30], and it sorts the population of an EA based on Pareto dominance, such that all nondominated individuals are assigned the same rank (or importance). The aim is that all nondominated individuals get the same probability of being selected, and that such probability is higher than the one corresponding to individuals which are dominated. Although conceptually simple, this sort of selection mechanism allows for a wide variety of possible implementations [8, 15].

A number of methods have been proposed in the literature to maintain diversity in an EA. Such approaches include fitness sharing and niching [32, 16], clustering [78, 84], geographically-based schemes [42], and the use of entropy [39, 12], among others. Additionally, some researchers have proposed the use of mating restriction schemes [72, 84]. Furthermore, the use of relaxed forms of Pareto dominance has also become relatively popular in recent years, mainly as an archiving technique which encourages diversity, while allowing the archive to regulate convergence (see for example, ϵ -dominance [45]).

A third component of modern MOEAs is elitism, which normally consists of using an external archive (called a “secondary population”) that can (or cannot) interact in different ways with the main (or “primary”) population of the MOEA. The main purpose of this archive is to store all the nondominated solutions generated throughout the search process, while removing those that become dominated later in the search (called local nondominated solutions). The approximation of the Pareto optimal set produced by a MOEA is thus the final contents of this archive.

1.3 Multi-Objective Evolutionary Algorithms

Despite the considerable volume of literature on MOEAs that is currently available², very few algorithms are used by a significant number of researchers around the world. The following are, from the author’s perspective, the most representative MOEAs in current use:

²The author maintains the EMOO repository, which, as of December 2008, contains over 3,600 bibliographic references on evolutionary multi-objective optimization. The EMOO repository is available at: <http://delta.cs.cinvestav.mx/~ccoello/EMOO/>

1. **Strength Pareto Evolutionary Algorithm (SPEA)**: This MOEA was conceived as the merge of several algorithms developed during the 1990s [84]. It adopts an external archive (called the external nondominated set), which stores the nondominated solutions previously generated, and participates in the selection process (together with the main population). For each individual in this archive, a *strength* value is computed. This strength is proportional to the number of solutions which a certain individual dominates. In SPEA, the fitness of each member of the current population is computed according to the strengths of all external nondominated solutions that dominate it. Since the external nondominated set can grow too much, this could reduce the selection process and could slow down the search. In order to avoid this, SPEA adopts a technique that prunes the contents of the external nondominated set so that its size remains below a certain (pre-defined) threshold. For that sake, the authors use a clustering technique.
2. **Strength Pareto Evolutionary Algorithm 2 (SPEA2)**: This approach has three main differences with respect to its predecessor [83]: (1) it incorporates a fine-grained fitness assignment strategy which takes into account for each individual the number of individuals that dominate it and the number of individuals by which it is dominated; (2) it uses a nearest neighbor density estimation technique which guides the search more efficiently, and (3) it has an enhanced archive truncation method that guarantees the preservation of boundary solutions.
3. **Pareto Archived Evolution Strategy (PAES)**: This is perhaps the most simple MOEA than one can conceive, and was introduced by Knowles and Corne [44]. It consists of a (1+1) evolution strategy (i.e., a single parent that generates a single offspring) in combination with a historical archive that stores the nondominated solutions previously found. This archive is used as a reference set against which each mutated individual is being compared. Such (external) archive adopts a crowding procedure that divides objective function space in a recursive manner. Then, each solution is placed in a certain grid location based on the values of its objectives (which are used as its “coordinates” or “geographical location”). A map of such a grid is maintained, indicating the number of solutions that reside in each grid location. When a new non-dominated solution is ready to be stored in the archive, but there is no room for them

(the size of the external archive is bounded), a check is made on the grid location to which the solution would belong. If this grid location is less densely populated than the most densely populated grid location, then a solution (randomly chosen) from this heavily populated grid location is deleted to allow the storage of the newcomer. This aims to redistribute solutions, favoring the less densely populated regions of the Pareto front. Since the procedure is adaptive, no extra parameters are required (except for the number of divisions of the objective space).

4. **Nondominated Sorting Genetic Algorithm II (NSGA-II)**: This is a heavily revised version of the Nondominated Sorting Genetic Algorithm (NSGA), which was introduced in the mid 1990s [74]. The NSGA-II adopts a more efficient ranking procedure than its predecessor. Additionally, it estimates the density of solutions surrounding a particular solution in the population by computing the average distance of two points on either side of this point along each of the objectives of the problem. This value is the so-called *crowding distance*. During selection, the NSGA-II uses a crowded-comparison operator which takes into consideration both the nondomination rank of an individual in the population and its crowding distance (i.e., nondominated solutions are preferred over dominated solutions, but between two solutions with the same nondomination rank, the one that resides in the less crowded region is preferred). The NSGA-II does not use an external archive as most of the modern MOEAs in current use. Instead, the elitist mechanism of the NSGA-II consists of combining the best parents with the best offspring obtained (i.e., a $(\mu + \lambda)$ -selection). Due to its clever mechanisms, the NSGA-II is much more efficient (computationally speaking) than its predecessor, and its performance is so good that it has become very popular in the last few years, triggering a significant number of applications, and becoming some sort of landmark against which new MOEAs have to be compared in order to merit publication.

5. **Pareto Envelope-based Selection Algorithm (PESA)**: This algorithm was proposed by Corne et al. [11], and uses a small internal population and a larger external (or secondary) population. PESA adopts the same adaptive grid from PAES to maintain diversity. However, its selection mechanism is based on the crowding measure used by

the aforementioned grid. This same crowding measure is used to decide what solutions to introduce into the external population (i.e., the archive of nondominated vectors found along the evolutionary process). Therefore, in PESA, the external memory plays a crucial role in the algorithm since it determines not only the diversity scheme, but also the selection performed by the method. There is also a revised version of this algorithm, called PESA-II [10], which is identical to PESA, except for the fact that region-based selection is used in this case. In region-based selection, the unit of selection is a hyperbox rather than an individual. The procedure consists of selecting (using any of the traditional selection techniques [31]) a hyperbox and then randomly selecting an individual within such hyperbox. The main motivation of this approach is to reduce the computational costs associated with traditional MOEAs (i.e., those based on Pareto ranking).

Many other MOEAs have been proposed in the specialized literature (see for example [9, 81, 17]), but they will not be discussed here due to obvious space limitations. A more interesting issue, however, is to devise which sort of MOEA will become predominant in the next few years. Efficiency is, for example, a concern nowadays, and several approaches have been developed in order to improve the efficiency of MOEAs (see for example [37, 41]). There is also an interesting trend consisting on designing MOEAs based on a performance measure (see for example [82, 3]). However, no clear trend exists today, from the author's perspective, that seems to attract the interest of a significant portion of the EMO community, regarding algorithmic design.

1.4 Applications

Today, there exists a very important volume of applications of MOEAs in a wide variety of domains. Next, we will provide a brief list of sample applications classified in three large groups: engineering, industrial and scientific. Specific areas within each of these large groups are also identified.

By far, engineering applications are the most popular in the current EMO literature. This is not surprising if we consider that engineering disciplines normally have problems with better understood mathematical models, which facilitates the use of MOEAs. A representative sample of engineering applications is the following:

- Electrical engineering [63, 1]
- Hydraulic engineering [62, 51]
- Structural engineering [56, 58]
- Aeronautical engineering [38, 47]
- Robotics [2, 77]
- Control [5, 6]
- Telecommunications [59, 75]
- Civil engineering [22, 36]
- Transport engineering [50, 73]

Industrial applications are the second most popular in the EMO literature. A representative sample of industrial applications of MOEAs is the following:

- Design and manufacture [33, 19]
- Scheduling [40, 29]
- Management [53, 64]

Finally, there are several EMO papers devoted to scientific applications. For obvious reasons, computer science applications are the most popular in the EMO literature. A representative sample of scientific applications is the following:

- Chemistry [60, 76]

- Physics [67, 61]
- Medicine [28, 24]
- Computer science [14, 48]

This sample of applications should give at least a rough idea of the increasing interest of researchers for adopting MOEAs in practically all types of disciplines.

1.5 Current Challenges

The existence of challenging, but solvable problems, is a key issue to preserve the interest in a research discipline. Although EMO is a discipline in which a very important amount of research has been conducted, mainly within the last ten years, several interesting problems still remain open. Additionally, the research conducted so far has also led to new, and intriguing topics. The following is a small sample of open problems that currently attract a significant amount of research within EMO:

- **Scalability:** In spite of the popularity of MOEAs in a plethora of applications, it is known that Pareto ranking is doomed to fail as we increase the number of objectives, and it is also known that with about ten objectives, it behaves like random sampling [43]. The reason is that most of the individuals in a population will become non-dominated, as the number of objectives increases. In order to deal with this problem, researchers have proposed selection schemes different from Pareto ranking [23, 18], as well as mechanisms that allow to reduce the number of objectives of a problem [4, 49]). However, there is still a lot of work to be done in this regard, and this is currently a very active research area.
- **Incorporation of user's preferences:** It is normally the case, that the user does not need the entire Pareto front of a problem, but only a certain portion of it. For example, solutions lying at the extreme parts of the Pareto front are unlikely necessary since they

represent the best value for one objective, but the worst for the others. Thus, if the user has at least a rough idea of the sort of trade-offs that aims to find it is desirable to be able to explore in more detail only the nondominated solutions within the neighborhood of such trade-offs. This is possible, if we use, for example, biased versions of Pareto ranking [13] or some multi-criteria decision making technique, from the many developed in Operations Research [7]. Nevertheless, this area has not been very actively pursued by EMO researchers, in spite of its usefulness.

- **Parallelism:** Although the use of parallel MOEAs is relatively common in certain disciplines such as aeronautical engineering [55], the lack of serious research in this area is remarkable [8, 79]. Thus, it is expected to see much more research around this topic in the next few years, for example, related to algorithmic design, the role of local search in parallel MOEAs and convergence analysis, among others.
- **Theoretical Foundations:** Although an important effort has been made in recent years to develop theoretical work related to MOEAs, in areas such as convergence [66, 80], archiving [69], algorithm complexity [54], and run-time analysis [46], a lot of work still remains to be done in this regard.

1.6 Conclusions

In this chapter, we have provided some basic concepts related to evolutionary multi-objective optimization, as well as a short description of the main multi-objective evolutionary algorithms in current use. The main application areas of such algorithms have also been included, in order to provide a better idea of their wide applicability and of the increasing interest to use them.

In the last part of the chapter, we provided a short discussion of some challenging topics that are currently very active within this research area. The main objective of this chapter

is to serve as a general (although brief) overview of the EMO field. Its main aim is to motivate researchers and newcomers from different areas, who have to deal with multi-objective problems, to consider MOEAs as a viable choice.

Acknowledgements

The author acknowledges support from CONACYT project no. 103570.

References

- [1] M.A. Abido. Multiobjective Evolutionary Algorithms for Electric Power Dispatch Problem. *IEEE Transactions on Evolutionary Computation*, 10(3):315–329, June 2006.
- [2] Gideon Avigad and Kalyanmoy Deb. The Sequential Optimization-Constraint Multi-objective Problem and its Applications for robust Planning of robot paths. In *2007 IEEE Congress on Evolutionary Computation (CEC'2007)*, pages 2101–2108, Singapore, September 2007. IEEE Press.
- [3] Nicola Beume, Boris Naujoks, and Michael Emmerich. SMS-EMOA: Multiobjective selection based on dominated hypervolume. *European Journal of Operational Research*, 181(3):1653–1669, 16 September 2007.
- [4] Dimo Brockhoff, Tobias Friedrich, Nils Hebbinghaus, Christian Klein, Frank Neumann, and Eckart Zitzler. Do Additional Objectives Make a Problem Harder? In Dirk Thierens, editor, *2007 Genetic and Evolutionary Computation Conference (GECCO'2007)*, volume 1, pages 765–772, London, UK, July 2007. ACM Press.
- [5] Martin Brown and Nicky Hutaeruk. Multi-objective optimisation for process design and control. *Measurement & Control*, 40(6):182–187, July 2007.
- [6] Genci Capi. Multiobjective evolution of neural controllers and task complexity. *IEEE Transactions on Robotics*, 23(6):1225–1234, 2007.
- [7] Carlos A. Coello Coello. Handling Preferences in Evolutionary Multiobjective Opti-

- mization: A Survey. In *2000 Congress on Evolutionary Computation*, volume 1, pages 30–37, Piscataway, New Jersey, July 2000. IEEE Service Center.
- [8] Carlos A. Coello Coello, Gary B. Lamont, and David A. Van Veldhuizen. *Evolutionary Algorithms for Solving Multi-Objective Problems*. Springer, New York, second edition, September 2007. ISBN 978-0-387-33254-3.
- [9] Carlos A. Coello Coello and Gregorio Toscano Pulido. Multiobjective Optimization using a Micro-Genetic Algorithm. In Lee Spector, Erik D. Goodman, Annie Wu, W.B. Langdon, Hans-Michael Voigt, Mitsuo Gen, Sandip Sen, Marco Dorigo, Shahram Pezeshk, Max H. Garzon, and Edmund Burke, editors, *Proceedings of the Genetic and Evolutionary Computation Conference (GECCO'2001)*, pages 274–282, San Francisco, California, 2001. Morgan Kaufmann Publishers.
- [10] David W. Corne, Nick R. Jerram, Joshua D. Knowles, and Martin J. Oates. PESA-II: Region-based Selection in Evolutionary Multiobjective Optimization. In Lee Spector, Erik D. Goodman, Annie Wu, W.B. Langdon, Hans-Michael Voigt, Mitsuo Gen, Sandip Sen, Marco Dorigo, Shahram Pezeshk, Max H. Garzon, and Edmund Burke, editors, *Proceedings of the Genetic and Evolutionary Computation Conference (GECCO'2001)*, pages 283–290, San Francisco, California, 2001. Morgan Kaufmann Publishers.
- [11] David W. Corne, Joshua D. Knowles, and Martin J. Oates. The Pareto Envelope-based Selection Algorithm for Multiobjective Optimization. In Marc Schoenauer, Kalyanmoy Deb, Günter Rudolph, Xin Yao, Evelyne Lutton, Juan Julian Merelo, and Hans-Paul Schwefel, editors, *Proceedings of the Parallel Problem Solving from Nature VI Conference*, pages 839–848, Paris, France, 2000. Springer. Lecture Notes in Computer Science No. 1917.
- [12] Xunxue Cui, Miao Li, and Tingjian Fang. Study of Population Diversity of Multiobjective Evolutionary Algorithm Based on Immune and Entropy Principles. In *Proceedings of the Congress on Evolutionary Computation 2001 (CEC'2001)*, volume 2, pages 1316–1321, Piscataway, New Jersey, May 2001. IEEE Service Center.
- [13] Dragan Cvetković and Ian C. Parmee. Preferences and their Application in Evolutionary Multiobjective Optimisation. *IEEE Transactions on Evolutionary Computation*, 6(1):42–57, February 2002.
- [14] B. de la Iglesia, G. Richards, M.S. Philpott, and V.J. Rayward-Smith. The application

- and effectiveness of a multi-objective metaheuristic algorithm for partial classification. *European Journal of Operational Research*, 169:898–917, 2006.
- [15] Kalyanmoy Deb. *Multi-Objective Optimization using Evolutionary Algorithms*. John Wiley & Sons, Chichester, UK, 2001. ISBN 0-471-87339-X.
- [16] Kalyanmoy Deb and David E. Goldberg. An Investigation of Niche and Species Formation in Genetic Function Optimization. In J. David Schaffer, editor, *Proceedings of the Third International Conference on Genetic Algorithms*, pages 42–50, San Mateo, California, June 1989. George Mason University, Morgan Kaufmann Publishers.
- [17] Kalyanmoy Deb, Manikanth Mohan, and Shikhar Mishra. Evaluating the ϵ -Domination Based Multi-Objective Evolutionary Algorithm for a Quick Computation of Pareto-Optimal Solutions. *Evolutionary Computation*, 13(4):501–525, Winter 2005.
- [18] Francesco di Pierro, Shoon-Thiam Khu, and Dragan A. Savić. An Investigation on Preference Order Ranking Scheme for Multiobjective Evolutionary Optimization. *IEEE Transactions on Evolutionary Computation*, 11(1):17–45, February 2007.
- [19] C. Dimopoulos. Explicit consideration of multiple objective in cellular manufacturing. *Engineering Optimization*, 39(5):551–565, July 2007.
- [20] Francis Ysidro Edgeworth. *Mathematical Psychics*. P. Keagan, London, England, 1881.
- [21] A.E. Eiben and J.E. Smith. *Introduction to Evolutionary Computing*. Springer, Berlin, 2003. ISBN 3-540-40184-9.
- [22] K. El-Rayes and K. Hyari. Optimal lighting arrangements for nighttime highway construction projects. *Journal of Construction Engineering and Management—ASCE*, 131(12):1292–1300, December 2005.
- [23] M. Farina and P. Amato. A fuzzy definition of “optimality” for many-criteria optimization problems. *IEEE Transactions on Systems, Man, and Cybernetics Part A—Systems and Humans*, 34(3):315–326, May 2004.
- [24] Paulo Fazendeiro, Jose Valente de Oliveira, and Witold Pedrycz. A multiobjective design of a patient and anaesthetist-friendly neuromuscular blockade controller. *IEEE Transactions on Biomedical Engineering*, 54(9):1667–1678, September 2007.
- [25] David B. Fogel. *Evolutionary Computation. Toward a New Philosophy of Machine Intelligence*. The Institute of Electrical and Electronic Engineers, New York, 1995.
- [26] Lawrence J. Fogel. *Artificial Intelligence through Simulated Evolution*. John Wiley, New

York, 1966.

- [27] Lawrence J. Fogel. *Artificial Intelligence through Simulated Evolution. Forty Years of Evolutionary Programming*. John Wiley & Sons, Inc., New York, 1999.
- [28] B. Gaal, I. Vassanyi, and G. Kozmann. A novel artificial intelligence method for weekly dietary menu planning. *Methods of Information in Medicine*, 44(5):655–664, 2005.
- [29] Martin Josef Geiger. On operators and search space topology in multi-objective flow shop scheduling. *European Journal of Operational Research*, 181(1):195–206, August 16 2007.
- [30] David E. Goldberg. *Genetic Algorithms in Search, Optimization and Machine Learning*. Addison-Wesley Publishing Company, Reading, Massachusetts, 1989.
- [31] David E. Goldberg and Kalyanmoy Deb. A Comparison of Selection Schemes Used in Genetic Algorithms. In Gregory J. E. Rawlins, editor, *Foundations of Genetic Algorithms*, pages 69–93. Morgan Kaufmann, San Mateo, California, 1991.
- [32] David E. Goldberg and Jon Richardson. Genetic algorithm with sharing for multimodal function optimization. In John J. Grefenstette, editor, *Genetic Algorithms and Their Applications: Proceedings of the Second International Conference on Genetic Algorithms*, pages 41–49, Hillsdale, New Jersey, 1987. Lawrence Erlbaum.
- [33] Ashwin Gurnani, Scott Ferguson, Kemper Lewis, and Joseph Donndelinger. A constraint-based approach to feasibility assessment in preliminary design. *AI EDAM—Artificial Intelligence for Engineering Design Analysis and Manufacturing*, 20(4):351–367, Fall 2006.
- [34] P. Hajela and C. Y. Lin. Genetic search strategies in multicriterion optimal design. *Structural Optimization*, 4:99–107, 1992.
- [35] John H. Holland. Concerning efficient adaptive systems. In M. C. Yovits, G. T. Jacobi, and G. D. Goldstein, editors, *Self-Organizing Systems—1962*, pages 215–230. Spartan Books, Washington, D.C., 1962.
- [36] K. Hyari and K. El-Rayes. Optimal planning and scheduling for repetitive construction projects. *Journal of Management in Engineering*, 22(1):11–19, 2006.
- [37] Mikkel T. Jensen. Reducing the Run-Time Complexity of Multiobjective EAs: The NSGA-II and Other Algorithms. *IEEE Transactions on Evolutionary Computation*, 7(5):503–515, October 2003.

- [38] Shinkyu Jeong, Kazuhisa Chiba, and Shigeru Obayashi. Data Mining for Aerodynamic Design Space. *Journal of Aerospace Computing, Information, and Communication*, 2:452–469, November 2005.
- [39] Hajime Kita, Yasuyuki Yabumoto, Naoki Mori, and Yoshikazu Nishikawa. Multi-Objective Optimization by Means of the Thermodynamical Genetic Algorithm. In Hans-Michael Voigt, Werner Ebeling, Ingo Rechenberg, and Hans-Paul Schwefel, editors, *Parallel Problem Solving from Nature—PPSN IV*, Lecture Notes in Computer Science, pages 504–512, Berlin, Germany, September 1996. Springer-Verlag.
- [40] Mark P. Kleeman and Gary B. Lamont. Scheduling of Flow-Shop, Job-Shop, and Combined Scheduling Problems using MOEAs with Fixed and Variable Length Chromosomes. In Keshav P. Dahal, Kay Chen Tan, and Peter I Cowling, editors, *Evolutionary Scheduling*, Studies in Computational Intelligence (SCI), pages 49–99. Springer, Berlin, 2007. ISBN 3-540-48582-1.
- [41] Joshua Knowles. ParEGO: A Hybrid Algorithm With On-Line Landscape Approximation for Expensive Multiobjective Optimization Problems. *IEEE Transactions on Evolutionary Computation*, 10(1):50–66, February 2006.
- [42] Joshua Knowles and David Corne. Properties of an Adaptive Archiving Algorithm for Storing Nondominated Vectors. *IEEE Transactions on Evolutionary Computation*, 7(2):100–116, April 2003.
- [43] Joshua Knowles and David Corne. Quantifying the Effects of Objective Space Dimension in Evolutionary Multiobjective Optimization. In Shigeru Obayashi, Kalyanmoy Deb, Carlo Poloni, Tomoyuki Hiroyasu, and Tadahiko Murata, editors, *Evolutionary Multi-Criterion Optimization, 4th International Conference, EMO 2007*, pages 757–771, Matshushima, Japan, March 2007. Springer. Lecture Notes in Computer Science Vol. 4403.
- [44] Joshua D. Knowles and David W. Corne. Approximating the Nondominated Front Using the Pareto Archived Evolution Strategy. *Evolutionary Computation*, 8(2):149–172, 2000.
- [45] Marco Laumanns, Lothar Thiele, Kalyanmoy Deb, and Eckart Zitzler. Combining Convergence and Diversity in Evolutionary Multi-objective Optimization. *Evolutionary Computation*, 10(3):263–282, Fall 2002.

- [46] Marco Laumanns, Lothar Thiele, and Eckart Zitzler. Running Time Analysis of Multiobjective Evolutionary Algorithms on Pseudo-Boolean Functions. *IEEE Transactions on Evolutionary Computation*, 8(2):170–182, April 2004.
- [47] Michèle R. Lavagna. Multi-Objective PSO for Interplanetary Trajectory Design. In Dirk Thierens, editor, *2007 Genetic and Evolutionary Computation Conference (GECCO'2007)*, volume 1, page 175, London, UK, July 2007. ACM Press.
- [48] Zne-Jung Lee, Shih-Wei Lin, Shun-Feng Su, and Chun-Yen Lin. A hybrid watermarking technique applied to digital images. *Applied Soft Computing*, 8(1):798–808, January 2008.
- [49] Antonio López Jaimes, Carlos A. Coello Coello, and Debrup Chakraborty. Objective Reduction Using a Feature Selection Technique. In *2008 Genetic and Evolutionary Computation Conference (GECCO'2008)*, pages 674–680, Atlanta, USA, July 2008. ACM Press. ISBN 978-1-60558-131-6.
- [50] H.R. Lourenço, J.P. Paixão, and R. Portugal. Multiobjective metaheuristics for the bus-driver scheduling problem. *Transportation Science*, 35(3):331–343, August 2001.
- [51] Carlos E. Mariano-Romero, Víctor H. Alcocer-Yamanaka, and Eduardo F. Morales. Multi-objective optimization of water-using systems. *European Journal of Operational Research*, 181(3):1691–1707, 16 September 2007.
- [52] Kaisa M. Miettinen. *Nonlinear Multiobjective Optimization*. Kluwer Academic Publishers, Boston, Massachusetts, 1999.
- [53] Misgana K. Muleta. *A Decision Support System for the Management of Non-Point Source Pollution from Watersheds*. PhD thesis, College of Engineering, Southern Illinois University Carbondale, February 2003.
- [54] Frank Neumann. Expected runtimes of a simple evolutionary algorithm for the multi-objective minimum spanning tree problem. *European Journal of Operational Research*, 181(3):1620–1629, 16 September 2007.
- [55] Shigeru Obayashi and Daisuke Sasaki. Multiobjective Aerodynamic Design and Visualization of Supersonic Wings by Using Adaptive Range Multiobjective Genetic Algorithms. In Carlos A. Coello Coello and Gary B. Lamont, editors, *Applications of Multi-Objective Evolutionary Algorithms*, pages 295–315. World Scientific, Singapore, 2004.

- [56] M. Ohsaki, T. Kinoshita, and P. Pan. Multiobjective heuristic approaches to seismic design of steel frames with standard sections. *Earthquake Engineering & Structural Dynamics*, 36(11):1481–1495, September 2007.
- [57] Vilfredo Pareto. *Cours D'Economie Politique*, volume I and II. F. Rouge, Lausanne, 1896.
- [58] Ricardo Perera and Antonio Ruiz. A multistage FE updating procedure for damage identification in large-scale structures based on multiobjective evolutionary optimization. *Mechanical Systems and Signal Processing*, 22(4):970–991, May 2008.
- [59] Larry Raisanen and Roger M. Whitaker. Comparison and Evaluation of Multiple Objective Genetic Algorithms for the Antenna Placement Problem. *Mobile Networks & Applications*, 10(1–2):79–88, February–April 2005.
- [60] Naveed Ramzan and Werner Witt. Multi-objective optimization in distillation unit: a case study. *Canadian Journal of Chemical Engineering*, 84(5):604–613, October 2006.
- [61] Wasim Raza and Kwang-Yong Kim. Multiobjective optimization of a wire-wrapped LMR fuel assembly. *Nuclear Technology*, 162(1):45–52, April 2008.
- [62] Patrick Reed, Joshua B. Kollat, and V.K. Deviredy. Using interactive archives in evolutionary multiobjective optimization: A case study for long-term groundwater monitoring design. *Environmental Modelling & Software*, 22(5):683–692, May 2007.
- [63] Francisco Rivas-Dávalos and Malcolm R. Irving. An Approach Based on the Strength Pareto Evolutionary Algorithm 2 for Power Distribution System Planning. In Carlos A. Coello Coello, Arturo Hernández Aguirre, and Eckart Zitzler, editors, *Evolutionary Multi-Criterion Optimization. Third International Conference, EMO 2005*, pages 707–720, Guanajuato, México, March 2005. Springer. Lecture Notes in Computer Science Vol. 3410.
- [64] Samuel Rochet and Claude Baron. An Evolutionary Algorithm for Decisional Assistance to Project Management. In Jean-Philippe Rennard, editor, *Handbook of Research on Nature Inspired Computing for Economy and Management*, volume 2, pages 444–464. Idea Group Reference, Hershey, UK, 2006. ISBN 1-59140-984-5.
- [65] R. S. Rosenberg. *Simulation of genetic populations with biochemical properties*. PhD thesis, University of Michigan, Ann Harbor, Michigan, 1967.
- [66] Günter Rudolph and Alexandru Agapie. Convergence Properties of Some Multi-

- Objective Evolutionary Algorithms. In *Proceedings of the 2000 Conference on Evolutionary Computation*, volume 2, pages 1010–1016, Piscataway, New Jersey, July 2000. IEEE Press.
- [67] Daniel E. Salazar, Claudio M. Rocco, and Enrico Zio. Robust reliability design of a nuclear system by multiple objective evolutionary optimisation. *International Journal of Nuclear Knowledge Management*, 2(3):333–345, 2007.
- [68] J. David Schaffer. Multiple Objective Optimization with Vector Evaluated Genetic Algorithms. In *Genetic Algorithms and their Applications: Proceedings of the First International Conference on Genetic Algorithms*, pages 93–100. Lawrence Erlbaum, 1985.
- [69] Oliver Schuetze, Marco Laumanns, Emilia Tantar, Carlos A. Coello Coello, and El ghazali Talbi. Convergence of Stochastic Search Algorithms to Gap-Free Pareto Front Approximations. In Dirk Thierens, editor, *2007 Genetic and Evolutionary Computation Conference (GECCO'2007)*, volume 1, pages 892–899, London, UK, July 2007. ACM Press.
- [70] Hans-Paul Schwefel. Kybernetische evolution als strategie der experimentellen forschung in der strömungstechnik. Dipl.-Ing. thesis, 1965. (in German).
- [71] Hans-Paul Schwefel. *Numerical Optimization of Computer Models*. Wiley, Chichester, UK, 1981.
- [72] K. J. Shaw and P. J. Fleming. Initial Study of Practical Multi-Objective Genetic Algorithms for Scheduling the Production of Chilled Ready Meals. In *Proceedings of Mendel'96, the 2nd International Mendel Conference on Genetic Algorithms*, Brno, Czech Republic, September 1996.
- [73] M.M. Ould Sidi, S. Hayat, S. Hammadi, and P. Borne. A novel approach to developing and evaluating regulation strategies for urban transport disrupted networks. *International Journal of Computer Integrated Manufacturing*, 21(4):480–493, 2008.
- [74] N. Srinivas and Kalyanmoy Deb. Multiobjective Optimization Using Nondominated Sorting in Genetic Algorithms. *Evolutionary Computation*, 2(3):221–248, Fall 1994.
- [75] E.G. Talbi and H. Meunier. Hierarchical parallel approach for GSM mobile network design. *Journal of Parallel and Distributed Computing*, 66(2):274–290, February 2006.
- [76] A. Tarafder, G.P. Rangaiah, and Ajay K. Ray. A study of finding many desirable solutions in multiobjective optimization of chemical processes. *Computers & Chemical*

- Engineering*, 31(10):1257–1271, October 2007.
- [77] Jason Teo, Linnie D. Neri, Minh H. Nguyen, and Hussein A. Abbass. Walking with EMO: Multi-Objective Robotics for Evolving Two, Four, and Six-Legged Locomotion. In Lam Thu Bui and Sameer Alam, editors, *Multi-Objective Optimization in Computational Intelligence: Theory and Practice*, pages 300–332. Information Science Reference, Hershey, PA, USA, 2008. ISBN 978-1-59904-498-9.
 - [78] Gregorio Toscano Pulido and Carlos A. Coello Coello. Using Clustering Techniques to Improve the Performance of a Particle Swarm Optimizer. In Kalyanmoy Deb et al., editor, *Genetic and Evolutionary Computation—GECCO 2004. Proceedings of the Genetic and Evolutionary Computation Conference. Part I*, pages 225–237, Seattle, Washington, USA, June 2004. Springer-Verlag, Lecture Notes in Computer Science Vol. 3102.
 - [79] David A. Van Veldhuizen, Jesse B. Zydallis, and Gary B. Lamont. Considerations in Engineering Parallel Multiobjective Evolutionary Algorithms. *IEEE Transactions on Evolutionary Computation*, 7(2):144–173, April 2003.
 - [80] Mario Villalobos-Arias, Carlos A. Coello Coello, and Onésimo Hernández-Lerma. Asymptotic Convergence of Metaheuristics for Multiobjective Optimization Problems. *Soft Computing*, 10(11):1001–1005, September 2006.
 - [81] Sanyou Y. Zeng, Lishan S. Kang, and Lixin X. Ding. An Orthogonal Multi-objective Evolutionary Algorithm for Multi-objective Optimization Problems with Constraints. *Evolutionary Computation*, 12(1):77–98, Spring 2004.
 - [82] Eckart Zitzler and Simon Künzli. Indicator-based Selection in Multiobjective Search. In Xin Yao et al., editor, *Parallel Problem Solving from Nature - PPSN VIII*, pages 832–842, Birmingham, UK, September 2004. Springer-Verlag. Lecture Notes in Computer Science Vol. 3242.
 - [83] Eckart Zitzler, Marco Laumanns, and Lothar Thiele. SPEA2: Improving the Strength Pareto Evolutionary Algorithm. In K. Giannakoglou, D. Tsahalis, J. Periaux, P. Papailou, and T. Fogarty, editors, *EUROGEN 2001. Evolutionary Methods for Design, Optimization and Control with Applications to Industrial Problems*, pages 95–100, Athens, Greece, 2002.
 - [84] Eckart Zitzler and Lothar Thiele. Multiobjective Evolutionary Algorithms: A Comparative Case Study and the Strength Pareto Approach. *IEEE Transactions on Evolutionary*

Computation, 3(4):257–271, November 1999.