Evolutionary Black-box Topology Optimization: Challenges and Promises

David Guirguis, Nikola Aulig, Renato Picelli, Bo Zhu, Yuqing Zhou, William Vicente, Francesco Iorio, Markus Olhofer, Wojciech Matusik, Carlos Artemio Coello Coello* and Kazuhiro Saitou

***Abstract*—Black-box topology optimization (BBTO) uses evolutionary algorithms and other soft computing techniques to generate near-optimal topologies of mechanical structures. Although evolutionary algorithms are widely used to compensate the limited applicability of conventional gradient optimization techniques, methods based on BBTO have been criticized due to numerous drawbacks. In this paper, we discuss topology optimization as a black-box optimization problem. We review the main BBTO methods, discuss their challenges and present approaches to relax them. Dealing with those challenges effectively can lead to wider applicability of topology optimization, as well as the ability to tackle industrial, highly-constrained, nonlinear, many-objective and multimodal problems. Consequently, future research in this area may open the door for innovating new applications in science and engineering that may go beyond solving classical optimization problems of structural engineering. Furthermore, algorithms designed for BBTO can be added to existing software toolboxes and packages of topology optimization.**

I. Introduction

STRUCTURAL OPTIMIZATION can be interpreted as the attempt to find optimal mechanical structures to support specific load cases respecting a set of constraints. Within this context, topology optimization aims to obtain connectivity, shape, and location of voids inside a prescribed structural design domain [1].

Topology is driven from the ancient Greek word $\tau\acute{o}\pi o\varsigma$ which means place, location, domain or space [2]. Therefore, topology optimization can be defined as the study of the efficient placing of holes inside the domain. Although, the methodology has been applied with significance in the conceptual and early design stages of mechanical structures, it can be extended to solve any problem regardless of the type of structure by using BBTO.

In the case of solid mechanical structures, the structural design domain is usually discretized into finite elements [3]. In this case, the design variables represent the presence or density of material in each finite element directly, or, in boundary description methods, are computed from the shapes of the structural layout. Topology optimization can be classified into two main categories: gradient-based topology optimization (GTO) and BBTO. GTO relies on the use of the gradient information of the objective and constraint functions. This leads to controversy among practitioners. On one hand, when using gradient information, the optimization algorithm tends to quickly (few hundreds of iterations) converge to a solution. On the other hand, BBTO implies higher computational cost, but is more flexible in application, as it can also be applied to problems where gradient information not easily obtained or not at all available.

Hence, BBTO is supposed to fill that gap in the applicability of topology optimization by approximating solutions to the problems that cannot be solved using conventional GTO. However, there are challenges that limit its effectiveness and wide use. In this paper, we discuss these challenges, presenting techniques to relax or to avoid them. Breaking through those challenges will allow BBTO to take advantage of recent advances in evolutionary computation. Hence, allowing it to extend its effectiveness to general, industrial black-box, highly-constrained, nonlinear, multimodal and multiobjective problems. Note that the application of GTO approaches to black-box problems is also possible (although not advisable in the general case) under consideration of finite differentiation approaches. In this paper, however, we focus on BBTO in the context of evolutionary algorithms[1]. Recent reviews on GTO and multi-objective, metaheuristics-based structural optimization can be found in [6], [1] and [7], [8] respectively.

II. Overview

In this section, we provide a brief survey on the main proposed methods in the literature, local and global optimization algorithms, in addition to solved problems by utilizing BBTO. Hybrid algorithms that combine sensitivity information with a

*Corresponding author

D. Guirguis is with the University of Toronto, ON M5S 3G4, Canada. This work was carried out during his visit at the University of Michigan, Ann Arbor, USA. (e-mail: dsg@mie.utoronto.ca).

N. Aulig and M. Olhofer are with Honda Research Institute Europe GmbH, Offenbach/Main, Germany (e-mails: nikola.aulig@honda-ri.de; markus.olhofer@honda-ri.de).

R. Picelli is with Cardiff School of Engineering, Cardiff University, Cardiff, CF24 3AA, United Kingdom (e-mail: PicelliR@cardiff.ac.uk).

B. Zhu and W. Matusik are with CSAIL, MIT, Cambridge, MA, USA (e-mails: boolzhu@csail.mit.edu; wojciech@mit.edu).

Y. Zhou and K. Saitou are with Mechanical Engineering, University of Michigan, Ann Arbor, USA (e-mails: yuqingz@umich.edu; kazu@umich.edu).

W. Vicente is with University of Campinas, Campinas, Brazil (e-mail: vicente@fem.unicamp.br).

F. Iorio is with Autodesk Research, Toronto, ON Canada (e-mail: francesco.iorio@autodesk.com).

C. A. Coello Coello is with CINVESTAV-IPN, Departamento de Computación (Evolutionary Computation Group), Mexico City, Mexico (e-mail: ccoello@cs.cinvestav.mx).

[1]It is important to point out that approaches known under the name (Bi-directional) Evolutionary Structural Optimization or (B)ESO [4], [5] classify as GTO and not as evolutionary algorithms, since they use gradient information and lack any features of selection and variation required for an evolutionary process in the Darwinian sense.

black-box optimization approach are out of the scope of this paper.

A. Design domain representation

The design domain is the design space that is predetermined by the user to define the allowable space to be occupied by the optimum topological structure. Initially, the domain was being discretized into uniform spaced joints and the design was represented by the members which connect these joints [9], [10] as shown in Fig. 1(a). This discrete representation is limited to truss-like or frame structures [11]. As a natural step to relax the space limitation of the discrete representation, the continuum domain formulation has emerged as an alternative to overcome its limitation over the design domain [12], [13]. The traditional continuum representation is simply a binary image formulation where the domain consists of square cells (or hexagonal, e.g., [14]) and each cell is assigned zero (void) or one (material) as illustrated in Fig. 1(b) and Fig. 2(a).



Fig. 1. Discrete representation (a) in comparison to continuum structural representation (b)

Although the binary coded representation can represent the topological details without the limitation of the discrete representation, it is associated with two main drawbacks. First, it results in stairs-like boundaries. Second, the number of decision variables is the total finite elements inside the domain. For instance, to get a fine-meshed equilateral domain of 100 elements in each direction, we would have 10,000 variables for a 2D structure and 1,000,000 variables for a 3D structure. These large-scale problems are computational prohibitive, and may need millions of function evaluations, e.g. [15]; as the total of possible solutions can be determined by the following formula:

$$\frac{N!}{M!\,(N-M)!} \tag{1}$$

where N is the total number of elements and M is the number of elements that could be filled with material according to the structure's specifications, satisfying the volume constraint. Towards relaxation of these limitations, implicit representations have been introduced to reduce the problem's scale and to allow the representation of finer topological details. The main continuum domain representations proposed are illustrated in Fig. 2. We will define them with detailed discussions 'in Section II.



Fig. 2. Illustration of main representations proposed for the structural topology: (a) bit array representation, (b) Voronoi representation, (c) dipole representation, (d) pairs of curves, (e) graph representation, (f) H-representation, (g) material-mask overlay, (h) cellular division, (i) moving morphable components (bar representation), (k) interpolated level-set functions (topology description function). A detailed dicussion on the different representations can be found in Sec. III

B. Search space exploration

Topology optimization has been intensively studied in the literature as a continuous differentiable mathematical problem. However, real-world applications can be complex, uncertain, discrete, and with conflicting objectives. The fitness functions can be of discontinuous landscapes, multimodal landscapes, contain ruggedness or flatten space [16]. The optimization problem can be straightforward, difficult or misleading [17]. Moreover, at the stage of product development, generating alternative designs and exploring their objective trade-offs are of crucial importance to reach an informative decision [18]. There are two search spaces that can be explored: the objective space (phenotype) and the space of the decision variables (genotype) [19], [20]. Gradient methods proceed with directional moves, that makes them very sensitive to the initial solution and the nature of the fitness landscape. On the other hand, black-box methods search the landscape without directed moves based on the gradients. The initial solutions and the fitness landscape impact the performance of the black-box methods as well [16], [21]. However, that influence is of a very little impact in comparison to the gradient methods and can be limited by using different mechanisms [22], [23]. The following approaches have been utilized in the literature of BBTO:

- Enhancement of the initial population [24], [25], [26], [27], [28]
- Multi-stage and multi-population evolutionary algorithms

[29], [30]
- Clustering at the objective space [24], [31], [32], [33]
- Sensitivity predictions and clustering in the state space [34], [35], [36], [37]
- Fitness sharing and speciation [38], [39], [30]
- Custom phenotype genetic operators [40], [41], [42], [43], [44], [45], [46], [47], [48]
- Generative designs [49], [50]
- Simple-to-complex evolutionary strategy [30]

C. Optimization algorithms

The selection of the optimization algorithm is crucial to achieve satisfactory results. Many factors should be considered, e.g., the nature of the fitness landscape, the correlation between the decision variables that are determined by the design domain representation, target accuracy, and the computational budget. A wide range of algorithms have been proposed in the literature starting from a population-based stochastic method e.g., [51] to a single-solution deterministic-based method e.g., [52]. Most commonly adopted optimization algorithms can be found in Table I.

For optimization of monolithic or multi-component structures, the structural connectivity is one of the non-linear constraints that should be taken into consideration [53], [54]. In addition, a structure's specifications and manufacturability are constraints that should be satisfied [54], [55], [56], [8], [57], [58], [59], [60]. Nonlinear constraints can be handled in two ways: (1) implicitly by using repair/filtering mechanisms, e.g., [61], [55], [54], [38], [62], [63], [64], [46], [65], [66] or assigning a penalty function to the objective function value, e.g., [54], [52], [30], [25], [40], and (2) coupled explicitly with the optimization algorithm [25], [67], [68], [69], [45], [70], [71], [72] incorporating constraint-handling techniques, e.g., [73], [23], [74], [75], [76], [77], [78].

D. Applications

To facilitate the application of mathematical programming and the usage of gradient methods, efforts have been exerted to devise differentiable objective functions for the problems on hand. On the other hand, the gradient-free optimization methods deal with the objective functions as black-boxes, i.e., the solver does not require the objective's gradients to proceed. Table I lists main design domain representations, optimization algorithms and applications.

Challenges of BBTO include high dimensionality, structural disconnectivity, coarse meshing, high computational cost, non-smooth boundaries, poor topological attainability, checkerboard patterns, poor quality of optimized solutions, and incapability to reproduce the results. A BBTO method is an integration of elements, where a single element may affect the performance of the whole method.

The design domain representation determines the number of variables and the correlation between them. In addition, it plays a vital role in the topological attainability and the features that can be represented in the optimized solutions [115], [128]. Most of these challenges are associated with the traditional bit-array representation. Recent BBTO methods that



Fig. 3. Level-set function representation using (a) moving morphable components and (b) Level-set function representation of interpolated fixed knots

are based on parametric level-set methods have succeeded to reduce the problem's dimensionality, generate topologies with smooth boundaries, overcoming drawbacks of checkerboard patterns, poor quality of optimized solutions, see Fig. 3. Furthermore, the attainability of high-resolution topologies with complex features is demonstrated in [128].

The role of the optimization algorithms comes next. The optimization algorithm can be selected based on the design domain formulation, the correlation between the variables, the number of conflicting objectives, the nature of constraints and the landscape of the problem's objective domain. Although the dimensionality can be significantly reduced by using effective design representations, hundreds of variables are needed to attain detailed and complex features [128]. Thus, development of optimization algorithms that are capable to deal with such a large-scale problem is crucial to advance BBTO. Advancement in hardware acceleration, e.g., GPUs and multiprocessing, can be utilized to reduce the computational expense, however, efforts to increase the computational efficiency of the optimization algorithm is still needed to make it possible for BBTO to be added to software toolboxes and commercial packages of topology optimization.

The rest of the paper is organized as follows. We will discuss different continuum formulations to represent the design domain in Section III, whereas efficient evolutionary algorithms that are recommended to solve the BBTO as a large-scale problem will be reviewed in Section IV. In Section V, we will present approaches to speed up computation using high-performance computing. In the last section, we will discuss some of example applications on topology optimization, discussing how such applications can benefit from BBTO.

III. Continuum domain formulations

The general, continuum topology optimization problem can be formulated as [6]:

$$\begin{aligned} &\min_{\rho} \; F(\mathbf{u}(\rho), \rho) \\ &\text{s.t.}: G_0(\rho) = \int_{\Omega} \rho(\mathbf{x}) dV - V_0 \leq 0 \\ &\qquad G_l(\mathbf{u}(\rho), \rho) \leq 0, \; l = 1, \ldots, L \\ &\qquad \rho(\mathbf{x}) = 0 \text{ or } 1, \; \forall \mathbf{x} \in \Omega \end{aligned} \tag{2}$$

where the density variable ρ describes the material distribution depending on location $\mathbf{x}$ in the design domain Ω and can take

TABLE I
REVIEW OF MAIN REPRESENTATIONS, ALGORITHMS AND APPLICATIONS

Design domain representations	Optimization algorithms	Applications
• Explicit bit array representation [79], [80], [51], [40], [81], [38], [82], [32], [83], [25] • Voronoi representation [84], [47], [85], [86], [87] • Dipole representation [84] • H-representation [47] • Parametric curves and graph [88], [43], [89], [90], [67], [91] • Map Lyndenmayer systems [66], [92], [93], [94] • Moving morphable components and solid geometries [84], [95], [61], [96], [71], [97] • Material mask overlay [64], [98], [99], [100], [41] • Ground element filtering and multi-resolution design variables [101], [70], [102], [103] • Spectral level-set formulation [104], [105]. • Interpolated level-sets [106], [107], [52] • Parameterized B-spline surface [108]. • State-based representation [34], [36], [37].	• Binary-coded genetic algorithms (GAs) [40], [81], [44], [38], [82], [70], [109], [110], [29], [62], [111], [112] • Branch and cut [113] • Real-coded GAs [114], [90], [64], [63], [115], [116], [88], [97] • Neuroevolution of augmenting topologies [117] • Multi-objective GAs [28], [118], [30], [55], [54], [61], [45], [32], [119], [24], [31], [120] • Population-based incremental learning [101], [121], [102], [70], [103] • Evolutionary algorithms with custom operators [44], [40], [62], [111], [19], [81] • Differential evolution [122], [123], [124] • Artificial immune systems [125], [126], [68], [127] • Hill climbing [99], [41] • Pattern search [52], [128] • Particle swarm optimization [98], [129], [130], [131] • Simulated annealing [65], [70], [69], [102], [101] • Covariance Matrix Adaptation Evolution Strategy (CMA-ES) [34], [36], [37], [71], [132], [133], [134] • Ant colony optimization [135], [136], [137] • Constrained optimization by linear approximations (COBYLA) [104], [105], [138] • Random search [105], [138]	• Structural stiffness and/or strength [116], [51], [38], [139], [32], [29], [129], [62], [111], [140], [46] • Vehicle crashworthiness [36], [37], [71], [141] • Eigenfrequency [116], [142] • Micro-mechanical resonators [110] • Frequency selective surfaces [82], [143], [144], [145] • Magnetics [68], [146], [127] • Electromagnetics of corrugated metallic sheets [147] • Microelectronic applications [148] • Bandpass Filters [149] • Composite structures [150], [151], [152] • Butterfly valve disc [72] • Heat transfer [69], [15], [120], [153], [154], [128] • Fluid flow channels [155] • Satellite systems [156] • Multi-material and multi-component structures [157], [158], [159], [55], [48], [54], [30], [160], [128] • Optics and photonics [161], [162], [163], [133], [134] • Piezoelectric actuators [164] • Compliant mechanisms [98], [165], [45], [88], [64], [100], [157], [24], [27], [31], [166], [91] • Biomaterials [109] • Protein design [167], [168] • Stereology [169] • Resin transfer molding [56] • Helmet facemask [119] • PV panels [117] • Vibration control [94]

the value 1 for material and 0 for voids. The objective function $F(\rho, \mathbf{u}(\rho))$ is to be minimized, where $\mathbf{u}(\rho)$ is the state vector obtained from solving the governing equation and G_0 and G_l are optimization constraints with the target volume V_0. The function F represents a fairly wide variety of objective functions especially it is not limited to aggregations over the structure which is often the case in classical mechanical problems. However note that the purpose of the formulation is to provide a basis for discussion, not to formally restrict the material discussed in this article. Many of the presented approaches could also serve for extended formulations (such as formulations with more than two materials, where x can take more values than two, or multi-objective problems where F is a vector).

Typically, two major challenges have to be faced when dealing with topology optimization problems in this formulation (or extensions). The first challenge is the variability of possible solutions. For instance, in the discretized case the number of possible solutions can be quantified by a high but finite number as in (1). In general, material is freely distributed within the design domain Ω and able to form arbitrary shapes and connections. In fact, structural parts may be arbitrarily small, reaching the domain of anisotropic micro-structures i.e., there is a lack of closeness of the possible solutions [170]. In the face of this design freedom, any suitable optimization method needs a representation that is able to capture the appropriate solutions for the considered problem without over-simplifying or over-complicating it too much.

The second challenge is the computational expense for evaluations of the objective function. One evaluation typically requires at least one finite element analysis. Hence, in (2), the field $\mathbf{u}(\rho)$ associates the design space with a mathematical physics model of the addressed problem. Commonly, the corresponding differential equations are solved by numerical approaches. Depending on the application domain, often solid mechanics, the problem is typically analyzed by a linear or non-linear finite element analysis. For instance, the famous 88-line topology optimization performs a linear elastic analysis to assess the compliance and sensitivities of the structure [171]. Many linear elastic problems of moderate mesh size can be analyzed on contemporary workstations within a moderate time of a few seconds up to a few minutes. Other topology optimization problems may require responses based on non-linear analysis, such as compliant mechanisms [170] or crash problems [172], Depending on the problem, also responses based on alternate physics solvers such as heat conduction, computational fluid dynamics or multi-physics simulations might be used (see e.g., [1] for an overview). However, the simulation time may increase significantly with increasing resolution of the analysis mesh. An example is the field of crashworthiness simulations, where a single evaluation can require hours or even days to run on several machines of a computational cluster. Therefore, an *efficient* optimization approach is of critical importance for real applications, for which performing as many as hundreds of evaluations might be a serious challenge for an engineer or designer within a company.

To address the two previously indicated challenges, we

want to emphasize the importance of the parameterization of the problem in this section. While plenty of optimization algorithms are available in the literature to be used as black-box optimizers (see Section IV), at least as important as the optimization scheme, is the meaning of the optimization variables with respect to the actual design. The right choice of parameterization will adjust the variability suitably and will limit the number of variables so that an efficient optimization is possible.

Many efficient and successful optimization algorithms are originally inspired by the field of evolutionary computation. The biological inspiration is based on the concepts of "genotype" and "phenotype". The phenotype of a solution is exposed to the actual evaluation and hence the selection operator. The genotype is the underlying vector of optimization variables that are "seen" by the optimization process and modified by its variational operators. Eiben and Smith define a *representation* as a "*mapping from the phenotypes onto a set of genotypes*"[173].

Common representations are binary encodings used in genetic algorithms [174]; for instance, when a continuous number is represented as a binary number. A more natural encoding is that of a binary encoding for decision problems such as the Travelling Salesperson Problem. Other natural encodings are real-valued design variables in evolution strategies [175], [176]; which is particularly useful for engineering optimization problems.

In the context of problem (2), formally, we can describe the representation, or *encoding*, $\mathcal{R}$ as:

$$\mathcal{R} : \rho(\mathbf{x}) \rightarrow \boldsymbol{\theta} \ \forall \ \rho(\mathbf{x}) \in \mathcal{P}_{\mathcal{R}} \tag{3}$$

where $\boldsymbol{\theta} \in \mathbb{R}^M$ is the vector of design variables and $\mathcal{P}_{\mathcal{R}}$ is the set of represented phenotypes. Importantly, the number M of design variables is the dimensionality of the search space spanned by the representation.

Explicit knowledge of the encoding is not necessary. Practically, it is only necessary to implement the inverse operation, i.e., *decoding* $\mathcal{D}$:

$$\mathcal{D} : \boldsymbol{\theta} \rightarrow \rho(\mathbf{x}) \tag{4}$$

Then, a black-box optimizer can be applied to address the optimization problem (2) in the chosen representation resulting in the new formulation:

$$\begin{aligned} &\min_{\boldsymbol{\theta}} \ F_{\mathcal{D}}(\mathbf{u}(\boldsymbol{\theta}), \boldsymbol{\theta}) \\ &\text{s.t.} : G_0(\boldsymbol{\theta}) = V(\boldsymbol{\theta}) - V_0 \leq 0 \\ &\qquad G_l(\mathbf{u}(\boldsymbol{\theta}), \boldsymbol{\theta}) \leq 0, \ l = 1, \ldots, L \\ &\qquad \boldsymbol{\theta}_{\text{lo}} \leq \boldsymbol{\theta} \leq \boldsymbol{\theta}_{\text{up}} \end{aligned} \tag{5}$$

where $\boldsymbol{\theta}_{\text{lo}}$ and $\boldsymbol{\theta}_{\text{up}}$ are vectors of lower and upper bounds on the variables, $V(\boldsymbol{\theta})$ is the volume covered by material, and the $F_{\mathcal{D}}$ indicates that the function contains the wrapping to (2).

As expressed in (3) only a subset of the possible phenotypes may be represented. Therefore, a representation needs to include close-to optimum phenotypes for the given problem. This implies that choosing the representation requires some previous knowledge of favorable solutions. The representation strongly influences the fitness landscape of the problem: the choice can introduce or avoid discontinuities or smoothness and it is possible to support or restrain the capabilities of the optimizer, which may heavily affect the progress of the optimization. Representations themselves can be complex, for instance, by involving developmental steps with a small number of parameters that encode more versatile phenotypic variation (see for instance [177]). Hence, depending on the representation, the optimizer has to deal with different search spaces. A well-chosen representation facilitates beneficial changes obtained from the search operators. This is related to the topic of evolvability in the field of evolutionary computation, which captures the ability of a representation to efficiently improve solutions [178], [179], [180].

Based on this argumentation, we conclude that the representation is an essential part of the topology optimization problem and that the representation has a decisive effect on the realizability of a black-box optimization. In the following subsections, we describe known representations from the literature with assets and limitations based on three definitions of representations [181]: grid, geometric and indirect representations. Fig. 4 shows an overview of these three fundamental categories.

In this overview, as in the majority of the related literature, we focus on distributions of a single material type and voids according to (2) but extensions for several materials are imaginable by additional variables for most of the presented approaches. Similarly, most approaches only consider two-dimensional formulations but seem to be extensible to three-dimensional problems.

A. Grid Representation

We classify a representation as a "Grid Representation" if the genotype encodes properties of fixed locations in a grid that discretizes the design space [181], [37]. The grid representations include the bit-array representation which is illustrated in Fig. 2 (a). The material distribution $\rho(\mathbf{x})$ is discretized in a vector of design variables $\boldsymbol{\rho}$ with elements $\rho_i, \quad i = 1 \ldots N$. According to our proposed notation, a majority of publications are described by $\theta_i = \rho_i$, with $M = N$. Since binary representations are discussed briefly already in Sec. II-A, and quite critically in literature [182], we continue the discussion with less known geometric and indirect representations.

B. Geometric Representation

We classify a representation as "Geometric Representation" if the genotype encodes properties of a set of fixed or movable shape primitives that define the geometry of the structure within the design domain [181], [37]. These primitives, or components, can be fixed or moved around freely in the design domain, or restricted by enforcing some connectivity, for instance by relating them as nodes and edges of a graph. The number of primitives can be defined by the user or can be adaptive.

Each primitive k is defined by a number of parameters $\boldsymbol{\theta}^{(k)}$ such as coordinates, radius, length or shape parameters defining a geometric domain $\phi_k(\boldsymbol{\theta}^{(k)})$. In the most simple



Fig. 4. Three types of representations for topology optimization with evolutionary computation [181]. For increased generality, we consider a non-discretized design domain here.

cases, the area or volume defined by the domain is filled with a default material or describes a void, but of course, further parameters may determine the material properties. Assuming each primitive simply defines a geometric space filled with a default material, this can be expressed by

$$\rho(\mathbf{x}) = \begin{cases} 1 & \mathbf{x} \in \phi_k \\ 0 & \mathbf{x} \in \Omega \setminus \phi_k \end{cases} \tag{6}$$

Note, however, there are approaches, for which this relation might be inversely defined or depend on an optimization variable for the material type. In the considered case (6), however, the complete space occupied by material is given by

$$\Phi(\boldsymbol{\theta}) = \bigcup_{j=1}^{K} \phi_k(\boldsymbol{\theta}^{(k)}) \tag{7}$$

In the following, we briefly review the existing formulations.

1) Voronoi and H-representation: One of the first approaches developed as an alternative to the grid representation is the Voronoi cell parameterization proposed by Schoenauer [47], [183], [184], [185]. The genotype encodes the coordinates and the material properties of a number of Voronoi cells. Concretely, the parameters encode the Voronoi site (i.e., the center) of the Voronoi cell and an additional binary variable indicating material or void. In this way, the design domain is subdivided in a number of polyhedral-shaped subdomains. Figure 2(b). illustrates this representation. The idea was picked up later again in [84], [85] and in more recent work on the design of electromechanical devices [186], [187]. Another early geometric representation is the holes representation (or H-representation), where the material is removed in the area of a superposition of rectangular shape primitives. This was investigated by Schoenauer et al. [183], [184], [185] and, relying on their references, related, even as early as 1993 [188], [189]. The primitives are defined by four real numbers, coordinates of the center and length in both dimensions. A similar approach has been explored by Saxena et al. with the material mask overlay strategy [63], [98], in which the shape primitives are circular masks, defined by coordinates, radius and a binary variable for material. In more recent publications, this variable is defaulted to the removal of material [100], [190], [191], [192], effectively resulting in a method closely resembling the holes representation with circles instead of rectangles. The circular material mask method is shown in Fig. 2(g).

2) Level Set Method: Geometric representations define the boundary between material and void implicitly by the superposition of the shape primitives. If this boundary is defined mathematically by a superposition of basis functions, we enter the domain of level set methods for topology optimization. Level set methods define the boundary between material and void as the contour of a level set function. Often level set functions are composed of a large number of basis functions in order to also represent fine shape variations and therefore, which are typically optimized with gradient-based methods [193], [194], [195]. The basis functions, e.g. radial basis functions, can be considered as shape primitives, or a complete level set function as a parameterized shape. Hence, we can consider them geometric representations as defined in this section.

Initially, the computational cost of genetic algorithms was found to be too large when using a topology description function [196]. However, recently, methods using explicit level set functions appeared whose basis functions are suitable for BBTO. For instance, a structural boundary may be represented by a Kriging model, interpolating values of a level set function at knot points [107], [54], [52], [30]. Another approach is the Movable Morphable Components (MMC) framework, where beam shaped components define the level set boundary, hence this relates to level set methods based on geometric basis

functions [197], [198], [199], [200]. The MMC approach lead to an evolutionary level set method applied to crashworthiness topology optimization [95], [132], [96], [71], [141]. Yet another representation with more design freedom is based on closed B-splines (CBS) [201] instead of predefined beam shapes.

3) Graph Representation: For some of the mentioned geometric approaches, the shape primitives move around freely in the design domain by means of varying their coordinates. However, for many problems, material regions a concept of connectivity between the components may be useful. For instance, a geometric representation can be augmented by a graph that defines connections so that the genotype encodes locations of the nodes and properties of edges such as form or thickness. Edges may represent beams or spline curves, which are connected in the nodes.

A representation based on Bézier Curves was proposed by Tai and Chee [88], [202]. They connect loads and supports by Bézier curves and the end- and control points form the genotype. The structure is obtained by assigning material to all elements passed by the curve, where surrounding elements are added based on a thickness property of the curve. In later publications, the variables are explicitly encoded in a graph and optimized with graph specific crossovers [89], [90], [203], [204]. The graph representation with Bézier curves is shown in Fig. 5.

Although the authors focused on a graph representation using Bézier curves, they performed similar investigations also for beams instead of splines [205]. Sauter et al. proposed a similar representation using complex-shaped beams connected by a graph [206], [207]. Their approach considers straight, variable-thickness, and curved variable-thickness beams with specialized operators such as splitting and merging of beams. Another, hybrid approach, combining a grid and a geometric representation is proposed by Balamurugan et al. [62], which uses a bit array optimization that yields a skeleton starting point for a graph optimization, where the nodes are rectangles of material connected by edges defined by the skeleton. In [24], [166], the structure is defined by piecewise linear segments with different length and orientations. Recently, a constructive solid geometry is proposed by Ahmed et al. [208], [209], [61], [97]. In their work, nodes of the graph define start and end points of rectangular bar primitives and are optimized. The bars i.e. edges of the graph are obtained by Delaunay triangulation and combined by using solid modeling operators such as the constructive solid modeling union operator that yields a material domain for overlapping bars. Figure 6 shows the principle of this approach.

C. Indirect Representation

A representation classifies as an "Indirect Representation" if the genotype encodes variable properties of a generative model, which implicitly defines material locations or a geometry [181], [37]. Boundaries between geometric representations and indirect representations can be slightly blurred. For example, the geometric primitives in the Voronoi representation and level set methods are also implicitly defined. However, in contrast to a descriptive model, the genotype $\boldsymbol{\theta}$ of an indirect representation encodes properties of a more abstract process to obtain the material distribution in the structure. These parameters are, for instance, parameters of rules or a development process, possibly inspired by onto- or morphogenesis in nature. Usually, the mapping $\mathcal{D}(\boldsymbol{\theta}) \rightarrow \rho(\mathbf{x})$ can be very non-linear, possibly requiring a complex, dynamic simulation of a development process. Indirect representations known in the literature are presented in this section.

1) Lindenmayer system: Hornby used a generative Lindenmayer system (L-system) representation to evolve a family of three-dimensional table-like structures [210], [211], [212]. The L-system is a grammatical rewriting system, modeling the cellular division process of organisms, e.g., branched topology in plants. Although Hornby's work does not explicitly address a topology optimization task and no finite element analysis for evaluating the performance is used, the task of finding a table-like structure resembles a topology optimization in the sense that the distribution of material in a voxel-based design domain is optimized. Explicitly, a more recent approach uses the L-system as an indirect representation for topology optimization [213], [66]. The L-system model features successive cell division processes. The parameters that are encoded in the genotype are an axiom, production rules and additional physical and geometrical properties such as the thickness of edges. An illustration of the topology growing process is shown in Fig. 7. The topology is obtained by performing the development, starting from the axiom and successive application of the rules that lead to splits of design domain regions, where each split introduces a new edge. Besides minimum compliance, this representation has been applied to the optimization of wing designs [214], [215].

2) Gene-regulatory Network: Another biologically-inspired indirect representation was proposed by Steiner et al. [216], [217], [218], [219]. The representation encodes a gene-regulatory network that determines the behavior of a cellular growth process, where cells grow inside a design domain. The genotype is composed of parameters that form regulatory and structural units. The state of the cell and its environment influence the regulatory unit that can trigger the activation of



Fig. 5. Example of a Bézier curves representation connected by a graph [89].



Fig. 6. Example of the solid geometry modeling representation [209].

the structural units. In the basic variant, the model includes the physical interaction of cells, cellular division, and cell specialization into material and void cells [217].

An enhanced model [218] includes a chemical Gauss-shaped gradient that is used for chemotaxis, i.e. an additional force that is acting on the cells and can also be read by the regulatory units for gene activation. The gradient is pre-defined and does not change during the developmental process and can be considered as a means of providing global directional and location information. Additionally, forces on cell adherence and repellence are introduced. Figure 8 shows an example of the growing process into a topology.

3) State-based Representation: Another method for an indirect representation of the structure is to represent the design space based on the structural state [36], [37]. Every evaluation using a finite element analysis not only yields the objective function value but also detailed state information on, for instance, nodal displacements, stresses and energies that are locally related to every element. Based on this state information, groups of similar elements are obtained by clustering in the space of selected local state features. For a small number of element clusters, a low dimensional representation is obtained, where elements are close in feature space, but not necessarily close, or even connected, in the design domain. This representation is illustrated in Fig. 9. The result of optimizing this representation is used to iteratively change the structure so that the corresponding state will change and the representation is adapted when necessary. Hence, the optimization is turned into a sequence of optimizations with a lower dimensional representation. This approach forms a generic topology optimization approach, where a gradient-like optimization is performed based on a model that substitutes elements' sensitivities based on the feature input [37]. Alternative approaches to train the model are by finite differences [35] or by training of a neural network model [34], [220].

4) Compositional Pattern Producing Network: An abstraction model of a development process is proposed in the form of Compositional Pattern Producing Networks (CPPN) [221]. The CPPN avoids to explicitly model a development from a small starting point to its final form. A CPPN model is similar to an artificial neural network model. Applied for topology optimization it processes coordinate information on the finite elements in the design domain as inputs. These inputs flow through nodes with regular mathematical activation functions. The network output then determines the state of the material in the considered elements. The CPPN model, i.e. neurons, functions and their parameters are optimized with a neuro-evolution by augmenting topologies algorithm [222]. Its usage



Fig. 7. The starting point and the first three developmental steps of the cellular division process of the L-system representation [66].



Fig. 8. A cellular growth model based on motile polarized cells and voxelization [218]. The cells iteratively move, divide and specialize into a structure.



Fig. 9. State-based representation approach [36]: The structure is divided into clusters based on the structural state information obtained from the simulation.

as representation for optimizing material in a design domain, i.e. topology optimization, has been studied in two independent works [223], [117].

The concept is shown in Fig. 10.

5) Variational Autoencoder: With the recent advent of neural network models with many layers and millions of tunable parameters, these have become state of the art for many machine learning problems for which plenty of data is available, for instance in the domains of object recognition, image segmentation, and natural language processing. Based on these deep neural networks a new type of unsupervised dimensionality reduction method has become more popular, so-called Autoencoders [224]. The target of the training process is a reconstruction of the input at the output layer. The network architecture is composed of an encoder, a latent layer (a kind of bottleneck for the information) and a decoder. Hence to achieve a precise reconstruction, the low-dimensional latent layer needs to be an abstract representation that captures most information on the content. As an extension, *variational* autoencoder trains to reproduce the data by capturing the probability distribution of the input data in the latent space. In the context of topology optimization, this representation has been explored by using large datasets of topology optimization results to train the autoencoder for reconstruction of optimized structures, see Fig. 11 for an illustration. Naturally, the reconstruction quality depends on the size of the latent



Fig. 10. Example for CPPN representation, adapted from [223]. Cartesian and polar coordinates of the design space elements serve as input to a CPPN-NEAT model. The nodal activation functions are optimized and include for instance sine, Gaussian or sigmoidal functions. For each element, the output of the network specifies the material within the corresponding element.



Fig. 11. Illustration of an autoencoder network for representation of structures obtained from topology optimization, as used in [225], [154].

representation, which can be chosen freely. Yu et al. [225] use the obtained model to predict the optimal structures for given boundary conditions. Guo et al. [154] use the representation to perform optimization in latent space for a different objective function which was used to create the training data. The work in the topology domain has been restricted to two-dimensional cases but in the domain of object classification autoencoders are already applied to voxel spaces [226], which may provide insights on directions for future applications to three dimensions.

IV. Efficient evolutionary algorithms

Many types of evolutionary algorithms have been proposed over the years with the aim of addressing challenging problems such as the following:

Constrained optimization: Constraints are very common in real-world applications, and a number of constraint-handling techniques specially designed for evolutionary algorithms have been proposed. Mezura and Coello [78] categorized the constrained-handling approaches into feasibility rules, e.g., [227], stochastic ranking, e.g., [228], ε-constrained method [229], Penalty functions, [230], [231], special operators, e.g., [232], multi-objective concepts, e.g., [233], and ensemble of constraint-handling techniques, e.g., [234].

Classical topology optimization formulations as in (5), at least have to balance the material versus a structural performance metric, where one of them typically comes as constraint. Hence any algorithm applied to a topology optimization has to be able to handle constraints. Besides volume, classical constraints result are geometric, e.g. resulting from manufacturing constraints. Depending on the applied representation structural feasibility (e.g.connectivity) can be a main constraints can be handled implicitly by using repair mechanisms or explicitly by using constraint-handling techniques [25].

Multi-objective optimization: Dealing with two or more (often conflicting) objectives can be solved a different type of approach than the typical weighting schemes in GTO. Research on so-called multi-objective evolutionary algorithms (MOEAs) has flourished in the last 15 years, giving rise to a wide variety of approaches. Currently, the most popular MOEAs for few objectives (two or three) are NSGA-II [235] and MOEA/D [236]. For more than three objectives (the so-called many-objective problems), there are many proposals [237], but some frequently used MOEAs include NSGA-III [238] and SMS-EMOA [239]. A few papers solved multi-objective topology optimization problems. For instance, NSGA-II was used to minimize volume and compliance in [61], [24], and to solve a many-objective multi-component problem considering manufacturability in [55], [54]. Besides multi-physics and multi-discipline problems, typical structural problems involve several load cases, which can be considered as different objectives.

Expensive objectives: In real-world problems, it is very common to deal with expensive objective functions, whose evaluation may take minutes, hours or even days. Such problems are normally handled using surrogate methods, e.g., [240]. For instance, Efficient Global Optimization (EGO) [241] with a Kriging model is used in [155] for topology optimization of fluid problems. The selection of the surrogate model and the infill criterion is crucial for the success of the surrogate-based optimization process [242]. We refer the reader to [243], [244] for detailed discussions on opportunities for surrogate-assisted evolutionary computation, as well as [245] for parallel-based algorithms. Hybrid algorithms with integrated local searches and/or the inclusion of gradient or approximate gradient information can be an alternative for problems with computationally expensive evaluations. Such hybrid algorithms would be worth a separate review, however some examples of hybrid algorithms that use both gradients and global search methods are [36], [111], [246], [247]. A review on comparing different derivative-free algorithms, including increasing problems sizes can be found in [248].

Parallel implementation: The use of parallel computing is very common nowadays due to the increasing complexity of the problems being solved using evolutionary algorithms [249], [250]. Cantú-Paz [251] classified parallelization ways of genetic algorithms into global parallelization, coarse and fine grained parallelism, i.e., distributed GAs, in addition to hybrid parallelism. In global parallelism, there is a single population and the function evaluations of the individuals are performed in parallel. On the other hand, in coarse-grained parallelism, the population is divided into subgroups in isolated subpopulations that can be structured in different topologies of communication channels for individuals migration. In fine-grained parallel GAs, the population is partitioned into a big number of demes. Insights into theory and implementation of parallel algorithms can be found in [250].

Niching: The use of niching [252], which allows clustering together solutions that share some similarities is a useful tool when dealing with highly nonlinear problems and deceptive landscapes. Niching mechanisms are implemented in BBTO methods and showed tangible success as in [38], [39], [30]. From the application perspective, niching improves the capability of population-based algorithms to find more than just one solution. A set of conceptually different solutions to chose from can support engineers in their creative process to select the best structure according to additional criteria not obvious to the optimization as are typically present in real-world applications.

V. Speeding up computation using GPU and multiprocessing

Thanks to the advent of high-performance computing hardware and software, engineers and designers can simulate mechanical structures and physical systems governed by sophisticated mathematical models. These simulation algorithms can be further coupled with mathematical optimization frameworks to explore the optimized topology, geometry, and material layout of physical designs. The bottleneck of this pipeline lies in the process of evaluating the physical/mechanical performance (e.g., structural compliance, target deformation, etc.) given a set of system parameters, which typically requires solving a set of partial differential equations with thousands to millions of unknowns. This evaluation happens in every iteration of the optimization loop. Developing new simulation techniques, in particular, those fast and predictive approaches, play an essential role in reducing the computational cost associated with these optimization procedures. In this section, we will review a few branches of techniques to boost the efficiency of large-scale numerical simulation of complex mechanical systems, with focuses on hardware and data structures.

A. Hardware Acceleration

The most expensive step in topology optimization is the evaluation of the system's objective for the current material distribution, which usually requires solving a large-scale sparse system. The rapid development of parallel computing hardware, in particular, General-Purpose Graphics Processing Unit (GPGPU), opens up new possibilities for accelerating these solvers. A vast literature [253], [254], [255], [256], [257] has been devoted to the development of GPU-based algorithms to solve large-scale systems that are sparse, linear and symmetric positive definite.

A large variety of algorithms have been developed in the effort to extend a traditional CPU-based iterative solver, such as a preconditioned conjugate gradient solver, to its GPU implementation for direct efficiency gain. These iterative solvers are particularly suited to be implemented on a modern GPUs for parallelization. The high memory bandwidth, high peak computational throughput, and the single instruction multiple data (SIMD) architecture of the GPU hardware allow the fast implementation of several critical operations in such solver, including the matrix-free implementation of the sparse matrix-vector multiplication [258], the red-black Gauss-Seidel smoothing [259], and the geometric multi-level preconditioning [260]. The combination of these parallelization techniques in one solver enables orders of magnitude acceleration compared to its streamlined CPU counterpart, opening up possibilities to a broad range of new applications, such as real-time simulation [260], evolutionary computing [261], meshfree simulation [262], unstructured mesh simulation [263], and super-scale topology optimization with up to a billion of degrees of freedom [257]. In addition, regarding the physical equations, GPU algorithms have proved the efficiency in accelerating a diversity of applications, such as thermal conductivity [253], elastodynamics [264], and so on. In particular, the linear elastic GPU solver based on finite element discretization [254] [257] has been drawing the most attention in the topology optimization community.

Most GPU-accelerated numerical solvers run on a single GPU with relatively small data size–up to millions of unknowns with double precision–to take full advantage of GPU's high internal memory bandwidth and peak computation throughput. The communication between CPU and GPU is minimized, in order to maximize the latency of the entire system. This restriction makes scalability become one of the primary challenges for a GPU solver. For example, for a three-dimensional elastic FEM system, an NVidia GeForce GPU with 6G memory can hold the hierarchy of multigrid matrices (stored in CRS format and double precision) with up to two million elements. In contrast, a CPU-based parallel solver (e.g., the FEM solver in PETSc [265]) can scale the problem up to 83 million voxels on a cluster where memory is not the bottleneck. To reduce the memory usage on GPU, a matrix-free representation for the sparse matrix turns out to be efficient (e.g, see [266], [267]). Instead of explicitly storing the sparse matrix, a matrix-free approach reads very few parameters from memory and assembles the local matrix block on-the-fly when a linear operator such as matrix-vector multiplication is performed. Such technique (e.g., see [257]) enables high-resolution topology optimization results at the level of 14 million active FEM elements on a single Nvidia GPU with 8G memory.

For large-scale simulation problems, the development of numerical algorithms that fit GPU clusters (multiple GPUs connected by PCIe bus) or heterogeneous platforms (CPU multiprocessors enhanced by multiple GPUs) have been drawing attention in many areas. Some pioneering explorations in this direction include [268] and [269]. The key philosophy to build these hardware architecture-aware numerical algorithms is to keep the data on GPU for local computation for as long as possible, in order to minimize the data transfer cost over the PCIe bus. Different strategies have been taken on different parallization level. One strategy is to assign processors different tasks for coarse-grained parallelism. For example, in [268], multiple GPUs are assigned different computational tasks for uncertainty propagation to achieve task-level parallelism. Heterogeneous computing platforms have also demonstrated their efficacy in accelerating large-scale simulations. For example, a multigrid solver based on the Schur-Complement scheme [269] has increased the resolution to one billion active elements, on a heterogeneous CPU-GPU workstation, taking

advantage of both processors.

B. Adaptivity and Sparsity

Density [12], [270] and interface [193], [194] are the two most commonly used material representations for topology optimization. Among the various data structures that have been developed in the literature, uniform grids play an essential role in tracking the material evolution for their multiple advantages in computation. These advantages include cache-coherent memory access, regular subdivisions for parallelization, simple data layout, and, in particular, the existence of efficient numerical PDE solvers. A multigrid FEM solver discretized on a uniform grid has been established as one of the standard physical equation solvers for topology optimization (e.g. [271]).

1) Adaptivity: The main weakness of a uniform grid lies in its lack of adaptivity. To improve this, researchers inverted hierarchical data structures maintaining grid cells with different resolutions, e.g., the octree grid [273] and the AMR grid [274]. These data structures can adaptively refine a single grid cell to allocate computational resources around regions of interest. High-performance solvers [275] are combined with an octree grid to solve large-scale problems with adaptivity. Instead of adding new cells, researchers also deform grid cells, e.g., by translating [276] or bending [277] grid lines, to get finer discretizations around important regions. This strategy preserves most of the computational advantages of a uniform grid. Multiple overlapping grids with different resolutions [278] have also been used to improve the adaptivity of a uniform grid structure.

2) Sparsity: The target structures for topology optimization usually occupy a small portion of the design space, exhibiting sparse and adaptive features. A discretization taking advantage of this sparse nature has the potential in boosting the efficiency for both simulation and optimization. A wealth of sparse data structures have been invented, e.g., OpenVDB [279] and SPGrid [280], to reduce the computational cost of by maintaining active elements selectively. The essential idea is to establish an efficient mapping from a grid cell index in the real, sparse space to an index in the virtual, compact storage, enabling the allocation of computational resources only to discretizations occupied by or near the real structures. Examples of these mappings include a standard hash table (e.g., local level set [281]), an octree (e.g., adaptive distance field [282], OpenVDB [279]), or via a Virtual Memory Page Table and the Translation Lookaside Buffer (TLB) (e.g., SPGrid [280]). These data structures enable large-scale optimization. For example, Liu et al [272] invented a new narrowband grid structure to perform topology optimization for super-resolution structures (1 billion voxels) on a regular workstation.

One of main challenge remaining in the creation of efficient data structures for large-scale topology optimization applications lies in the automated co-optimization of both the discretization and the material. It is essential to allocate the computational resources in an automatic way so that the local discretizations can accommodate the modeling of smooth, complex, and thin features emerged from the background. The ultimate goal is to enable the interleaving evolutions of both structure and discretization to obtain designs with better performance.

VI. Applications

Industrial engineering design optimization problems often involve black-box simulations. More precisely, simulations of structures or systems, for which the users do not have a precise mathematical model for determining analytical sensitivities or in general a limited expertise on the complex modeling behind the simulation. Where in academia, most often analytically traceable models are considered, in industrial development processes users are often confronted with simulation models, where only partial domain knowledge is available. These models are treated often more like experimental set-ups and validated by comparison to data from real-world experiments. From an optimization perspective, these models are black boxes for which a general optimization approach independent of gradients is the possibly only option, as long as specialized optimizers are not available.

Interesting domains are for instance virtual development processes, in automotive or aerospace industries. Examples of real-world applications are simultaneous topology, shape and sizing optimisation, multidisciplinary optimization of aircraft morphing wings as well as automotive components and structures. Black-box simulation may be problems that involve simulations which are challenging due to anisotropic materials (e.g. handling of composites), multiphysics simulations (e.g. thermo-mechanical or fluid-structure couplings), and simulations of manufacturing processes (e.g. metal-sheet forming or stamping processes) or optimization constraints resulting thereof. The black-box context is especially relevant when the simulations consider transient processes that have to be addressed by explicit finite element solvers. For the mentioned types of simulations, GTO methods are not always readily available in general, even less in the industrial process, due to the non-linearities, or complexity of the simulated experiments, also with respect to boundary conditions or a multitude of involved components that deviate from the assumptions of simple academic white-box models.

A. Vehicle crashworthiness design

One interesting domain for topology optimization is the industrial vehicle development that involves the optimization of many different design stages and objectives [283], [284]. Especially crashworthiness topology optimization is a possible application for the methods proposed in this article and is currently a very active field of research. Crashworthiness simulations are an important step in the automotive development process to ensure passive safety of the vehicle while reducing the number of physical prototypes for testing. Topology optimization of these models is hindered by the significant non-linearities and transient nature of the models, for which the derivation of analytical sensitivity information cannot be easily obtained. Due to the physical and numerical simulation noise and the high computational cost of the simulation, finite-differencing approaches are often difficult to realize



Fig. 12. The evolution of SPGrid block activation for a single iteration (left) and the bird beak structure obtained on the narrowband grid (right) [272].

or infeasible, as well. Under some assumptions, sensitivity information can be obtained for instance in a ground structure approach [285], [286]. This offers a chance for future hybrid approaches as well that may be able to deal efficiently with complex crash mechanics such as material failure or very non-linear objective functions such as accelerations.

Currently, specialized heuristic methods are applied to crashworthiness topology optimization, and among them, approaches that apply evolutionary optimization. Optimization of crashworthiness has been addressed by the state-based representation optimized with evolution strategies [36], [37], the evolutionary level set method [132], [71] and a Kriging-based optimization for a domain parameterized via a thickness clustering [287]. The challenging objective functions that are tackled include for instance control of energy absorption, intrusion or acceleration characteristics. Besides the variety for crash problems, these methods could also be an alternative to existing heuristics for objective functions found in impact mechanics problems, which are dominated by even more extreme dynamics and non-linearities, see for instance [288].

B. Design under manufacturing constraints

1) General-purpose manufacturing constraint: Early works of manufacturing constraints for topology optimization were actually not originated from manufacturability concerns, rather from the numerical instability and mesh-dependency considerations. It is well-known that topology optimization in a continuum domain tends to generate numerous small holes, *a.k.a.* checkerboards [289], [290]. For GTO, regularization schemes have been developed. There are two main categories, filtering methods (*e.g.*, [291], [292]) and constraint methods (*e.g.*, [290], [293]). Recently, the PDE-based filtering method [294], [295] gained popularity due to its ease of implementation and computational efficiency. For BBTO, early works [51], [38] with explicit bitmap geometric representations suffered from the same checkerboard issues. However, recent works [107], [52] based on level-set methods have naturally eliminated checkerboard features due to their implicit geometric representations. Topology optimization with regularization schemes not only avoided numerical instabilities but generated results with much simpler geometries. The reduced shape complexity usually means better general manufacturability. In BBTO methods, manufacturing constraints can be incorporated just as any other constraints.

2) Process-specific manufacturing constraint: Manufacturing constraints modeled for specific manufacturing processes are referred to as process-specific manufacturing constraints. Such constraints are usually imposed on part geometries and more detailed than the general-purpose manufacturing constraints. There are three major advantages for BBTO to incorporate process-specific manufacturing constraints.

First, for the BBTO, intermediate topologies have clear part boundaries. Instead, for density-based GTO, intermediate topologies are mostly "blurry". Since it is straightforward to evaluate the manufacturability of topologies with clear part boundaries, process-specific manufacturing constraints can be seamlessly integrated into BBTO. For GTO, however, in order to evaluate manufacturability of "blurry" intermediate topologies, modeling simplification and numerical approximation are often required, which still remains a challenging task. For example, in order to generate simply-connected topologies for additive manufacturing, the virtual temperature method [296] has been developed to avoid the formation of enclosed cavities by constraining the maximum temperature of an additional thermal conductivity analysis. This can intuitively be achieved, in a BBTO framework, by adding a penalty term to the objective function if the intermediate topology is checked as multiply-connected.

Second, since sensitivity information is required for GTO, only differentiable constraints can be incorporated. It is true that many non-differentiable constraints can be modified and approximated as differentiable. However, such numerical treatments usually lead to less accurate modeling and potential convergence issues. In contrast, both differentiable and non-differentiable manufacturing constraints can be integrated with BBTO because sensitivity analysis is not required. For example, the resin filling time consideration for liquid composite molding process has been incorporated into BBTO [56]. Such detailed manufacturing constraint will be difficult to implement using GTO due to the challenge of obtaining its analytical sensitivity.

Lastly, it is more challenging to solve GTO with multiple manufacturing constraints. Since each manufacturing constraint model comes with approximation and simplification, the accumulation effect of multiple constraints will make the

problem even more difficult to converge, if it is possible at all. For BBTO, it is relatively straightforward to formulate such problems as multi-objective and generate Pareto frontiers to present the optimized results. Most existing manufacturability-driven GTO had only one manufacturing constraint, *e.g.* casting [297], additive manufacturing [298], [299]. Multiple manufacturing constraints have been successfully applied to BBTO [55], [54].

Continuous relaxation of BBTO problems has become an interesting research trend. For example, the multi-component topology optimization considering manufacturing and assembly cost constraints have previously been modeled as black-box problems and solved by genetic algorithms [55], [54]. A continuously relaxed gradient-based formulation for the multi-component topology optimization has recently been proposed [300], [301], which enabled efficient GTO and showed promising computational efficiency improvement. The proposed gradient-based multi-component topology optimization framework has also been applied to an additive manufacturing application considering the printer build volume, the elimination of enclosed cavities and overhangs [302]. However, problems with many nonlinear constraints such as maximum stress constraints, and process-specific manufacturing constraints are challenging for GTO where the resultant multi-modal landscapes are required to explore for comprehensive studies. These multiple local optima cannot be easily explored by GTO methods even with a multi-start strategy as the number of possible starting point can be exponentially large (same argument as BBTO regarding the number of decision variables). On the other hand, a GA with a niching method can explore their landscapes quite easily and efficiently.

C. Multiphysics applications

Exploring the trade-offs between physical properties is essential for multiphysics topology optimization problems. In particular, it is crucial to design algorithms that are capable of exploring the trade-offs of the various possible combinations of properties, such as to find metamaterials with both optimal mechanical and acoustic properties and to design soft materials with specified electromagnetic bandwidths for soft antenna designs. The numerical measurements of these different physical properties are computationally expensive, particularly when multiple PDE systems need to be solved given one specific design. These computational costs make it challenging to incorporate the simulation models into the standard gradient-based optimizers. For multi-physics optimization where each physics is evaluated by a closed computer-aided engineering package that can only be evaluated in sequence, BBTO has less difficulty in integration and coordination, although combined solver packages could solve some of these issues with GTO methods.

Gradient-free approaches, in particular, the algorithms relying on large-scale data generation and data mining, and involving human intelligence in the design loop, will potentially play a central role in designing the next-generation topology optimization algorithms for multiphysics applications. Instead of working on the optimization of materials or structures directly to achieve multiple physical performances, these algorithms rely on generating samples in a performance space spanned by the different physical properties. It requires running large-scale simulations on parallel computing platforms to obtain these physical properties in the precomputation stage. These features can be correlated, e.g., Young's modulus and Poisson's ratio, or independent, e.g., material stiffness and electrical conductivity. The trade-offs between these properties can be explored straightforwardly on the boundary of the low-dimensional manifold in the performance space. A typical example of this type of computational pipeline can be seen in [303], where multiple physical properties are explored as independent axes of the space in the data generation phase and combined to explore the trade-offs in the optimization stage. Another direction to explore these multiphysics trade-offs is to develop interactive visualization tools [304] for large-scale precomputed data. These tools provide an efficient way to incorporate human designers into the optimization loop for making decisions between multiple design objectives.

D. Design-dependent physics

Within the multiphysics applications framework, a noteworthy group of problems can be denominated as design-dependent. In such problems, the structure is interacting with one or more distinct physical fields through a well-defined interface, when in the presence of acoustic waves, fluid flow, etc., or a volume, when associated with electromagnetics, temperature variation, etc. The problem is said to be design-dependent only when the loads on the structure can change their location, direction, and magnitude during optimization due to modifications in the multiphysics interfaces or volumes.

Design-dependent problems represent a challenge for topology optimization. For example, in thermoelastic design, thermal stresses are dependent on the structural design. The current methods lead to ill-behaved optimization problems and might produce solutions that are opposed to design practices related to thermal stresses [305], [1]. Thermoelastic problems, although design-dependent, can be treated as a single physics problem when the temperature field or variation is known. Other design-dependent problems present inherent interaction between two or more physics, e.g., fluid-structure interaction (FSI). In these problems, fluid pressure and/or viscous loads are dependent on the structural boundary location and the optimization method must explicitly track the fluid-structure interfaces in order to account for accurate equilibrium. Although optimization algorithms with discrete design variables and explicitly defined boundaries, e.g., in hydrostatic loaded structures [306], acoustic-structure interaction [307], [308] and FSI with viscous fluid flow [309], [310] have used to design such systems, the potential of BBTO is yet to be explored.

VII. Conclusion

In this paper, we presented topology optimization as a black-box optimization problem. The problem is mostly studied in the literature based on the traditional binary-coded formulation for minimum compliance. However, the subject of problem formulation is rich in innovation and different formulations

have been proposed to diminish the design space for more efficient and effective optimization. Having said that, the design representation should be formulated considering topological attainability and how the topological details affect optimality of the achievable solutions.

The BBTO can be considered as an application of large-scale global optimization. However, the problem is mostly studied using standard evolutionary algorithms that may not perform efficiently with high dimensionality. To advance this topic of research, it is crucial to develop global search algorithms that are capable to deal efficiently with high-dimensional complex problems. We provided some examples of algorithms and techniques that can be utilized in BBTO methods.

Furthermore, we presented various techniques to speed up computation at software and hardware levels. The increasing trend in using multi-core processors, in personal and portable computers, makes the issue of computational cost less significant than before. BBTO can be considered as a complement to topology optimization, filling the gap in the applicability of GTO for new or non-conventional problems. Thus, we reviewed some example applications including crashworthiness design, design for manufacturability, multiphysics, and design dependent physics. Finally, we can conclude that although recent advancements succeeded to overcome major challenges of BBTO, the existing literature is still long far from fully utilizing all advances in evolutionary computation and high-performance computing. More empirical studies using the presented methods are needed to increase the community's knowledge on their best usage.

Appendix

Image matching can be used to study the topological attainability, e.g., [115], [128]. In Figs. 13 and 14, we show the capability of advanced representations to attain complex features with low to moderate numbers of decision variables by using image matching and FEA. The results show the effectiveness of geometric representations that we discussed in Section III to attain complex features and to relax the limitation of coarse meshing.



Fig. 13. Assessment of the topological attainability via image matching: (a) optimized topologies to obtain the image of reference topology (at the top-right corners) using Kriging interpolated level-sets with simple GA [115]; (b) high-resolution optimized topologies to obtain highly detailed images using the derivative-free level-set method [128]



Fig. 14. Topological attainability of the gradient-free level-set formulation of the MMCs [132], [71] by using FEA with CMA-ES

Acknowledgment

Renato Picelli acknowledges the financial support by the São Paulo Research Foundation (FAPESP), grant number [2018/05797-8]. Carlos A. Coello Coello gratefully acknowledges support from CONACyT project no. 2016-01-1920.

References

[1] J. D. Deaton and R. V. Grandhi, "A survey of structural and multidisciplinary continuum topology optimization: post 2000," *Structural and Multidisciplinary Optimization*, vol. 49, no. 1, pp. 1–38, 2014.

[2] H. A. Eschenauer and N. Olhoff, "Topology optimization of continuum structures: A review," *Applied mechanics reviews*, vol. 54, no. 4, p. 331, 2001.

[3] G. I. N. Rozvany, "A critical review of established methods of structural topology optimization," *Structural and Multidisciplinary Optimization*, vol. 37, no. 3, pp. 217–237, Jan. 2009.

[4] Y. Xie and G. P. Steven, "A simple evolutionary procedure for structural optimization," *Computers & structures*, vol. 49, no. 5, pp. 885–896, 1993.

[5] X. Huang and Y. Xie, *Evolutionary Topology Optimization of continuum structures*. John Wiley & Sons, 2012.

[6] O. Sigmund and K. Maute, "Topology optimization approaches," *Structural and Multidisciplinary Optimization*, vol. 48, no. 6, pp. 1031–1055, 2013.

[7] G. R. Zavala *et al.*, "A survey of multi-objective metaheuristics applied to structural optimization," *Structural and Multidisciplinary Optimization*, vol. 49, no. 4, pp. 537–558, 2013.

[8] R. Kicinger *et al.*, "Evolutionary computation and structural design: A survey of the state-of-the-art," *Comput Struct*, vol. 83, pp. 1943–1978, Sep. 2005.

[9] W. S. Dorn *et al.*, "Automatic design of optimal structures," *Journal de Mecanique*, vol. 3, pp. 25–52, 1964.

[10] G. I. N. Rozvany *et al.*, "Layout optimization of structures," *Applied mechanics reviews*, vol. 48, no. 2, p. 41, 1995.

[11] A. G. M. Michell, "Lviii. the limits of economy of material in frame-structures," *Philosophical Magazine Series 6*, vol. 8, no. 47, pp. 589–597, Nov. 1904.

[12] M. P. Bendsøe, "Optimal shape design as a material distribution problem," *Structural Optimization*, vol. 1, no. 4, pp. 193–202, 1989.

[13] M. Bendsøe and N. Kikuchi, "Generating optimal topologies in optimal design using a homogenization method," *Computer Methods in Applied Mechanics and Engineering*, vol. 71, pp. 197–224, 1988.

[14] R. Saxena and A. Saxena, "On honeycomb representation and sigmoid material assignment in optimal topology synthesis of compliant mechanisms," *Finite Elements in Analysis and Design*, vol. 43, no. 14, pp. 1082–1098, Oct. 2007.

[15] R. Boichot and Y. Fan, "A genetic algorithm for topology optimization of area-to-point heat conduction problem," *International Journal of Thermal Sciences*, vol. 108, pp. 209–217, Oct. 2016.

[16] G. Lu *et al.*, "Fitness landscapes and problem difficulty in evolutionary algorithms: from theory to applications," in *Recent advances in the theory and application of fitness landscapes*, H. Richter and A. Engelbrecht, Eds. Berlin, Heidelberg: Springer Berlin Heidelberg, 2014, pp. 133–152.

[17] T. F. Jones and Stephanie, *Fitness Distance Correlation as a Measure of Problem Difficulty for Genetic Algorithms*. Morgan Kaufmann Publishers Inc., 1995.

[18] E. Bradner *et al.*, "Parameters tell the design story: Ideation and abstraction in design optimization," in *SimAUD 2014 Conference proceedings, Tampa, Florida, US*, 2014.

[19] C. Kane and M. Schoenauer, "Topological optimum design using genetic algorithms," *Control and Cybernetics*, vol. 25, pp. 1059–1088, 1996.

[20] D. B. Fogel, *Evolutionary Computation*. John Wiley & Sons, Inc, 2005.

[21] K. E. Kinnear, "Fitness landscapes and difficulty in genetic programming," in *Proceedings of the First IEEE Conference on Evolutionary Computation*, 1994, pp. 142–147.

[22] E. K. Burke *et al.*, "Diversity in genetic programming: an analysis of measures and correlation with fitness," *IEEE Transactions on Evolutionary Computation*, vol. 8, no. 1, pp. 47–62, Feb. 2004.

[23] Z. Michalewicz, *Genetic algorithms + data structures = evolution programs (3rd ed.)*. Springer-Verlag, 1996.

[24] D. Sharma *et al.*, "Domain-specific initial population strategy for compliant mechanisms using customized genetic algorithm," *Structural and Multidisciplinary Optimization*, vol. 43, no. 4, pp. 541–554, 2011.

[25] S. Wang and K. Tai, "Structural topology design optimization using genetic algorithms with a bit-array representation," *Computer Methods in Applied Mechanics and Engineering*, vol. 194, no. 36-38, pp. 3749 – 3770, 2005.

[26] S. Y. Wang and K. Tai, "A bit-array representation ga for structural topology optimization," in *The 2003 Congress on Evolutionary Computation*, 2003, pp. 671–677.

[27] D. Sharma *et al.*, "An improved initial population strategy for compliant mechanism designs using evolutionary optimization," in *ASME 2008 International Design Engineering Technical Conferences and Computers and Information in Engineering Conference*. American Society of Mechanical Engineers, 2008, pp. 1175–1184.

[28] J. A. Madeira *et al.*, "Multiobjective topology optimization of structures using genetic algorithms with chromosome repairing," *Structural and Multidisciplinary Optimization*, vol. 32, no. 1, pp. 31–39, 2006.

[29] R. Balamurugan *et al.*, "Performance evaluation of a two stage adaptive genetic algorithm (TSAGA) in structural topology optimization," *Applied soft computing*, vol. 8, no. 4, pp. 1607–1624, Sep. 2008.

[30] D. Guirguis and M. F. Aly, "An evolutionary multi-objective topology optimization framework for welded structures," in *Evolutionary Computation (CEC), 2016 IEEE Congress on*. IEEE, 2016, pp. 372–378.

[31] D. Sharma *et al.*, "Customized evolutionary optimization procedure for generating minimum weight compliant mechanisms," *Engineering Optimization*, vol. 46, no. 1, pp. 39–60, Jan. 2014.

[32] K. Deb and T. Goel, "Multi-objective evolutionary algorithms for engineering shape design," in *Evolutionary Optimization, Boston*. Kluwer Academic Publishers, 2003, pp. 147–175.

[33] D. Sharma *et al.*, "Towards generating diverse topologies of path tracing compliant mechanisms using a local search based multi-objective genetic algorithm procedure," in *2008 IEEE Congress on Evolutionary Computation (IEEE World Congress on Computational Intelligence)*, June 2008, pp. 2004–2011.

[34] N. Aulig and M. Olhofer, "Neuro-evolutionary topology optimization of structures by utilizing local state features," in *Proceedings of the 2014 Conference on Genetic and Evolutionary Computation*, ser. GECCO '14. New York, NY, USA: ACM, 2014, pp. 967–974.

[35] N. Aulig and M. Olhofer, "Topology optimization by predicting sensitivities based on local state features," in *5th. European Conference on Computational Mechanics (ECCM V)*, Barcelona, Spain, 2014.

[36] N. Aulig and M. Olhofer, "State-based representation for structural topology optimization and application to crashworthiness," in *Evolutionary Computation (CEC), 2016 IEEE Congress on*, Vancouver, BC, Canada, July 2016, pp. 1642–1649.

[37] N. Aulig, "Generic topology optimization based on local state features," Ph.D. dissertation, TU Darmstadt, Düsseldorf, 2017.

[38] M. J. Jakiela *et al.*, "Continuum structural topology design with genetic algorithms," *Comput Methods Appl Mech Eng*, vol. 186, pp. 31–43, Jun. 2000.

[39] J. W. Duda, *clustering and other genetic algorithm improvements for structural topology optimization*. Doctoral dissertation, Massachusetts Institute of Technology, 1996.

[40] C. Kane and M. Schoenauer, *Genetic operators for two-dimentional shape optimization*. Berlin, Heidelberg: Springer Berlin Heidelberg, 1996, pp. 355–369.

[41] P. Sharma and A. Saxena, "On evaluation of adaptive mask overlay topology synthesis method using different mask shapes," in *34th Annual Mechanisms and Robotics Conference, Parts A and B*, 2010, vol. 2, pp. 665–674.

[42] D. Sharma *et al.*, "A domain-specific crossover and a helper objective for generating minimum weight compliant mechanisms," in *proceedings of Genetic and Evolutionary Computation Conference (GECCO), Atlanta, Georgia, USA*, 2008, pp. 1723–1724.

[43] S. Akhtar *et al.*, "Topology optimization of compliant mechanisms using evolutionary algorithm with design geometry encoded as a graph," in *Volume 2: 28th Design Automation Conference*, Montreal, Quebec, Canada, 2002, vol. 2:28th, pp. 1047–1055.

[44] P. J. Baron *et al.*, "A voxel-based representation for the evolutionary shape optimisation of a simplified beam: A case-study of a problem-centred approach to genetic operator design," in *Soft computing in engineering design and manufacturing*, P. K. Chawdhry *et al.*, Eds. London: Springer London, 1998, pp. 251–258.

[45] N. F. Wang and X. M. Zhang, "Topology optimization of compliant mechanisms using pairs of curves," *Engineering Optimization*, vol. 47, no. 11, pp. 1497–1522, Nov. 2015.

[46] D. W. Fanjoy and W. A. Crossley, "Topology design of planar cross-sections with a genetic algorithm: Part 1–overcoming the obstacles," *Engineering Optimization*, vol. 34, no. 1, pp. 1–22, Jan. 2002.

[47] M. Schoenauer, "Shape representations and evolution schemes," in *Proceedings of the 5th Annual Conference on Evolutionary Programming*, 1996.

[48] Z. Zhou *et al.*, "Decomposition templates and joint morphing operators for genetic algorithm optimization of multicomponent structural topology," *Journal of Mechanical Design*, vol. 136, no. 2, p. 021004, Dec. 2013.

[49] G. S. Hornby, *Generative representations for evolving families of designs*. Springer-Verlag, 2003.

[50] M. H. Kobayashi, "On a biologically inspired topology optimization method," *Communications in Nonlinear Science and Numerical Simulation*, vol. 15, no. 3, pp. 787–802, Mar. 2010.

[51] C. D. Chapman *et al.*, "Genetic algorithms as an approach to configuration and topology design," *Journal of Mechanical Design*, vol. 116, no. 4, pp. 1005–1012, 1994.

[52] D. Guirguis and M. F. Aly, "A derivative-free level-set method for topology optimization," *Finite Elements in Analysis and Design*, vol. 120, pp. 41–56, Nov. 2016.

[53] S. Y. Wang *et al.*, "An enhanced genetic algorithm for structural topology optimization," *International Journal for Numerical Methods in Engineering*, vol. 65, no. 1, pp. 18–44, 2006.

[54] D. Guirguis *et al.*, "Multi-objective topology optimization of multi-component continuum structures via a Kriging-interpolated level set approach," *Structural and Multidisciplinary Optimization*, vol. 51, no. 3, pp. 733–748, Mar. 2015.

[55] A. R. Yildiz and K. Saitou, "Topology synthesis of multicomponent structural assemblies in continuum domains," *Journal of Mechanical Design*, vol. 133, no. 1, p. 011008, 2011.

[56] Y. Zhou and K. Saitou, "Topology optimization of composite structures with data-driven resin filling time manufacturing constraint," *Structural and Multidisciplinary Optimization*, vol. 55, no. 6, pp. 2073–2086, 2017.

[57] S. L. Vatanabe *et al.*, "Topology optimization with manufacturing constraints: A unified projection-based approach," *Advances in Engineering Software*, vol. 100, pp. 97–112, Oct. 2016.

[58] O. Sigmund, "On topology optimization with manufacturing constraints," in *III European Conference on Computational Mechanics*. Springer, 2006, pp. 497–497.

[59] J. Liu and Y. Ma, "A survey of manufacturing oriented topology optimization methods," *Advances in Engineering Software*, vol. 100, pp. 161–175, Oct. 2016.

[60] R. Roy *et al.*, "Recent advances in engineering design optimisation: Challenges and future trends," *CIRP Annals*, vol. 57, no. 2, pp. 697–715, 2008.

[61] F. Ahmed *et al.*, "Structural topology optimization using multi-objective genetic algorithm with constructive solid geometry representation," *Applied Soft Computing*, vol. 39, pp. 240–250, 2016.

[62] R. Balamurugan *et al.*, "A two phase approach based on skeleton convergence and geometric variables for topology optimization using genetic algorithm," *Structural and Multidisciplinary Optimization*, vol. 43, no. 3, pp. 381–404, Mar. 2011.

[63] A. Saxena, "On optimization of 2d compliant mechanisms using honeycomb discretization with material-mask overlay strategy," in *ASME 2007 International Design Engineering Technical Conferences and Computers and Information in Engineering Conference*, vol. Volume 6: 33rd Design Automation Conference, Parts A and B. American Society of Mechanical Engineers, 2007, pp. 1331–1341.

[64] A. Saxena, "A material-mask overlay strategy for continuum topology optimization of compliant mechanisms using honeycomb discretization," *Journal of Mechanical Design*, vol. 130, no. 8, p. 082304, 2008.

[65] P. Y. Shim and S. Manoochehri, "Generating optimal configurations in structural design using simulated annealing," *Int J Numer Methods Eng*, vol. 40, no. 6, pp. 1053–1069, Mar. 1997.

[66] H.-T. C. Pedro and M. H. Kobayashi, "On a cellular division method for topology optimization," *Int J Numer Methods Eng*, vol. 88, no. 11, pp. 1175–1197, 2011.

[67] H. Zhou and K. L. Ting, "Shape and size synthesis of compliant mechanisms using wide curve theory," *Journal of Mechanical Design*, vol. 128, no. 3, p. 551, 2006.

[68] K. Watanabe *et al.*, "Optimization of inductors using evolutionary algorithms and its experimental validation," *IEEE Trans Magn*, vol. 46, no. 8, pp. 3393–3396, Aug. 2010.

[69] G. Anagnostou *et al.*, "A computational procedure for part design," *Comput Methods Appl Mech Eng*, vol. 97, no. 1, pp. 33–48, May 1992.

[70] S. Bureerat and T. Kunakote, "Topological design of structures using population-based optimization methods," *Inverse Probl Sci Eng*, vol. 14, no. 6, pp. 589–607, Sep. 2006.

[71] M. Bujny *et al.*, "Identification of optimal topologies for crashworthiness with the evolutionary level set method," *International Journal of Crashworthiness*, pp. 1–22, 2017.

[72] S. C. Caraballo *et al.*, "Optimization of a butterfly valve disc using 3D topology and genetic algorithms," *Structural and Multidisciplinary Optimization*, pp. 1–17, May 2017.

[73] C. A. C. Coello, "Theoretical and numerical constraint-handling techniques used with evolutionary algorithms: a survey of the state of the art," *Comput Methods Appl Mech Eng*, vol. 191, pp. 1245–1287, Jan. 2002.

[74] Z. Michalewicz, "Genetic algorithms, numerical optimization, and constraints," in *Proceedings of the Sixth International Conference on Genetic Algorithms*. Morgan Kaufmann, 1995, pp. 151–158.

[75] C. A. C. Coello and E. M. Montes, "Constraint-handling in genetic algorithms through the use of dominance-based tournament selection," *Advanced Engineering Informatics*, vol. 16, no. 3, pp. 193–203, 2002.

[76] K. Deb, "An efficient constraint handling method for genetic algorithms," *Comput Methods Appl Mech Eng*, vol. 186, pp. 311–338, Jun. 2000.

[77] Z. Michalewicz and M. Schoenauer, "Evolutionary algorithms for constrained parameter optimization problems," *Evol Comput*, vol. 4, no. 1, pp. 1–32, 1996.

[78] E. Mezura-Montes and C. A. Coello Coello, "Constraint-Handling in Nature-Inspired Numerical Optimization: Past, Present and Future," *Swarm and Evolutionary Computation*, vol. 1, no. 4, pp. 173–194, December 2011.

[79] E. Sandgren *et al.*, "Topological design of structural components using genetic optimization methods," in *Sensitivity Analysis and Optimization with Numerical Methods, Dallas, TX*, 1990, vol. 115l, pp. 31–43.

[80] E. Sandgren and E. Jensen, "Automotive structural design employing a genetic optimization algorithm," in *SAE Technical Paper Series*, 1992, vol. 400.

[81] J. W. Duda and M. J. Jakiela, "Generation and classification of structural topologies with genetic algorithm speciation," *Journal of Mechanical Design*, vol. 119, no. 1, p. 127, 1997.

[82] S. Chakravarty *et al.*, "Application of a microgenetic algorithm (mga) to the design of broadband microwave absorbers using multiple frequency selective surface screens buried in dielectrics," *IEEE Transactions on Antennas and Propagation*, vol. 50, no. 3, pp. 284–296, 2002.

[83] Y. Kim and O. De Weck, "Progressive structural topology optimization by variable chromosome length genetic algorithm," in *China-Japan-Korea Joint Symposium on Optimization of Structural and Mechanical Systems, M3*, 2004.

[84] H. Hamda *et al.*, "Compact unstructured representations for evolutionary design," *Applied Intelligence*, vol. 16, no. 2, pp. 139–155, Mar. 2002.

[85] H. Hamda and M. Schoenauer, "Topological optimum design with evolutionary algorithms," *Journal of convex analysis*, vol. 9, no. 2, pp. 503–518, 2002.

[86] F. Mansanne *et al.*, *Evolutionary algorithms as fitness function debuggers*. presented at the International Symposium on Methodologies for Intelligent Systems, 1999.

[87] M. Schoenauer *et al.*, "Non-parametric identification of geological models," in *1998 IEEE International Conference on Evolutionary Computation Proceedings*, 1998, pp. 136–141.

[88] K. Tai and T. Chee, "Design of structures and compliant mechanisms by evolutionary optimization of morphological representations of topology," *Journal of Mechanical Design*, vol. 122, no. 4, pp. 560–566, 2000.

[89] S. Wang and K. Tai, "Graph representation for structural topology optimization using genetic algorithms," *Computers & Structures*, vol. 82, no. 20-21, pp. 1609 – 1622, 2004.

[90] K. Tai and S. Akhtar, "Structural topology optimization using a genetic algorithm with a morphological geometric representation scheme," *Structural and Multidisciplinary Optimization*, vol. 30, no. 2, pp. 113–127, 2005.

[91] N. Wang and X. Zhang, "Compliant mechanisms design based on pairs of curves," *Science China Technological Sciences*, vol. 55, no. 8, pp. 2099–2106, Aug. 2012.

[92] T. J. Ikonen and A. Sobester, "Two variations to the map l-systems-based topology optimization method," in *17th AIAA Aviation Technology, Integration, and Operations Conference, Reston, Virginia*, 2017.

[93] A. Khetan *et al.*, "Managing variable-dimension structural optimization problems using generative algorithms," *Structural and Multidisciplinary Optimization*, vol. 52, no. 4, pp. 695–715, 2015.

[94] E. Sabbatini *et al.*, "Vibration reduction using biologically inspired topology optimization method: optimal stiffeners distribution on an acoustically excited plate," *Journal of Vibration and Control*, vol. 21, no. 7, pp. 1398–1412, May 2015.

[95] M. Bujny, "Development of a hybrid evolutionary approach for level set topology optimization," Master's thesis, Technische Universität München, 2015.

[96] M. Bujny *et al.*, "Hybrid evolutionary approach for level set topology optimization," in *Evolutionary Computation (CEC), 2016 IEEE Congress on*. IEEE, 2016, pp. 5092–5099.

[97] A. Pandey *et al.*, "Topology optimization of compliant structures and mechanisms using constructive solid geometry for 2-d and 3-d applications," *Soft Computing*, vol. 21, no. 5, pp. 1157–1179, Mar 2017.

[98] N. Padhye, "Topology optimization of compliant mechanism using multi-objective particle swarm optimization," in *Proceedings of the 2008 GECCO conference companion on Genetic and evolutionary computation (GECCO), New York, USA*, 2008, p. 1831.

[99] P. Kumar *et al.*, "Synthesis of c0 path-generating contact-aided compliant mechanisms using the material mask overlay method," *Journal of Mechanical Design*, vol. 138, no. 6, p. 062301, Apr. 2016.

[100] C. Jain and A. Saxena, "An improved material-mask overlay strategy for topology optimization of structures and compliant mechanisms," *Journal of Mechanical Design*, vol. 132, no. 6, p. 061006, 2010.

[101] S. Bureerat and J. Limtragool, "Performance enhancement of evolutionary search for structural topology optimisation," *Finite Elements in Analysis and Design*, vol. 42, no. 6, pp. 547 – 566, 2006.

[102] S. Bureerat and J. Limtragool, "Structural topology optimisation using simulated annealing with multiresolution design variables," *Finite Elements in Analysis and Design*, vol. 44, no. 12, pp. 738 – 747, 2008.

[103] S. Sleesongsom and S. Bureerat, "Topology optimisation using mpbils and multi-grid ground element," *Applied Sciences*, vol. 8, no. 2, 2018.

[104] A. A. Gomes and A. Suleman, "Topology optimization of a reinforced wing box for enhanced roll maneuvers," *AIAA Journal*, vol. 46, no. 3, pp. 548–556, Mar. 2008.

[105] A. A. Gomes and A. Suleman, "Application of spectral level set methodology in topology optimization," *Structural and Multidisciplinary Optimization*, vol. 31, no. 6, pp. 430–443, 2006.

[106] M. J. de Ruiter and F. van Keulen, "Topology optimization using a topology description function," *Structural and Multidisciplinary Optimization*, vol. 26, no. 6, pp. 406–416, Apr. 2004.

[107] K. Hamza *et al.*, "A kriging-interpolated level-set approach for structural topology optimization," *Journal of Mechanical Design*, vol. 136, no. 1, p. 011008, 2013.

[108] I. Pehnec *et al.*, "Evolutionary topology opimization using parameterized b-spline surface," in *VII European Congress on Computational Methods in Applied Sciences and Engineering, Crete Island, Greece*, 2016.

[109] X. Guo and H. Gao, "Bio-inspired material design and optimization," in *IUTAM symposium on topological design optimization of structures, machines and materials*, M. P. Bendsoe *et al.*, Eds., 2006, pp. 439–453.

[110] W. He *et al.*, "Topology optimization in micromechanical resonator design," *Optimization and Engineering*, vol. 13, no. 2, pp. 271–292, Jun. 2012.

[111] C. Y. Wu and C. C. Ku, "Stress-enhanced clonal selection algorithm for structural topology optimization," *International Journal for Numerical Methods in Engineering*, vol. 89, no. 8, pp. 957–974, 2012.

[112] H. Zhou and R. B. Patil, "The discrete topology optimization of structures using the improved hybrid discretization model," *Journal of Mechanical Design*, vol. 134, no. 12, p. 124503, Nov. 2012.

[113] M. Stolpe and M. P. Bendsøe, "Global optima for the zhou–rozvany problem," *Structural and Multidisciplinary Optimization*, vol. 43, no. 2, pp. 151–164, 2011.

[114] E. Kita and H. Tanie, "Topology and shape optimization of continuum structures using GA and BEM," *Structural optimization*, vol. 17, no. 2, pp. 130–139, Apr 1999.

[115] D. Guirguis *et al.*, "Image Matching Assessment of Attainable Topology via Kriging-Interpolated Level-Sets," in *ASME 2014 International Design Engineering Technical Conferences and Computers and Information in Engineering Conference*, 2014, vol. 2A:, p. V02AT03A002.

[116] J. Madeira *et al.*, "Ga topology optimization using random keys for tree encoding of structures," *Structural and Multidisciplinary Optimization*, vol. 40, no. 1-6, pp. 227–240, 2010.

[117] R. Evins *et al.*, "Multi-material compositional pattern-producing networks for form optimisation," in *European Conference on the Applications of Evolutionary Computation*. Springer, 2014, pp. 189–200.

[118] J. A. Madeira *et al.*, "Multi-objective optimization of structures topology by genetic algorithms," *Advances in Engineering Software*, vol. 36, no. 1, pp. 21–28, 2005.

[119] K. L. Johnson *et al.*, "Constrained topological optimization of a football helmet facemask based on brain response," *Mater Des*, vol. 111, pp. 108–118, 2016.

[120] K. Maneeratana *et al.*, "Co-operative co-evolutionary genetic algorithms for multi-objective topology design," *Computer-aided design and applications*, vol. 2, p. 487496, Jan. 2005.

[121] T. Kunakote and S. Bureerat, "Multi-objective topology optimization using evolutionary algorithms," *Engineering Optimization*, vol. 43, no. 5, pp. 541–557, 2011.

[122] C. Y. Wu and K. Y. Tseng, "Stress-based binary differential evolution for topology optimization of structures," *Proceedings of the Institution of Mechanical Engineers, Part C: Journal of Mechanical Engineering Science*, vol. 224, no. 2, pp. 443–457, Feb. 2010.

[123] C. Y. Wu and K. Y. Tseng, "Engineering optimization using modified binary differential evolution algorithm," in *2010 Third International Joint Conference on Computational Science and Optimization*, 2010, pp. 501–505.

[124] C. Y. Wu and K. Y. Tseng, "Topology optimization of structures using modified binary differential evolution," *Structural and Multidisciplinary Optimization*, vol. 42, no. 6, pp. 939–953, Dec. 2010.

[125] G.-C. Luh and C.-H. Chueh, "Multi-modal topological optimization of structure using immune algorithm," *Computer Methods in Applied Mechanics and Engineering*, vol. 193, no. 36, pp. 4035–4055, 2004.

[126] C.-Y. Wu and C.-C. Ku, "Optimizaton using clonal selection algorithm and immune memory based on self-organizing map," in *2013 International Conference on Machine Learning and Cybernetics*, 2013, pp. 1224–1229.

[127] F. Campelo *et al.*, "3d topology optimization using an immune algorithm," *COMPEL: The International Journal for Computation and Mathematics in Electrical and Electronic Engineering*, vol. 26, no. 3, pp. 677–688, 2007.

[128] D. Guirguis *et al.*, "High-resolution non-gradient topology optimization," *Journal of Computational Physics*, vol. 372, pp. 107 – 125, 2018.

[129] C. B. Zhang and C. Y. Wu, "An enhanced binary particle swarm optimization for structural topology optimization," *Proceedings of the Institution of Mechanical Engineers, Part C: Journal of Mechanical Engineering Science*, vol. 224, no. 10, pp. 2271–2287, Oct. 2010.

[130] G.-C. Luh *et al.*, "A binary particle swarm optimization for continuum structural topology optimization," *Applied Soft Computing*, vol. 11, no. 2, pp. 2833 – 2844, 2011, the Impact of Soft Computing for the Progress of Artificial Intelligence.

[131] G. C. Luh and C. Y. Lin, "A binary particle swarm optimization for structural topology optimization," in *2010 Third International Joint Conference on Computational Science and Optimization*, 2010, pp. 395–399.

[132] M. Bujny *et al.*, "Evolutionary level set method for crashworthiness topology optimization," in *Proceedings of the VII European Congress on Computational Methods in Applied Sciences and Engineering (ECCOMAS Congress 2016), Athens*, 2016, pp. 309–322.

[133] G. Fujii *et al.*, "Direct-current electric invisibility through topology optimization," *Journal of Applied Physics*, vol. 123, no. 23, p. 233102, 2018.

[134] G. Fujii *et al.*, "Exploring optimal topology of thermal cloaks by CMA-ES," *Applied Physics Letters*, vol. 112, no. 6, p. 061108, 2018.

[135] S. Kim *et al.*, "Development of modified ant colony optimization algorithm for compliant mechanisms," in *The Fourth International Conference on Advances in System Simulation*, 2012.

[136] K. S. Yoo and S. Y. Han, "Modified ant colony optimization for topology optimization of geometrically nonlinear structures," *International Journal of Precision Engineering and Manufacturing*, vol. 15, no. 4, pp. 679–687, Apr. 2014.

[137] K. S. Yoo and S. Y. Han, "Topology optimum design of compliant mechanisms using modified ant colony optimization," *Journal of Mechanical Science and Technology*, vol. 29, no. 8, pp. 3321–3327, Aug. 2015.

[138] A. A. Gomes and A. Suleman, "Spectral level set methodology in MDO," in *45th AIAA/ASME/ASCE/AHS/ASC Structures, Structural Dynamics & Materials Conference, Reston, Virigina*, 2004.

[139] C. D. Chapman and M. J. Jakiela, "Genetic algorithm-based structural topology design with compliance and topology simplification considerations," *Journal of Mechanical Design*, vol. 118, no. 1, p. 89, 1996.

[140] D. W. Fanjoy and W. A. Crossley, "Topology design of planar cross-sections with a genetic algorithm: Part 2–bending, torsion and combined loading applications," *Engineering Optimization*, vol. 34, no. 1, pp. 49–64, Jan. 2002.

[141] E. Raponi *et al.*, *Kriging-guided Level Set Method for Crash Topology Optimization*. 7th GACM Colloquium on Computational Mechanics for Young Scientists from Academia and Industry, Stuttgart, Germany, 2017.

[142] N. Tanlak, "Topological indentation pattern design of plates for maximum frequency gap," *Structural and Multidisciplinary Optimization*, vol. 57, no. 3, pp. 995–1003, 2018.

[143] J. A. Bossard *et al.*, "The design and fabrication of planar multiband metallodielectric frequency selective surfaces for infrared applications," *IEEE Trans Antennas Propag*, vol. 54, no. 4, pp. 1265–1276, Apr. 2006.

[144] S. Cui *et al.*, "Novel planar electromagnetic absorber designs using genetic algorithms," *IEEE Trans Antennas Propag*, vol. 54, no. 6, pp. 1811–1817, Jun. 2006.

[145] J. A. Bossard *et al.*, "A novel design methodology for reconfigurable frequency selective surfaces using genetic algorithms," *IEEE Trans Antennas Propag*, vol. 53, no. 4, pp. 1390–1400, Apr. 2005.

[146] J. Denies *et al.*, "Study of a topology optimization tool associating a hybrid algorithm with a voronoi-based formalism for the design of electromagnetic devices," in *The XIX International Conference on Electrical Machines - ICEM 2010*, 2010, pp. 1–6.

[147] A. Altnoklu *et al.*, "Electromagnetic optimization of corrugated metallic sheets for maximum power focusing," *Journal of Electromagnetic Waves and Applications*, vol. 31, no. 8, pp. 837–849, May 2017.

[148] X.-S. Yang *et al.*, "Bat algorithm for topology optimization in microelectronic applications," in *The First International Conference on Future Generation Communication Technologies*, 2012, pp. 150–155.

[149] M.-I. Lai and S.-K. Jeng, "Compact microstrip dual-band bandpass filters design using genetic-algorithm techniques," *IEEE Trans Microw Theory Tech*, vol. 54, no. 1, pp. 160–168, Jan. 2006.

[150] D. C. Keller, *Evolutionary design of laminated composite structures*. Doctoral dissertation, ETH Zurich, 2010.

[151] S. Zein *et al.*, "A repair operator for the preliminary design of a composite structure using genetic algorithms," *Structural and Multidisciplinary Optimization*, vol. 55, no. 6, pp. 2099–2110, Jun. 2017.

[152] E. D. Goodman *et al.*, "Parallel genetic algorithms in the optimization of composite structures," in *Soft computing in engineering design and*

manufacturing, P. K. Chawdhry *et al.*, Eds. London: Springer London, 1998, pp. 199–208.

[153] D. J. Lohan *et al.*, "Topology optimization for heat conduction using generative design algorithms," *Structural and Multidisciplinary Optimization*, vol. 55, no. 3, pp. 1063–1077, Mar. 2017.

[154] T. Guo *et al.*, "An indirect design representation for topology optimization using variational autoencoder and style transfer," in *2018 AIAA/ASCE/AHS/ASC Structures, Structural Dynamics, and Materials Conference*, 2018, p. 0804.

[155] M. Yoshimura *et al.*, "Topology optimization of fluid problems using genetic algorithm assisted by the Kriging model," *Int J Numer Methods Eng*, vol. 109, no. 4, pp. 514–532, 2016.

[156] N. Y. Kawabata, *A biologically inspired methodology for multidisciplinary topology optimization*. Masters thesis, 2012.

[157] A. Saxena, "On multiple-material optimal compliant topologies: Discrete variable parameterization using genetic algorithm," in *27th Biennial Mechanisms and Robotics Conference*, 2002, vol. 5, pp. 85–96.

[158] N. Lyu and K. Saitou, "Topology optimization of multi-component structures via decomposition-based assembly synthesis," in *29th Design Automation Conference, Parts A and B*, 2003, vol. 2, pp. 269–281.

[159] Z. Zhou *et al.*, "Multi-objective topology optimization of spot-welded planar multi-component continuum structures," in *9th world congress on structural and multidisciplinary optimization, Shizuoka, Japan*, 2011.

[160] Q. Li *et al.*, "Evolutionary structural optimization for connection topology design of multicomponent systems," *Engineering Computations*, vol. 18, no. 3, pp. 460–479, 2001.

[161] S. Yu *et al.*, "Topology optimization for light-trapping structure in solar cells," *Structural and Multidisciplinary Optimization*, vol. 50, no. 3, pp. 367–382, Sep. 2014.

[162] C. Wang *et al.*, "Highly efficient light-trapping structure design inspired by natural evolution," *Sci Rep*, vol. 3, p. 1025, Jan. 2013.

[163] L. Xie *et al.*, "Topology optimization of phononic crystals with uncertainties," *Structural and Multidisciplinary Optimization*, vol. 56, no. 6, pp. 1319–1339, 2017.

[164] M.-R. Akbarzadeh-T *et al.*, "Adaptive fuzzy fitness granulation for evolutionary optimization," *International Journal of Approximate Reasoning*, vol. 49, no. 3, pp. 523–538, 2008.

[165] C. Jain and A. Saxena, "On an adaptive multi-mask overlay strategy for topology optimization of structures and compliant mechanisms," in *On an Adaptive Multi-Mask Overlay Strategy for Topology Optimization of Structures and Compliant Mechanisms*, 2009, vol. 7:33rd, pp. 171–181.

[166] D. Sharma and K. Deb, "Generation of compliant mechanisms using hybrid genetic algorithm," *Journal of The Institution of Engineers (India): Series C*, vol. 95, no. 4, pp. 295–307, 2014.

[167] J. D. Szustakowski and Z. Weng, "Protein structure alignment using a genetic algorithm." *Proteins*, vol. 38, no. 4, pp. 428–440, Mar. 2000.

[168] B. Kolbeck *et al.*, "Connectivity independent protein-structure alignment: a hierarchical approach," *BMC Bioinformatics*, vol. 7, p. 510, Nov. 2006.

[169] D. Basanta *et al.*, "Using genetic algorithms to evolve three-dimensional microstructures from two-dimensional micrographs," *Metallurgical and Materials Transactions A*, vol. 36, no. 7, pp. 1643–1652, 2005.

[170] M. Bendsøe and O. Sigmund, *Topology Optimization Theory, Methods and Applications*, 2nd ed. Springer Verlag Berlin, 2004.

[171] E. Andreassen *et al.*, "Efficient topology optimization in MATLAB using 88 lines of code," *Structural and Multidisciplinary Optimization*, vol. 43, no. 1, pp. 1–16, 2011.

[172] N. M. Patel *et al.*, "Crashworthiness design using topology optimization," *Journal of Mechanical Design*, vol. 131, p. 061013, 2009.

[173] A. E. Eiben and J. E. Smith, *Introduction to Evolutionary Computing*. Springer Berlin Heidelberg, 2003.

[174] D. Beasley *et al.*, "An overview of genetic algorithms: Part 1, fundamentals," *University computing*, vol. 15, no. 2, pp. 56–69, 1993.

[175] I. Rechenberg, *Evolutionsstrategie - Optimierung technischer Systeme nach Prinzipien der biologischen Evolution*. Fommann-Holzboog, 1973.

[176] T. Bäck *et al.*, *Contemporarey Evolution Strategies*, ser. 1619-7127. Springer Verlagg Berlinn Heidelberg, 2013.

[177] R. Dawkins, *The blind watchmaker*. New York: Norton, 1986.

[178] N. Aulig, "Evolutionary optimization of the robustness and evolvability of design solutions," Diploma thesis, Technische Universität Darmstadt, 2011.

[179] T. Hu and W. Banzhaf, "Evolvability and speed of evolutionary algorithms in light of recent developments in biology," *Journal of Artificial Evolution and Applications*, 2010.

[180] R. Dawkins, "The evolution of evolvability," in *On Growth, Form and Computers*, S. Kumar, Ed. San Diego, CA: Elsevier, 2003, pp. 239 – 255.

[181] N. Aulig and M. Olhofer, "Evolutionary computation for topology optimization of mechanical structures: An overview of representations," in *Evolutionary Computation (CEC), 2016 IEEE Congress on*, Vancouver, BC, Canada, July 2016, pp. 1948–1955.

[182] O. Sigmund, "On the usefulness of non-gradient approaches in topology optimization," *Structural and Multidisciplinary Optimization*, vol. 43, pp. 589–596, 2011.

[183] M. Schoenauer *et al.*, "Mechanical inclusions identification by evolutionary computation," *Revue européenne des éléments finis*, vol. 5, no. 5-6, pp. 619–648, 1996.

[184] M. Schoenauer *et al.*, "Identification of mechanical inclusions," in *Evolutionary Algorithms in Engineering Applications*, D. Dasgupta and Z. Michalewicz, Eds. Berlin, Heidelberg: Springer, 1997, pp. 479–496.

[185] L. Kallel and M. Schoenauer, "Fitness distance correlation for variable length representations," Technical Report 363, CMAP, Ecole Polytechnique, Tech. Rep., 1996.

[186] J. Denies *et al.*, "Genetic algorithm-based topology optimization: Performance improvement through dynamic evolution of the population size," in *Power Electronics, Electrical Drives, Automation and Motion (SPEEDAM), 2012 International Symposium on*. IEEE, 2012, pp. 1033–1038.

[187] J. Denies, "Métaheuristiques pour l'optimisation topologique: application à la conception de dispositifs électromagnétiques," Ph.D. dissertation, École normale supérieure de Cachan-ENS Cachan, 2013.

[188] J. Dejonghe, "Allègement de platines métalliques par algorithmes génétiques," Palaiseau, Rapport de stage d'option B2 de l'Ecole Polytechnique, 1993.

[189] M. Seguin, "Optimisation de formes par évolution artificielle. etude de deux représentations," Rapport de DEA d'Analyse Numérique de l'Université de Paris VI, Tech. Rep., 1995.

[190] A. Saxena, "An adaptive material mask overlay method: Modifications and investigations on binary, well connected robust compliant continua," *J. Mech. Des*, vol. 133, no. 4, p. 041004, 2011.

[191] A. Saxena, "Are circular shaped masks adequate in adaptive mask overlay topology synthesis method?" *Journal of Mechanical Design*, vol. 133, no. 1, p. 011001, 2011.

[192] A. Saxena, "Topology design with negative masks using gradient search," *Structural and Multidisciplinary Optimization*, vol. 44, no. 5, pp. 629–649, 2011.

[193] M. Y. Wang *et al.*, "A level set method for structural topology optimization," *Computer Methods in Applied Mechanics and Engineering*, vol. 192, no. 12, 2003.

[194] G. Allaire *et al.*, "Structural optimization using sensitivity analysis and a level-set method," *Journal of computational physics*, vol. 194, no. 1, pp. 363–393, 2004.

[195] N. P. van Dijk *et al.*, "Level-set methods for structural topology optimization: a review," *Structural and Multidisciplinary Optimization*, vol. 48, no. 3, pp. 437–472, 2013.

[196] M. De Ruiter and F. Van Keulen, "Topology optimization using a topology description function," *Structural and Multidisciplinary Optimization*, vol. 26, no. 6, pp. 406–416, 2004.

[197] X. Guo *et al.*, "Doing topology optimization explicitly and geometricallya new moving morphable components based framework," *Journal of Applied Mechanics*, vol. 81, no. 8, p. 081009, 2014.

[198] X. Guo *et al.*, "Explicit structural topology optimization based on moving morphable components (mmc) with curved skeletons," *Computer Methods in Applied Mechanics and Engineering*, vol. 310, pp. 711–748, 2016.

[199] W. Zhang *et al.*, "A new topology optimization approach based on moving morphable components (MMC) and the ersatz material model," *Structural and Multidisciplinary Optimization*, vol. 53, no. 6, pp. 1243–1260, 2016.

[200] W. Zhang *et al.*, "Structural complexity control in topology optimization via moving morphable component (MMC) approach," *Structural and Multidisciplinary Optimization*, vol. 56, no. 3, pp. 535–552, 2017.

[201] W. Zhang *et al.*, "Cbs-based topology optimization including design-dependent body loads," *Computer Methods in Applied Mechanics and Engineering*, 2017.

[202] K. Tai *et al.*, "Design synthesis of path generating compliant mechanisms by evolutionary optimization of topology and shape," *Journal of Mechanical Design*, vol. 124, no. 3, pp. 492–500, 2002.

[203] N. Wang and K. Tai, "Target matching problems and an adaptive constraint strategy for multiobjective design optimization using genetic

algorithms," *Computers & Structures*, vol. 88, no. 19-20, pp. 1064 – 1076, 2010.

[204] N. F. Wang *et al.*, "A hybrid genetic algorithm for constrained multi-objective optimization under uncertainty and target matching problems," *Applied Soft Computing*, vol. 13, no. 8, pp. 3636–3645, 2013.

[205] S. Wang and K. Tai, "Bar-system representation for topology optimization using genetic algorithms," *Engineering Computations*, vol. 22, no. 2, pp. 206–231, 2005.

[206] M. Sauter, "A graph-based optimization method for the design of compliant mechanisms and structures," Ph.D. dissertation, Swiss Federal Institute of Technology Zurich, 2008.

[207] M. Sauter *et al.*, "Complex-shaped beam element and graph-based optimization of compliant mechanisms," *Structural and Multidisciplinary Optimization*, vol. 36, no. 4, pp. 429–442, 2008.

[208] F. Ahmed *et al.*, "Structural topology optimization using multi-objective genetic algorithm with constructive solid geometry representation," Department of Mechanical Engineering Indian Institute of Technology, Kanpur 208016, India, KanGAL Report 2012018, November 2012.

[209] F. Ahmed *et al.*, "Constructive solid geometry based topology optimization using evolutionary algorithm," in *Proceedings of Seventh International Conference on Bio-Inspired Computing: Theories and Applications (BIC-TA 2012)*, ser. Advances in Intelligent Systems and Computing, J. C. Bansal *et al.*, Eds. Springer India, 2013, vol. 201, pp. 227–238.

[210] G. S. Hornby, "Generative representations for evolutionary design automation," Ph.D. dissertation, Citeseer, 2003.

[211] G. S. Hornby, "Creating complex building blocks through generative representations," *Proceedings of the 2003 AAAI Spring Symposioum: Computational Synthesis: From Basic Building Blocks to High Level Functionality, American Association for Artificial Intelligence, AAAI Press*, pp. 98–105, 2003.

[212] G. S. Hornby, "Generative representations for evolving families of designs," in *Genetic and Evolutionary Computation - GECCO 2003*. Springer, 2003, pp. 1678–1689.

[213] M. H. Kobayashi *et al.*, "On a cellular division method for aircraft structural design," *The Aeronautical Journal*, vol. 113, pp. 821–831, 2009.

[214] B. Stanford *et al.*, "Aeroelastic optimization of flapping wing venation: A cellular division approach," *AIAA Journal*, vol. 50, no. 4, pp. 938–951, 2012.

[215] B. Stanford *et al.*, "Simultaneous topology optimization of membrane wings and their compliant flapping mechanisms," *AIAA Journal*, vol. 51, no. 6, pp. 1431–1441, 2013.

[216] M. Brenn, "Dreidimensionale topologieoptimierung mit hilfe eines zellwachstummodells," Master's thesis, Technische Universität Darmstadt, 2008.

[217] T. Steiner *et al.*, "A cellular model for the evolutionary development of lightweight material with an inner structure," in *Proceedings of the Genetic and Evolutionary Computation Conference (GECCO 2008)*. New York, NY, USA: ACM, 2008.

[218] T. Steiner *et al.*, "Global shape with morphogen gradients and motile polarized cells," in *Proceedings of the 2009 IEEE Congress on Evolutionary Computation, Trondheim*. IEEE, 2009.

[219] T. Steiner, "Artificial evolutionary development," Ph.D. dissertation, Universität Bielefeld, 2010.

[220] N. Aulig and M. Olhofer, "Neuro-evolutionary topology optimization with adaptive improvement threshold," in *Applications of Evolutionary Computation*, ser. Lecture Notes in Computer Science, A. M. Mora and G. Squillero, Eds. Springer International Publishing, 2015, vol. 9028, pp. 655–666.

[221] K. O. Stanley, "Compositional pattern producing networks: A novel abstraction of development," *Genetic programming and evolvable machines*, vol. 8, no. 2, pp. 131–162, 2007.

[222] K. O. Stanley and R. Miikkulainen, "Evolving neural networks through augmenting topologies," *Evolutionary computation*, vol. 10, no. 2, pp. 99–127, 2002.

[223] N. Cheney *et al.*, "Automated vibrational design and natural frequency tuning of multi-material structures," in *Proceedings of the 2014 Conference on Genetic and Evolutionary Computation*, ser. GECCO '14. New York, NY, USA: ACM, 2014, pp. 1079–1086.

[224] G. E. Hinton and R. R. Salakhutdinov, "Reducing the dimensionality of data with neural networks," *science*, vol. 313, no. 5786, pp. 504–507, 2006.

[225] Y. Yu *et al.*, "Deep learning for topology optimization design," *arXiv preprint arXiv:1801.05463*, 2018.

[226] A. Brock *et al.*, "Generative and discriminative voxel modeling with convolutional neural networks," *arXiv preprint arXiv:1608.04236*, 2016.

[227] E. Mezura-Montes and C. A. C. Coello, "A simple multimembered evolution strategy to solve constrained optimization problems," *IEEE Transactions on Evolutionary Computation*, vol. 9, no. 1, pp. 1–17, 2005.

[228] T. P. Runarsson and X. Yao, "Stochastic ranking for constrained evolutionary optimization," *IEEE Transactions on Evolutionary Computation*, vol. 4, no. 3, pp. 284–294, 2000.

[229] T. Takahama and S. Sakai, "Constrained optimization by the ε constrained differential evolution with gradient-based mutation and feasible elites," in *2006 IEEE International Conference on Evolutionary Computation*, July 2006, pp. 1–8.

[230] A. Homaifar *et al.*, "Constrained optimization via genetic algorithms," *SIMULATION*, vol. 62, no. 4, pp. 242–253, 1994.

[231] J. A. Joines and C. R. Houck, "On the use of non-stationary penalty functions to solve nonlinear constrained optimization problems with ga's," in *Proceedings of the First IEEE Conference on Evolutionary Computation. IEEE World Congress on Computational Intelligence*, vol. 2, 1994, pp. 579–584.

[232] H. Lu and W. Chen, "Self-adaptive velocity particle swarm optimization for solving constrained optimization problems," *Journal of Global Optimization*, vol. 41, no. 3, pp. 427–445, Jul 2008.

[233] Y. Wang *et al.*, "An adaptive tradeoff model for constrained evolutionary optimization," *IEEE Transactions on Evolutionary Computation*, vol. 12, no. 1, pp. 80–92, 2008.

[234] R. Mallipeddi and P. N. Suganthan, "Ensemble of constraint handling techniques," *IEEE Transactions on Evolutionary Computation*, vol. 14, no. 4, pp. 561–579, 2010.

[235] K. Deb *et al.*, "A Fast and Elitist Multiobjective Genetic Algorithm: NSGA–II," *IEEE Transactions on Evolutionary Computation*, vol. 6, no. 2, pp. 182–197, April 2002.

[236] Q. Zhang and H. Li, "MOEA/D: A Multiobjective Evolutionary Algorithm Based on Decomposition," *IEEE Transactions on Evolutionary Computation*, vol. 11, no. 6, pp. 712–731, December 2007.

[237] B. Li *et al.*, "Many-Objective Evolutionary Algorithms: A Survey," *ACM Computing Surveys*, vol. 48, no. 1, September 2015.

[238] K. Deb and H. Jain, "An Evolutionary Many-Objective Optimization Algorithm Using Reference-Point-Based Nondominated Sorting Approach, Part I: Solving Problems With Box Constraints," *IEEE Transactions on Evolutionary Computation*, vol. 18, no. 4, pp. 577–601, August 2014.

[239] N. Beume *et al.*, "SMS-EMOA: Multiobjective selection based on dominated hypervolume," *European Journal of Operational Research*, vol. 181, no. 3, pp. 1653–1669, 16 September 2007.

[240] F. A. C. Viana *et al.*, "Special section on multidisciplinary design optimization: Metamodeling in multidisciplinary design optimization: How far have we really come?" *AIAA Journal*, vol. 52, no. 4, pp. 670–690, Apr. 2014.

[241] D. R. Jones *et al.*, "Efficient global optimization of expensive black-box functions," *Journal of Global Optimization*, vol. 13, no. 4, pp. 455–492, 1998.

[242] A. I. Forrester and A. J. Keane, "Recent advances in surrogate-based optimization," *Progress in Aerospace Sciences*, vol. 45, no. 1-3, pp. 50–79, Jan. 2009.

[243] Y. Jin, "Surrogate-assisted evolutionary computation: Recent advances and future challenges," *Swarm and Evolutionary Computation*, vol. 1, no. 2, pp. 61 – 70, 2011.

[244] Y. Jin *et al.*, "Data-driven evolutionary optimization: An overview and case studies," *IEEE Transactions on Evolutionary Computation*, pp. 1–1, 2018.

[245] R. T. Haftka *et al.*, "Parallel surrogate-assisted global optimization with expensive functions – a survey," *Structural and Multidisciplinary Optimization*, vol. 54, no. 1, pp. 3–13, Jul 2016.

[246] N. Garcia-Lopez *et al.*, "A hybrid topology optimization methodology combining simulated annealing and SIMP," *Computers & Structures*, vol. 89, no. 15–16, pp. 1512–1522, Jan. 2011.

[247] N. Pholdee and S. Bureerat, "Performance enhancement of multiobjective evolutionary optimisers for truss design using an approximate gradient," *Computers & Structures*, vol. 106, pp. 115–124, 2012.

[248] L. M. Rios and N. V. Sahinidis, "Derivative-free optimization: a review of algorithms and comparison of software implementations," *Journal of Global Optimization*, vol. 56, no. 3, pp. 1247–1293, Jul 2013.

[249] D. Sudholt, "Parallel Evolutionary Algorithms," in *Springer Handbook of Computational Intelligence*, J. Kacprzyk and W. Pedrycz, Eds. Springer, 2015, pp. 929–959, iSBN 978-3-662-43504-5.

[250] E. Alba and M. Tomassini, "Parallelism and evolutionary algorithms," *IEEE Transactions on Evolutionary Computation*, vol. 6, no. 5, pp. 443–462, 2002.

[251] E. Cant-Paz, "A summary of research on parallel genetic algorithms," in *IlliGAL Report no 95007*. University of Illinois at Urbana-Champaign, 1995.

[252] Y.-H. Zhang *et al.*, "Toward Fast Niching Evolutionary Algorithms: A Locality Sensitive Hashing-Based Approach," *IEEE Transactions on Evolutionary Computation*, vol. 21, no. 3, pp. 347–362, 2017.

[253] E. Wadbro and M. Berggren, "Megapixel topology optimization on a graphics processing unit," *SIAM review*, vol. 51, no. 4, pp. 707–721, 2009.

[254] S. Schmidt and V. Schulz, "A 2589 line topology optimization code written for the graphics card," *Computing and Visualization in Science*, vol. 14, no. 6, pp. 249–256, 2011.

[255] V. J. Challis *et al.*, "High resolution topology optimization using graphics processing units (gpus)," *Structural and Multidisciplinary Optimization*, vol. 49, no. 2, pp. 315–325, 2014.

[256] L. S. Duarte *et al.*, "Polytop++: an efficient alternative for serial and parallel topology optimization on cpus & gpus," *Structural and Multidisciplinary Optimization*, vol. 52, no. 5, pp. 845–859, 2015.

[257] J. Wu *et al.*, "A system for high-resolution topology optimization," *IEEE transactions on visualization and computer graphics*, vol. 22, no. 3, pp. 1195–1208, 2016.

[258] J. Wong *et al.*, "A new sparse matrix vector multiplication graphics processing unit algorithm designed for finite element problems," *Int J Numer Methods Eng*, vol. 102, no. 12, pp. 1784–1814, 2015.

[259] J. T. Liu *et al.*, "A gpu accelerated red-black sor algorithm for computational fluid dynamics problems," in *Advanced Materials Research*, vol. 320. Trans Tech Publ, 2011, pp. 335–340.

[260] C. Dick *et al.*, "A real-time multigrid finite hexahedra method for elasticity simulation using cuda," *Simulation Modelling Practice and Theory*, vol. 19, no. 2, 2011.

[261] J. Martínez-Frutos and D. Herrero-Pérez, "Gpu acceleration for evolutionary topology optimization of continuum structures using isosurfaces," *Computers & Structures*, vol. 182, pp. 119–136, 2017.

[262] A. Karatarakis *et al.*, "Gpu-acceleration of stiffness matrix calculation and efficient initialization of efg meshless methods," *Computer Methods in Applied Mechanics and Engineering*, vol. 258, pp. 63–80, 2013.

[263] T. Zegard and G. H. Paulino, "Toward gpu accelerated topology optimization on unstructured meshes," *Structural and multidisciplinary optimization*, vol. 48, no. 3, pp. 473–485, 2013.

[264] P. Huthwaite, "Accelerated finite element elastodynamic simulations using the gpu," *Journal of Computational Physics*, vol. 257, pp. 687–707, 2014.

[265] N. Aage *et al.*, "Topology optimization using petsc: An easy-to-use, fully parallel, open source topology optimization framework," *Structural and Multidisciplinary Optimization*, vol. 51, no. 3, pp. 565–572, 2015.

[266] P. Yadav and K. Suresh, "Large scale finite element analysis via assembly-free deflated conjugate gradient," *Journal of Computing and Information Science in Engineering*, vol. 14, no. 4, p. 041008, 2014.

[267] J. Martínez-Frutos *et al.*, "Fine-grained gpu implementation of assembly-free iterative solver for finite element problems," *Computers & Structures*, vol. 157, pp. 9–18, 2015.

[268] J. Martínez-Frutos and D. Herrero-Pérez, "Large-scale robust topology optimization using multi-gpu systems," *Computer Methods in Applied Mechanics and Engineering*, vol. 311, pp. 393–414, 2016.

[269] H. Liu *et al.*, "A scalable schur-complement fluids solver for heterogeneous compute platforms," *ACM Trans. Graph.*, vol. 35, no. 6, p. 201, 2016.

[270] M. Zhou and G. Rozvany, "The coc algorithm, part ii: topological, geometrical and generalized shape optimization," *Computer Methods in Applied Mechanics and Engineering*, vol. 89, no. 1, pp. 309–336, 1991.

[271] O. Sigmund and S. Torquato, "Design of smart composite materials using topology optimization," *Smart Materials and Structures*, vol. 8, no. 3, p. 365, 1999.

[272] H. Liu *et al.*, "Narrow-band topology optimization on a sparsely populated grid," *ACM Trans. Graph.*, vol. 37, no. 6, 2018.

[273] F. Losasso *et al.*, "Simulating water and smoke with an octree data structure," *ACM Trans. Graph.*, vol. 23, no. 3, pp. 457–462, 2004.

[274] J. Donea *et al.*, "An arbitrary lagrangian-eulerian finite element method for transient dynamic fluid-structure interactions," *Computer methods in applied mechanics and engineering*, vol. 33, no. 1-3, pp. 689–723, 1982.

[275] F. Ferstl *et al.*, "Large-scale liquid simulation on adaptive hexahedral grids," *IEEE transactions on visualization and computer graphics*, vol. 20, no. 10, pp. 1405–1417, 2014.

[276] B. Zhu *et al.*, "A new grid structure for domain extension," *ACM Trans. Graph.*, vol. 32, no. 4, p. 63, 2013.

[277] E. Kuhl *et al.*, "An arbitrary lagrangian eulerian finite-element approach for fluid–structure interaction phenomena," *Int J Numer Methods Eng*, vol. 57, no. 1, pp. 117–142, 2003.

[278] R. E. English *et al.*, "Chimera grids for water simulation," in *Proceedings of the 12th ACM SIGGRAPH/Eurographics Symposium on Computer Animation*. ACM, 2013, pp. 85–94.

[279] K. Museth, "Vdb: High-resolution sparse volumes with dynamic topology," *ACM Trans. Graph.*, vol. 32, no. 3, p. 27, 2013.

[280] R. Setaluri *et al.*, "Spgrid: A sparse paged grid structure applied to adaptive smoke simulation," *ACM Trans. Graph.*, vol. 33, no. 6, p. 205, 2014.

[281] E. Brun *et al.*, "A local level-set method using a hash table data structure," *Journal of Computational Physics*, vol. 231, no. 6, pp. 2528–2536, 2012.

[282] S. F. Frisken *et al.*, "Adaptively sampled distance fields: A general representation of shape for computer graphics," in *Proceedings of the 27th Annual Conference on Computer Graphics and Interactive Techniques*, ser. SIGGRAPH '00, 2000, pp. 249–254.

[283] A. Boonpan and S. Bureerat, "Multi-stage design of an automotive component," *International Journal of Vehicle Design*, vol. 60, no. 1/2, pp. 84–99, 2012, pMID: 49157.

[284] N. Aulig *et al.*, "Preference-based topology optimization for vehicle concept design with concurrent static and crash load cases," *Structural and Multidisciplinary Optimization*, vol. 57, no. 1, pp. 251–266, 2018.

[285] C. B. W. Pedersen, "Topology optimization design of crushed 2d-frames for desired energy absorption history," *Structural and Multidisciplinary Optimization*, vol. 25, no. 5-6, pp. 368–382, 2003.

[286] C. B. W. Pedersen, "Crashworthiness design of transient frame structures using topology optimization," *Computer Methods in Applied Mechanics and Engineering*, vol. 193, no. 6-8, pp. 653 – 678, 2004.

[287] K. Liu *et al.*, "Thin-walled compliant mechanism component design assisted by machine learning and multiple surrogates," in *SAE 2015 World Congress & Exhibition*, 2015.

[288] J. Goetz *et al.*, "Two-material optimization of plate armour for blast mitigation using hybrid cellular automata," *Engineering Optimization*, vol. 44, no. 8, pp. 985–1005, 2012.

[289] A. Diaz and O. Sigmund, "Checkerboard patterns in layout optimization," *Structural and Multidisciplinary Optimization*, vol. 10, no. 1, pp. 40–45, 1995.

[290] R. B. Haber *et al.*, "A new approach to variable-topology shape design using a constraint on perimeter," *Structural and Multidisciplinary Optimization*, vol. 11, no. 1, pp. 1–12, 1996.

[291] O. Sigmund, "On the design of compliant mechanisms using topology optimization," *Mechanics of Structures and Machines*, vol. 25, no. 4, 1997.

[292] T. E. Bruns and D. A. Tortorelli, "Topology optimization of non-linear elastic structures and compliant mechanisms," *Computer Methods in Applied Mechanics and Engineering*, vol. 190, no. 26, pp. 3443–3459, 2001.

[293] J. Petersson and O. Sigmund, "Slope constrained topology optimization," *Int J Numer Methods Eng*, vol. 41, no. 8, pp. 1417–1434, 1998.

[294] B. S. Lazarov and O. Sigmund, "Filters in topology optimization based on helmholtz-type differential equations," *International Journal for Numerical Methods in Engineering*, vol. 86, no. 6, pp. 765–781, 2011.

[295] A. Kawamoto *et al.*, "Heaviside projection based topology optimization by a pde-filtered scalar function," *Structural and Multidisciplinary Optimization*, vol. 44, no. 1, pp. 19–24, 2011.

[296] Q. Li *et al.*, "Structural topology optimization considering connectivity constraint," *Structural and Multidisciplinary Optimization*, vol. 54, no. 4, pp. 971–984, 2016.

[297] Y. Sato *et al.*, "Manufacturability evaluation for molded parts using fictitious physical models, and its application in topology optimization," *The International Journal of Advanced Manufacturing Technology*, pp. 1–19, 2017.

[298] X. Qian, "Undercut and overhang angle control in topology optimization: a density gradient based integral approach," *Int J Numer Methods Eng*, 2017.

[299] Y. Zhou *et al.*, "Multicomponent topology optimization for additive manufacturing with build volume and cavity free constraints," *Journal of Computing and Information Science in Engineering*, vol. 19, no. 2, p. 021011, Mar. 2019.

[300] Y. Zhou and K. Saitou, "Gradient-based multi-component topology optimization for stamped sheet metal assemblies (MTO-S)," *Structural and Multidisciplinary Optimization*, pp. 1–12, 2017.

[301] Y. Zhou *et al.*, "Multi-component topology and material orientation design of composite structures (MTO-C)," *Computer Methods in Applied Mechanics and Engineering*, vol. 342, pp. 438 – 457, 2018.

[302] Y. Zhou and K. Saitou, "Gradient-based multi-component topology optimization for additive manufacturing (MTO-A)," in *ASME 2017 International Design Engineering Technical Conferences and Computers and Information in Engineering Conference*. American Society of Mechanical Engineers, 2017, pp. V02AT03A033–V02AT03A033.

[303] B. Zhu *et al.*, "Two-scale topology optimization with microstructures," *ACM Trans. Graph.*, vol. 36, no. 5, pp. 164:1–164:16, Jul. 2017.

[304] A. Schulz *et al.*, "Interactive design space exploration and optimization for cad models," *ACM Trans. Graph.*, vol. 36, no. 4, pp. 157:1–157:14, Jul. 2017.

[305] G. Deaton, "Stiffening of restrained thermal structures via topology optimization," *Structural and Multidisciplinary Optimization*, vol. 48, no. 4, pp. 731–745, 2013.

[306] R. Picelli *et al.*, "Topology optimization for submerged buoyant structures," *Engineering Optimization*, vol. 49, no. 1, pp. 1–21, 2016.

[307] M. Shu, Wang, "Level set based topology optimization of vibrating structures for coupled acousticstructural dynamics," *Computer and Structures*, vol. 132, no. 1, pp. 32–42, 2014.

[308] W. Vicente *et al.*, "Topology optimization of frequency responses of fluid–structure interaction systems," *Finite Elements in Analysis and Design*, vol. 98, pp. 1–13, 2015.

[309] M. Jenkins, "An immersed boundary approach for shape and topology optimization of stationary fluid-structure interaction problems," *Structural and Multidisciplinary Optimization*, vol. 54, no. 1, pp. 1191–1208, 2016.

[310] R. Picelli *et al.*, "Evolutionary topology optimization for structural compliance minimization considering design-dependent fsi loads," *Finite Elements in Analysis and Design*, vol. 135, no. 1, pp. 44–55, 2017.

David Guirguis (M'16) received the M.A.S. degree in mechanical engineering from the University of Toronto, Toronto, ON, Canada, in 2016. He worked as a Research Assistant at the American University in Cairo, and the University of Toronto. He joined the University of Waterloo as a Research Associate. He has been with the Edward S. Rogers Sr. Department of Electrical and Computer Engineering, University of Toronto since 2017. He is a Design Engineer at Trimble Inc.

Nikola Aulig received his diploma in electrical engineering and information technology from Technical University Darmstadt in Germany in 2011. He joined the the Honda Research Institute Europe in Offenbach, Germany as a scientist in the Complex System Optimization and Analysis group where he researched combinations of topology optimization with evolutionary algorithms and machine learning. He completed his industrial doctorate in cooperation with the Technische Universitt Darmstadt in 2017. From 2017 to 2018 as a senior researcher with Honda, he shaped international multi-disciplinary research projects in the domains of optimization and artificial intelligence with relevance to the virtual product development. Today, he is pursuing a career as data scientist in the aerospace industry.

Renato Picelli is a Research Fellow at the Polytechnic School of the University of So Paulo. He received his PhD on "Evolutionary Topology Optimization of Fluid-structure Interaction Problems" from the University of Campinas, Brazil. His PhD work is acknowledged as one of the three existent methodologies for gradient-based topology optimization of design-dependent fluid- and acoustic-structure interaction problems. He was a visiting researcher at Delft University of Technology (TU Delft) in 2014, Royal Melbourne Institute of Technology (RMIT) in 2015, University of California San Diego (UCSD), in 2016 and a post-doctoral researcher at Cardiff University, in the UK, for three years.

Bo Zhu is an assistant professor in the Computer Science Department at Dartmouth College. He received his Ph.D. in Computer Science from Stanford University. He also worked as a postdoc researcher at MIT CSAIL. Bo's research interests encompass computer graphics, computational physics, and computational fabrication. In particular, he focuses on building computational approaches to automate the process of exploring complex physical systems.

Yuqing Zhou received the B.S. degree in mechanical engineering from Northeastern University, Shenyang, China, in 2012, and the M.S. and Ph.D. degrees in mechanical engineering from University of Michigan, Ann Arbor, MI, USA, in 2014 and 2018, respectively. He is currently a Postdoctoral Research Fellow with the Department of Mechanical Engineering, University of Michigan, Ann Arbor. His current research interest is structural topology optimization for manufacturability.

William Vicente is an assistant professor in structural dynamics and computational modeling at the School of Agricultural Engineering at University of Campinas. His current research interests include apply the finite element method and the structural topology optimization procedures to obtain innovative and efficient designs of implements/structures and materials that can be applied in the agricultural engineering.

Francesco Iorio received his M.Sc. in Computer Science (Information Technology) from the University of Liverpool, UK in 2008. He is currently working on his Ph.D. in computer science from the University of Toronto, Canada. In 2004 he joined Alias—Wavefront where he worked on scalable, high-performance 3D computer graphics for advanced visualization. In 2007 he joined the IBM High Performance Computing Group in Dublin, where he was the lead solution architect for all Cell Broadband Engine processor (Cell/B.E.) related projects in the fields of scientific computing, finance and high-throughput data analysis. In 2009 he joined Autodesk Research in Toronto, Canada, where he is Director of Computational Science Research and Distinguished Scientist. His research focuses on mathematical modeling, machine learning, creative AI and general design and exploitation of parallel algorithms on a variety of high-performance computing platforms. He has authored and co-authored more than 20 patents and publications.

Markus Olhofer is Chief Scientist at the Honda Research Institute Europe since 2010 and responsible for the Complex Systems Optimisation and Analysis Group of the institute. Markus Olhofer graduated in Electrical Engineering with a thesis on face detection and image recognition with a Diplom Ingenieur degree in 1997. After that he worked as PhD student at the Institute for Neural Computation (Institut fr Neuroinformatik), Ruhr-Universitt Bochum and received his PhD in 2000 from that university. He joined the Future Technology Research Division at Honda R&D Europe (Deutschland) GmbH in 1998 and since 2001 he works at the Honda Research Institute Europe GmbH.

Wojciech Matusik is an Associate Professor of Electrical Engineering and Computer Science at the Computer Science and Artificial Intelligence Laboratory at MIT, where he leads the Computational Fabrication Group. Before coming to MIT, he worked at Mitsubishi Electric Research Laboratories, Adobe Systems, and Disney Research Zurich. He studied computer graphics at MIT and received his PhD in 2003. He also received a BS in EECS from the University of California at Berkeley in 1997 and MS in EECS from MIT in 2001. His research interests are in direct digital manufacturing and computer graphics. In 2004, he was named one of the worlds top 100 young innovators by MITs Technology Review Magazine. In 2009, he received the Significant New Researcher Award from ACM Siggraph. In 2012, Matusik received the DARPA Young Faculty Award and he was named a Sloan Research Fellow.

Carlos Artemio Coello Coello (M98-SM04-F11) received Ph.D. degree in computer science from Tulane University, New Orleans, LA, USA, in 1996. He is a Professor (CINVESTAV-3F Researcher) with the Department of Computer Science of CINVESTAV-IPN, Mexico City, Mxico. He has authored and co-authored over 450 technical papers and book chapters. He has also co-authored the book Evolutionary Algorithms for Solving Multi-Objective Problems (Second Edition, Springer, 2007). His publications currently report over 48,900 citations in Google Scholar (h-index is 80). His research interests include evolutionary multi-objective optimization and constraint-handling techniques for evolutionary algorithms. He is a recipient of the 2007 National Research Award from the Mexican Academy of Sciences in the area of Exact Sciences, the 2013 IEEE Kiyo Tomiyasu Award and the 2012 National Medal of Science and Arts in the area of Physical, Mathematical and Natural Sciences. He is a member of the Association for Computing Machinery, Sigma Xi, and the Mexican Academy of Science.

Kazuhiro Saitou received the B.Eng. degree in mechanical engineering from the University of Tokyo, Tokyo, Japan, in 1990, and the M.S. and Ph.D. degrees in mechanical engineering from Massachusetts Institute of Technology, Cambridge, MA, USA, in 1992 and 1996, respectively. He is currently a Professor in the Department of Mechanical Engineering, University of Michigan, Ann Arbor, MI, USA. His research interest is algorithmic and optimal synthesis of products and systems, computational design for manufacture and assembly, and manufacturability-driven, multi-component structural topology optimization.