Recent Results and Open Problems in Evolutionary Multiobjective Optimization

Carlos A. Coello Coello*

CINVESTAV (Evolutionary Computation Group)
Departamento de Computación
Av. IPN No. 2508, Col. San Pedro Zacatenco
México, D.F. 07360, MEXICO
ccoello@cs.cinvestav.mx

Abstract. Evolutionary algorithms (as well as a number of other metaheuristics) have become a popular choice for solving problems having two or more (often conflicting) objectives (the so-called multi-objective optimization problems). This area, known as EMOO (Evolutionary Multi-Objective Optimization) has had an important growth in the last 20 years, and several people (particularly newcomers) get the impression that it is now very difficult to make contributions of sufficient value to justify, for example, a PhD thesis. However, a lot of interesting research is still under way. In this paper, we will briefly review some of the research topics on evolutionary multi-objective optimization that are currently attracting a lot of interest (e.g., indicator-based selection, many-objective optimization and use of surrogates) and which represent good opportunities for doing research. Some of the challenges currently faced by this discipline will also be delineated.

Keywords: evolutionary computing, optimization

1 Introduction

The solution of problems having two or more (normally conflicting) objectives has attracted a considerable attention in the last few years. The solution of these so-called *multi-objective optimization problems* (MOPs) gives rise to a set of solutions representing the best possible trade-offs among the objectives. Such solutions, defined in decision variable space constitute the so-called *Pareto optimal set*, and their corresponding objective function values form the so-called *Pareto front*.

Although a number of mathematical programming techniques have been developed since the 1970s to solve MOPs [81], such techniques present several limitations, from which two of the most relevant are that these algorithms are normally very susceptible to the shape or continuity of the Pareto front and that they tend to generate a single element of the Pareto optimal set per run.

* ORCID: 0000-0002-8435-680X

Additionally, in some real-world MOPs, the objective functions are not provided in algebraic form, but are the output of a black box software (which, for example, runs a simulation to obtain an objective function value), thus limiting the applicability of mathematical programming techniques. Such limitations have motivated the development of alternative approaches from which metaheuristics[1] have been, with no doubt, the most popular and effective choice available so far (see for example [24]).

From the many metaheuristics in current use, Evolutionary Algorithms (EAs) are, clearly, the most popular in today's specialized literature. EAs are inspired on the "survival of the fittest" principle from Darwin's evolutionary theory [43], and simulate the evolutionary process in a computer, as a way to solve problems. EAs have become very popular as multi-objective optimizers because of their ease of use (and implementation) and generality (e.g., they are less sensitive than mathematical programming techniques to the initial points used for the search and to the specific features of a MOP). EAs have also an additional advantage: since they are population-based techniques, it is possible for them to manage a set of solutions at a time, instead of only one, as normally done by traditional mathematical programming techniques. This allows EAs to generate several elements from the Pareto optimal set in a single run.

The first Multi-Objective Evolutionary Algorithm (MOEA) was proposed in the mid-1980s by David Schaffer [103]. However, it was until the mid-1990s that MOEAs started to attract serious attention from researchers. Nowadays, it is possible to find applications of MOEAs in practically all domains.[2]

The remainder of this paper is organized as follows. In Section 2, we provide some basic multi-objective optimization concepts required to make this paper self-contained. Section 3 briefly describes some relevant research topics that are worth currently being explored by EMOO researchers. In Section 4, we present other challenges in the field that have been only scarcely explored. Finally, the main conclusions of this paper are provided in Section 5.

2 Basic Concepts

We are interested in solving problems of the type[3]:

$$\text{minimize } \boldsymbol{f}(\boldsymbol{x}) := [f_1(\boldsymbol{x}), f_2(\boldsymbol{x}), \ldots, f_k(\boldsymbol{x})] \tag{1}$$

subject to:

$$g_i(\boldsymbol{x}) \leq 0 \quad i = 1, 2, \ldots, m \tag{2}$$

[1] A **metaheuristic** is a high level strategy for exploring search spaces by using different methods [14]. Metaheuristics have both a diversification (i.e., exploration of the search space) and an intensification (i.e., exploitation of the accumulated search experience) procedure.

[2] The author maintains the EMOO repository, which currently contains over 10,850 bibliographic references related to evolutionary multi-objective optimization. The EMOO repository is located at: https://emoo.cs.cinvestav.mx.

[3] Without loss of generality, we will assume only minimization problems.

$$h_i(\boldsymbol{x}) = 0 \quad i = 1, 2, \ldots, p \tag{3}$$

where $\boldsymbol{x} = [x_1, x_2, \ldots, x_n]^T$ is the vector of decision variables, $f_i : \mathbb{R}^n \to \mathbb{R}$, $i = 1, ..., k$ are the objective functions and $g_i, h_j : \mathbb{R}^n \to \mathbb{R}$, $i = 1, ..., m$, $j = 1, ..., p$ are the constraint functions of the problem.

To describe the concept of optimality in which we are interested, we will introduce next a few definitions.

Definition 1. Given two vectors $\boldsymbol{x}, \boldsymbol{y} \in \mathbb{R}^k$, we say that $\boldsymbol{x} \leq \boldsymbol{y}$ if $x_i \leq y_i$ for $i = 1, ..., k$, and that $\boldsymbol{x}$ **dominates** $\boldsymbol{y}$ (denoted by $\boldsymbol{x} \prec \boldsymbol{y}$) if $\boldsymbol{x} \leq \boldsymbol{y}$ and $\boldsymbol{x} \neq \boldsymbol{y}$.

Definition 2. We say that a vector of decision variables $\boldsymbol{x} \in \mathcal{X} \subset \mathbb{R}^n$ is **nondominated** with respect to $\mathcal{X}$, if there does not exist another $\boldsymbol{x}' \in \mathcal{X}$ such that $\boldsymbol{f}(\boldsymbol{x}') \prec \boldsymbol{f}(\boldsymbol{x})$.

Definition 3. We say that a vector of decision variables $\boldsymbol{x}^* \in \mathcal{F} \subset \mathbb{R}^n$ ($\mathcal{F}$ is the feasible region) is **Pareto-optimal** if it is nondominated with respect to $\mathcal{F}$.

Definition 4. The **Pareto Optimal Set** $\mathcal{P}^*$ is defined by:

$$\mathcal{P}^* = \{\boldsymbol{x} \in \mathcal{F} | \boldsymbol{x} \text{ is Pareto-optimal}\}$$

Definition 5. The **Pareto Front** $\mathcal{PF}^*$ is defined by:

$$\mathcal{PF}^* = \{\boldsymbol{f}(\boldsymbol{x}) \in \mathbb{R}^k | \boldsymbol{x} \in \mathcal{P}^*\}$$

We thus wish to determine the Pareto optimal set from the set $\mathcal{F}$ of all the decision variable vectors that satisfy (2) and (3). Note however that in practice, not all the Pareto optimal set is normally desirable (e.g., it may not be desirable to have different solutions that map to the same values in objective function space) or achievable.

3 Some Open Research Topics that are Worth Exploring

In spite of the significant development that MOEAs have experienced since their inception, there are still some research topics that are worth exploring in the next few years. From them, we will discuss three in this paper:

1. Algorithmic design
2. Scalability
3. Dealing with expensive objective functions

Next, we briefly discuss some of the most representative research that has been conducted on these topics.

3.1 Algorithmic design

In the early days of MOEAs, the approaches that were adopted were very simple and naive. For example, it was relatively common to use linear aggregating functions that combined all the objective functions into a single scalar value [48]. However, by the mid-1990s, several MOEAs started to adopt mechanisms such as *Pareto ranking* [43] and *nondominated sorting* [109]. In these mechanisms, the idea is to rank solutions based on Pareto optimality, such that nondominated individuals obtain the highest (best) possible rank. Since diversity is an important issue in MOEAs, in order to avoid convergence to a single solution, an additional mechanism was integrated to them: the so-called density estimator. Since the mid-1990s, a number of density estimators have been adopted, including: fitness sharing [44], clustering [129], adaptive grids [67], crowding [30], entropy [88] and parallel coordinates [54].

By the end of the 1990s, another mechanism was incorporated into MOEAs: elitism. The intuition behind the concept of *elitism* is that we need to retain the solutions that remain nondominated with respect to the new individuals that are being generated by our MOEA (otherwise, such solutions could be lost). Elitism is important not only from a practical point of view, but also for theoretical reasons, since this mechanism is required to guarantee convergence [99].

In spite of the large number of MOEAs that were proposed in the 1990s, few of them were widely used. From them, clearly the **Nondominated Sorting Genetic Algorithm II** (NSGA-II) [30] was the most popular (and is still being used today).

However, a few years after NSGA-II, another interesting MOEA was proposed: the **Multi-Objective Evolutionary Algorithm based on Decomposition** (MOEA/D) [124]. The idea of using decomposition was originally proposed in mathematical programming and it consists in transforming a multi-objective problem into several single-objective optimization problems which, in the case of MOEA/D are simultaneously solved, using neighborhood search. Decomposition-based methods would eventually become very popular research trend in algorithmic design (see for example [101]) and would influence the design of the **Nondominated Sorting Genetic Algorithm III** (NSGA-III) [29] which adopts decomposition and reference points.

Nevertheless, since 2004, a different type of algorithmic design has increasingly attracted interest from researchers: indicator-based selection. The idea of this sort of MOEA was introduced in the **Indicator-Based Evolutionary Algorithm** (IBEA) [126] which consists of an algorithmic framework that allows the incorporation of any performance indicator into the selection mechanism of a MOEA. IBEA was originally tested with the hypervolume [128] and the binary ϵ indicator [127]. Indicator-based selection has attracted a lot of interest, mainly because this sort of mechanism is known to work properly in many-objective optimization (i.e., MOPs having four or more objectives).

Over the years, a number of indicator-based MOEAs have been proposed, but probably the most representative approach within this family has been the **S Metric Selection Evolutionary Multiobjective Algorithm** (SMS-

EMOA) [36]. SMS-EMOA randomly generates an initial population and then produces a single solution per iteration (i.e., it uses steady state selection) using the crossover and mutation operators from NSGA-II. Then, it applies nondominated sorting (as in NSGA-II). When the last nondominated front has more than one solution, SMS-EMOA uses hypervolume to decide which solution should be removed. Beume et al. [11] proposed a new version of SMS-EMOA in which the hypervolume contribution is not used when, in the nondominated sorting process, we obtain more than one front. In this case, they use the number of solutions that dominate to a certain individual (i.e., the solution that is dominated by the largest number of solutions is removed).

After the introduction of SMS-EMOA, most indicator-based MOEAs that have been proposed adopt a performance indicator in their density estimator,[4] and not in their selection mechanism (see for example [59]). The actual use of a "pure" indicator-based selection mechanism has been very rare (see for example [78]).

So, at this point, one obvious question is: why is that the *hypervolume* is such an attractive choice for indicator-based selection?

The hypervolume (also known as the S metric or the Lebesgue Measure) of a set of solutions measures the size of the portion of objective space that is dominated by those solutions collectively. One of its main advantages are its mathematical properties, since it has been proved that the maximization of this performance measure is equivalent to finding the Pareto optimal set [39]. Additionally, empirical studies have shown that (for a certain number of points previously determined) the maximization of the hypervolume does indeed produce subsets of the Pareto front which are well-distributed [65, 36]. Also, the hypervolume assesses both convergence and, to a certain extent, also the spread of solutions along the Pareto front (although without enforcing uniform distribution of solutions).

However, there are several issues regarding the use of the hypervolume. First, the computation of this performance measure depends of a reference point, which can influence the results in a significant manner. Some people have proposed to use the worst objective function values in the current population, but this requires scaling of the objectives. Nevertheless, the most serious limitation of the hypervolume is its high computational cost. The best algorithms known to compute hypervolume have a polynomial complexity on the number of points used, but such complexity grows exponentially on the number of objectives [12]. This has triggered a significant amount of research regarding algorithms that can reduce the computational cost of computing the hypervolume[5] (see for example [121, 15, 120, 57]).

[4] In fact, the earliest use of the hypervolume into a MOEA is as a density estimator in a secondary population (see [65]).

[5] See also:
http://ls11-www.cs.uni-dortmund.de/rudolph/hypervolume/start
http://people.mpi-inf.mpg.de/~tfried/HYP/
http://iridia.ulb.ac.be/~manuel/hypervolume

An alternative to deal with this problem is to approximate the actual hypervolume contributions. This is the approach adopted by the **Hypervolume Estimation Algorithm for Multi-Objective Optimization** (HyPE) [3] in which Monte Carlo simulations are used to approximate exact hypervolume values. Although this is certainly a very interesting idea, in practice HyPE does not produce results as competitive as when using exact hypervolume computations.

Another possibility is to use another performance indicator, but the fact that the hypervolume is the only unary indicator which is known to be Pareto compliant [130] has made this alternative less attractive to researchers. Nevertheless, the use of a few other performance indicators has been reported to be successful in practice. Examples of these alternative indicator that have been used within MOEAs are: $R2$ [17, 51, 33, 46, 16, 52], Δ_p [105, 98, 79] and Inverted Generational Distance plus ($IGD+$) [60, 74]. Also, the use of other mechanisms such as the maximin fitness function, which seems to be related to the ϵ indicator are very promising (see for example [77]). All of these MOEAs are computationally inexpensive and perform quite well in many-objective problems, however, their use in practice is still very limited.

It is worth indicating that while some researchers debate if decomposition-based MOEAs or indicator-based MOEAs will become the new algorithmic trend in the next few years, other alternatives to the use of Pareto-based selection have been proposed. For example, Molinet Berenguer and Coello Coello [7], proposed an approach that transforms a multi-objective optimization problem into a linear assignment problem using a set of weight vectors uniformly scattered. Uniform design is adopted to obtain the set of weights, and the Kuhn-Munkres (Hungarian) algorithm [68] is used to solve the resulting assignment problem. This approach was found to perform quite well (and at a low computational cost) in many-objective optimization problems.

3.2 Scalability

In their early days, MOEAs were mainly used to solve problems having only two or three objectives. However, once Pareto-based MOEAs became popular, the need for solving problems having more objectives was very evident. At this point, problems started to arise, since it was soon evident that Pareto-based MOEAs tend to perform poorly in many-objective optimization problems [56]

Experimental [89, 117] and analytical studies [26, 66] have identified the following limitations of Pareto-based MOEAs in many-objective problems:

1. *Deterioration of the Search Ability:* The proportion of nondominated solutions in a population increases rapidly with the number of objectives [37]. According to Bentley *et al.* [5] the number of nondominated k-dimensional vectors on a set of size n is $O(\ln^{k-1} n)$. This implies that in problems with a large number objectives, the selection of solutions is carried out almost at random or guided by diversity criteria. In fact, Mostaghim and Schmeck [85] have shown that a random search optimizer achieves better results than NSGA-II [30] in a problem with 10 objectives.

2. *Dimensionality of the Pareto front:* Due to the 'curse of dimensionality' the number of points required to represent accurately a Pareto front increases exponentially with the number of objectives. The number of points necessary to represent a k-dimensional Pareto front with resolution r is given by $O(kr^{k-1})$ (*e.g.*, see [106]). This poses a challenge both to the data structures to efficiently manage that number of points and to the density estimators to achieve an even distribution of the solutions along the Pareto front.
3. *Visualization of the Pareto front:* Clearly, with more than three objectives is not possible to plot the Pareto front as usual. This is a serious problem since visualization plays a key role for a proper decision making process. In recent years, a number of visualization techniques have been proposed for many-objective problems (see for example [113]), but this is still an active research area.

In order to properly deal with many-objective optimization problems, three main approaches have been normally adopted [72, 70, 4]:

1. As indicated before, the use of indicator-based MOEAs has been an important research trend to deal with many-objective optimization problems, in spite of the limitations of some performance indicators such as the hypervolume (see for example [62]).
2. One interesting possibility that was adopted in the early days of many-objective optimization was the use of an optimality relation that yields a solution ordering finer than that yielded by Pareto optimality. Among these alternative relations we can find average ranking [6, 40], k-optimality [37], preference order ranking [32], favour relation [110], and a method that controls the dominance area [102], among others. Besides providing a richer ordering of the solutions, these relations obtain an optimal set that it is usually a subset of the Pareto optimal set.
3. Another interesting approach which is now rarely used is to reduce the number of objectives of the problem during the search process or in an *a posteriori* manner, during the decision making process [18, 31, 71]. The main goal of this kind of reduction techniques is to identify redundant objectives (or redundant to some degree) in order to discard them. A redundant objective is one that can be removed without changing the dominance relation induced by the original objective set.

In contrast with the significant interest that many-objective optimization has attracted in recent years, scalability in decision variable space has been only recently studied in the context of multi-objective optimization (see for example [82, 125, 83, 73]). This is remarkable if we consider that large-scale multi-objective optimization problems (i.e., problems having more than 100 decision variables) are not rare in real-world applications (see for example [119]). In this area, the use of cooperative coevolutionary approaches (which have been very successful in single-objective large-scale optimization) is the most common research trend. It is worth indicating, however, that no current benchmark exists that includes large-scale multi-objective optimization problems.

A more challenging problem would consist in solving many-objective large-scale problems, but no work in this direction has been reported yet, to the best of the author's knowledge.

3.3 Dealing with expensive objective functions

In spite of the current popularity of MOEAs, one of their limitations is that, since they are stochastic search techniques, they normally require a significant number of objective function evaluations in order to generate a proper sampling that allows a reasonably good approximation of the Pareto front, even when dealing with problems of low dimensionality. This is, indeed, a serious limitation when dealing with real-world problems, because in many cases, the cost of a MOEA becomes prohibitive.

In general, MOEAs can be unaffordable for an application when:

- The evaluation of the fitness functions is computationally expensive (i.e., it takes from minutes to hours).
- The fitness functions cannot be defined in an algebraic form (e.g., when the fitness functions are generated by a simulator).
- The total number of evaluations of the fitness functions is limited by financial constraints (i.e., there is a financial cost involved in computing the fitness functions).

In recent years, a significant amount of research has been conducted to allow MOEAs to properly deal with computationally expensive problems [100]. The main approaches that have been developed in this area can be roughly divided into three main groups:

1. **Use of parallelism:** This is clearly the most obvious approach given the current access to cheap parallel architectures (e.g., GPUs [28, 8, 107]). It is worth noting, however, that in spite of the existence of interesting proposals in this area (see for example [111, 84, 1]), the basic research in this area has remained scarce, since most publications involving parallel MOEAs focus on specific applications or on parallel extensions of specific MOEAs.
2. **Surrogates:** In this case, knowledge of past evaluations of a MOEA is used to build an empirical model that approximates the fitness functions to be optimized. This approximation can then be used to predict promising new solutions at a smaller evaluation cost than that of the original problem [64, 63]. Current functional approximation models include Polynomials (response surface methodologies [92, 41]), neural networks (e.g., multi-layer perceptrons (MLPs) [55, 58, 87]), radial-basis function (RBF) networks [86, 114, 122], support vector machines (SVMs) [104, 13], Gaussian processes [115, 20], and Kriging [35, 93] models. Although frequently used in engineering applications, surrogate methods can normally be adopted only in problems of low dimensionality, which is an important limitation when dealing with real-world MOPs.

3. **Fitness inheritance:** This technique was introduced by Smith et al. [108], and its main motivation is to reduce the total number of fitness function evaluations performed by a (single-objective) evolutionary algorithm. The mechanism works as follows: when assigning the fitness to an individual, some times we evaluate the objective function as usual, but the rest of the time, we assign fitness as an average of the fitness of the parents. This saves one fitness function evaluation, and is based on the assumption of similarity of an offspring to its parents. Fitness inheritance must not be always applied, since the algorithm needs to use the true fitness function several times, in order to obtain enough information to guide the search. The percentage of time in which fitness inheritance is applied is called *inheritance proportion*. If this inheritance proportion is 1, the algorithm is most likely to prematurely converge [23]. Extending fitness inheritance involves several issues, mainly related to its apparent limitation for dealing with non-convex Pareto fronts [34]. However, some researchers have managed to successfully adapt fitness inheritance to MOEAs [94], reporting important savings on the total number of objective function evaluations performed.

Other approaches are also possible. For example, some researchers have adopted cultural algorithms [25, 9, 10, 95], which obtain knowledge during the evolutionary process and use it to perform a more efficient search at the expense of a significantly large memory usage. Cultural algorithms were proposed by Reynolds [96, 97], as an approach that tries to add domain knowledge to an evolutionary algorithm during the search process, avoiding the need to add it *a priori*. This approach uses, in addition to the population space commonly adopted in evolutionary algorithms, a belief space, which encodes the knowledge obtained from the search points and their evaluation, in order to influence the evolutionary operators that guide the search. However, the belief space is commonly designed based on the group of problems that is to be solved. At each generation, the cultural algorithm selects some exemplar individuals from the population, in order to extract information from them that can be useful during the search. Such an information is used to update the belief space. The belief space will then influence the operators of the evolutionary algorithm, to transform them in informed operators and enhance the search process. Cultural algorithms can be an effective means of saving objective function evaluations, but since a map of decision variable space must be kept at all times, their cost will soon become prohibitive even for problems of moderate dimensionality.

4 Other Challenges

Several other topics remain scarcely explored in evolutionary multi-objective optimization. For example:

1. **Dynamic problems:** In the real world, there are problems in which the objective function values may vary over time (e.g., because of the presence

of noise), depending on certain events. The solution of such problems requires algorithms that are able to quickly "adapt" to these changes in the environment. There are relatively few MOEAs that have been designed to deal with dynamic MOPs and the current research in this area remains relatively scarce [21, 118, 27, 49, 91]. It is worth noting that dynamic problems require different types of benchmarks (see for example [38]) and performance measures (see for example [50]).

2. **Hyper-heuristics:** In spite of the fact that multi-objective memetic algorithms (i.e., MOEAs that are hybridized with a local search engine, which could be, for example, a gradient-based method [69] or a direct search method [123]) have gained popularity in recent years (see for example [42, 61, 75]), hyper-heuristics have been only scarcely explored in the context of multi-objective optimization, particularly for dealing with continuous optimization problems (see for example [45, 53]). Hyper-heuristics [22] are approaches that combine several types of heuristics, with the aim of combining their advantages in a wide class of problems. Their main motivation is to have a more general search engine that can solve a wider variety of hard optimization problems. Hyper-heuristics have been mostly developed for discrete search spaces and have been used to solve mainly single-objective optimization problems. However, their use in continuous multi-objective optimization problems, although possible, has been scarcely explored (see for example [76]). The use of other (similar) approaches that combine operators and different MOEAs into a common framework are also promising research venues (see for example [116, 47]).
3. **Automatic parameter configuration:** Although some relevant work has been conducted on parameter fine-tuning for MOEAs (see for example [19, 112, 2]), it has been only recently that researchers in evolutionary multi-objective optimization have considered the use of tools to do an automatic calibration of MOEAs (see for example [80]). One limitation for the use of such tools is that a scalar measure is required, but some researchers have relied on the use of hypervolume (see for example [90]) for that sake.

5 Conclusions

In this paper, a few research trends in evolutionary multi-objective optimization have been briefly described with the aim of encouraging more research in such areas.

The main goal of this paper is to illustrate that, in spite of its 32 years of existence, evolutionary multi-objective optimization still has several research opportunities to offer to newcomers. The contents of this paper is just a small sample of the several topics that are still available for starting a research career in this area.

Acknowledgements

The author gratefully acknowledges support from CONACyT grant no. 221551.

References

1. Alba, E., Luque, G., Nesmachnow, S.: Parallel metaheuristics: recent advances and new trends. International Transactions in Operational Research 20(1), 1–48 (January 2013)
2. Andersson, M., Bandaru, S., Ng, A.H.: Tuning of Multiple Parameter Sets in Evolutionary Algorithms. In: 2016 Genetic and Evolutionary Computation Conference (GECCO'2016). pp. 533–540. ACM Press, Denver, Colorado, USA (20-24 July 2016), iSBN 978-1-4503-4206-3
3. Bader, J., Zitzler, E.: HypE: An Algorithm for Fast Hypervolume-Based Many-Objective Optimization. Evolutionary Computation 19(1), 45–76 (Spring 2011)
4. Bechikh, S., Elarbi, M., Said, L.B.: Many-objective Optimization Using Evolutionary Algorithms: A Survey. In: Bechikh, S., Datta, R., Gupta, A. (eds.) Recent Advances in Evolutionary Multi-objective Optimization, pp. 105–137. Springer International Publishing, Switzerland (2017), iSBN 978-3-319-42977-9
5. Bentley, J., Kung, H., Schkolnick, M., Thompson, C.: On the average number of maxima in a set of vectors and applications. Journal of the Association for Computing Machinery 25(4), 536–543 (October 1978)
6. Bentley, P.J., Wakefield, J.P.: Finding Acceptable Solutions in the Pareto-Optimal Range using Multiobjective Genetic Algorithms. In: Chawdhry, P.K., Roy, R., Pant, R.K. (eds.) Soft Computing in Engineering Design and Manufacturing. pp. 231–240. Part 5, Springer Verlag London Limited, London (June 1997), (Presented at the 2nd On-line World Conference on Soft Computing in Design and Manufacturing (WSC2))
7. Berenguer, J.A.M., Coello Coello, C.A.: Evolutionary Many-Objective Optimization Based on Kuhn-Munkres' Algorithm. In: Gaspar-Cunha, A., Antunes, C.H., Coello Coello, C. (eds.) Evolutionary Multi-Criterion Optimization, 8th International Conference, EMO 2015, pp. 3–17. Springer. Lecture Notes in Computer Science Vol. 9019, Guimarães, Portugal (March 29 - April 1 2015)
8. Bernardes de Oliveira, F., Davendra, D., aes, F.G.G.: Multi-Objective Differential Evolution on the GPU with C-CUDA. In: Snášel, V., Abraham, A., Corchado, E.S. (eds.) Soft Computing Models in Industrial and Environmental Applications, 7th International Conference (SOCO'12), pp. 123–132. Springer. Advances in Intelligent Systems and Computing Vol. 188, Ostrava, Czech Republic (2013)
9. Best, C.: Multi-Objective Cultural Algorithms. Master's thesis, Wayne State University, Detroit, Michigan, USA (2009)
10. Best, C., Che, X., Reynolds, R.G., Liu, D.: Multi-objective Cultural Algorithms. In: 2010 IEEE Congress on Evolutionary Computation (CEC'2010). pp. 3330–3338. IEEE Press, Barcelona, Spain (July 18–23 2010)
11. Beume, N., Naujoks, B., Emmerich, M.: SMS-EMOA: Multiobjective selection based on dominated hypervolume. European Journal of Operational Research 181(3), 1653–1669 (16 September 2007)
12. Beume, N., Naujoks, B., Preuss, M., Rudolph, G., Wagner, T.: Effects of 1-Greedy S-Metric-Selection on Innumerably Large Pareto Fronts. In: Ehrgott, M., Fonseca, C.M., Gandibleux, X., Hao, J.K., Sevaux, M. (eds.) Evolutionary Multi-Criterion Optimization. 5th International Conference, EMO 2009, pp. 21–35. Springer. Lecture Notes in Computer Science Vol. 5467, Nantes, France (April 2009)
13. Bhattacharya, M., Lu, G.: A dynamic approximate fitness based hybrid ea for optimization problems. In: Proceedings of IEEE Congress on Evolutionary Computation. pp. 1879–1886 (2003)

14. Blum, C., Roli, A.: Metaheuristics in combinatorial optimization: Overview and conceptual comparison. ACM Computing Surveys 35(3), 268–308 (September 2003)
15. Bringmann, K., Friedrich, T.: The Maximum Hypervolume Set Yields Near-Optimal Approximation. In: Proceedings of the 12th annual conference on Genetic and Evolutionary Computation (GECCO'2010). pp. 511–518. ACM Press, Portland, Oregon, USA (July 7–11 2010), iSBN 978-1-4503-0072-8
16. Brockhoff, D.: A Bug in the Multiobjective Optimizer IBEA: Salutary Lessons for Code Release and a Performance Re-Assessment. In: Gaspar-Cunha, A., Antunes, C.H., Coello Coello, C. (eds.) Evolutionary Multi-Criterion Optimization, 8th International Conference, EMO 2015, pp. 187–201. Springer. Lecture Notes in Computer Science Vol. 9018, Guimarães, Portugal (March 29 - April 1 2015)
17. Brockhoff, D., Wagner, T., Trautmann, H.: On the Properties of the $R2$ Indicator. In: 2012 Genetic and Evolutionary Computation Conference (GECCO'2012). pp. 465–472. ACM Press, Philadelphia, USA (July 2012), iSBN: 978-1-4503-1177-9
18. Brockhoff, D., Zitzler, E.: Are All Objectives Necessary? On Dimensionality Reduction in Evolutionary Multiobjective Optimization. In: Runarsson, T.P., Beyer, H.G., Burke, E., Merelo-Guervós, J.J., Whitley, L.D., Yao, X. (eds.) Parallel Problem Solving from Nature - PPSN IX, 9th International Conference, pp. 533–542. Springer. Lecture Notes in Computer Science Vol. 4193, Reykjavik, Iceland (September 2006)
19. Büche, D., Milano, M., Koumoutsakos, P.: Self-Organizing Maps for Multi-Objective Optimization. In: Barry, A.M. (ed.) GECCO 2002: Proceedings of the Bird of a Feather Workshops, Genetic and Evolutionary Computation Conference. pp. 152–155. AAAI, New York (July 2002)
20. Bueche, D., Schraudolph, N., Koumoutsakos, P.: Accelerating evolutionary algorithms with gaussian process fitness function models. IEEE Transactions on Systems, Man, and Cybernetics: Part C 35(2), 183–194 (May 2005)
21. Bui, L.T., Nguyen, M.H., Branke, J., Abbass, H.A.: Tackling Dynamic Problems with Multiobjective Evolutionary Algorithms. In: Knowles, J., Corne, D., Deb, K. (eds.) Multi-Objective Problem Solving from Nature: From Concepts to Applications, pp. 77–91. Springer, Berlin (2008), iSBN 978-3-540-72963-1
22. Burke, E.K., Gendreau, M., Hyde, M., Kendall, G., Ochoa, G., Özcan, E., Qu, R.: Hyper-heuristics: a survey of the state of the art. Journal of the Operational Research Society 64(12), 1695–1724 (2013)
23. Chen, J.H., Goldberg, D.E., Ho, S.Y., Sastry, K.: Fitness Inheritance in Multi-Objective Optimization. In: Langdon, W., Cantú-Paz, E., Mathias, K., Roy, R., Davis, D., Poli, R., Balakrishnan, K., Honavar, V., Rudolph, G., Wegener, J., Bull, L., Potter, M., Schultz, A., Miller, J., Burke, E., Jonoska, N. (eds.) Proceedings of the Genetic and Evolutionary Computation Conference (GECCO'2002). pp. 319–326. Morgan Kaufmann Publishers, San Francisco, California (July 2002)
24. Coello Coello, C.A., Lamont, G.B., Van Veldhuizen, D.A.: Evolutionary Algorithms for Solving Multi-Objective Problems. Springer, New York, second edn. (September 2007), iSBN 978-0-387-33254-3
25. Coello Coello, C.A., Landa Becerra, R.: Evolutionary Multiobjective Optimization using a Cultural Algorithm. In: 2003 IEEE Swarm Intelligence Symposium Proceedings. pp. 6–13. IEEE Service Center, Indianapolis, Indiana, USA (April 2003)
26. Corne, D., Knowles, J.: Techniques for Highly Multiobjective Optimisation: Some Nondominated Points are Better than Others. In: Thierens, D. (ed.) 2007 Genetic

and Evolutionary Computation Conference (GECCO'2007). vol. 1, pp. 773–780. ACM Press, London, UK (July 2007)
27. Cruz, C., Gonzalez, J.R., Pelta, D.A.: Optimization in dynamic environments: a survey on problems, methods and measures. Soft Computing 15(7), 1427–1448 (July 2011)
28. Cserti, P., Szondi, S., Gaál, B., Kozmann, G., Vassányi, I.: GPU Based Parallel Genetic Algorithm Library. In: Filipič, B., Šilc, J. (eds.) Bioinspired Optimization Methods and Their Applications, Proceedings of the Fifth International Conference on Bioinspired Optimization Methods and their Applications, BIOMA 2012, pp. 231–244. Jožef Stefan Institute, Bohinj, Slovenia (24-25 May 2012), iSBN 978-961-264-043-9
29. Deb, K., Jain, H.: An Evolutionary Many-Objective Optimization Algorithm Using Reference-Point-Based Nondominated Sorting Approach, Part I: Solving Problems With Box Constraints. IEEE Transactions on Evolutionary Computation 18(4), 577–601 (August 2014)
30. Deb, K., Pratap, A., Agarwal, S., Meyarivan, T.: A Fast and Elitist Multiobjective Genetic Algorithm: NSGA–II. IEEE Transactions on Evolutionary Computation 6(2), 182–197 (April 2002)
31. Deb, K., Sinha, A., Kukkonen, S.: Multi-Objective Test Problems, Linkages, and Evolutionary Methodologies. In: et al., M.K. (ed.) 2006 Genetic and Evolutionary Computation Conference (GECCO'2006). vol. 2, pp. 1141–1148. ACM Press. ISBN 1-59593-186-4, Seattle, Washington, USA (July 2006)
32. di Pierro, F.: Many-Objective Evolutionary Algorithms and Applications to Water Resources Engineering. Ph.D. thesis, School of Engineering, Computer Science and Mathematics, UK (August 2006)
33. Díaz-Manríquez, A., Toscano-Pulido, G., Landa-Becerra, R.: A Hybrid Local Search Operator for Multiobjective Optimization. In: 2013 IEEE Congress on Evolutionary Computation (CEC'2013). pp. 173–180. IEEE Press, Cancún, México (20-23 June 2013), iSBN 978-1-4799-0454-9
34. Ducheyne, E.I., De Baets, B., De Wulf, R.: Is Fitness Inheritance Useful for Real-World Applications? In: Fonseca, C.M., Fleming, P.J., Zitzler, E., Deb, K., Thiele, L. (eds.) Evolutionary Multi-Criterion Optimization. Second International Conference, EMO 2003. pp. 31–42. Springer. Lecture Notes in Computer Science. Volume 2632, Faro, Portugal (April 2003)
35. Emmerich, M., Giotis, A., Özdenir, M., Bäck, T., Giannakoglou, K.: Metamodel-assisted evolution strategies. In: Parallel Problem Solving from Nature. pp. 371–380. No. 2439 in Lecture Notes in Computer Science, Springer (2002)
36. Emmerich, M., Beume, N., Naujoks, B.: An EMO Algorithm Using the Hypervolume Measure as Selection Criterion. In: Coello Coello, C.A., Hernández Aguirre, A., Zitzler, E. (eds.) Evolutionary Multi-Criterion Optimization. Third International Conference, EMO 2005. pp. 62–76. Springer. Lecture Notes in Computer Science Vol. 3410, Guanajuato, México (March 2005)
37. Farina, M.: A Neural Network Based Generalized Response Surface Multiobjective Evolutionary Algorithm. In: Congress on Evolutionary Computation (CEC'2002). vol. 1, pp. 956–961. IEEE Service Center, Piscataway, New Jersey (May 2002)
38. Farina, M., Deb, K., Amato, P.: Dynamic Multiobjective Optimization Problems: Test Cases, Approximations, and Applications. IEEE Transactions on Evolutionary Computation 8(5), 425–442 (October 2004)
39. Fleischer, M.: The Measure of Pareto Optima. Applications to Multi-objective Metaheuristics. In: Fonseca, C.M., Fleming, P.J., Zitzler, E., Deb, K., Thiele,

L. (eds.) Evolutionary Multi-Criterion Optimization. Second International Conference, EMO 2003. pp. 519–533. Springer. Lecture Notes in Computer Science. Volume 2632, Faro, Portugal (April 2003)

40. Garza Fabre, M., Toscano Pulido, G., Coello Coello, C.A.: Ranking Methods for Many-Objective Problems. In: Aguirre, A.H., Borja, R.M., García, C.A.R. (eds.) MICAI 2009: Advances in Artificial Intelligence. 8th Mexican International Conference on Artificial Intelligence. pp. 633–645. Springer. Lecture Notes in Artificial Intelligence Vol. 5845, Guanajuato, México (November 2009)
41. Goel, T., Vaidyanathan, R., Haftka, R., Shyy, W., Queipo, N., Tucker, K.: Response surface approximation of pareto optimal front in multiobjective optimization. Tech. Rep. 2004-4501, AIAA (2004)
42. Goh, C.K., Ong, Y.S., Tan, K.C. (eds.): Multi-Objective Memetic Algorithms. Springer, Berlin, Germany (2009), iSBN 978-3-540-88050-9
43. Goldberg, D.E.: Genetic Algorithms in Search, Optimization and Machine Learning. Addison-Wesley Publishing Company, Reading, Massachusetts (1989)
44. Goldberg, D.E., Richardson, J.: Genetic Algorithms with Sharing for Multimodal Function Optimization. In: Genetic Algorithms and their Applications: Proceedings of the Second International Conference on Genetic Algorithms. pp. 41–49. Lawrence Erlbaum, Massachusetts, USA (July 1987), iSBN 0-8058-0158-8
45. Gonçalves, R.A., Kuk, J.N., Almeida, C.P., Venske, S.M.: MOEA/D-HH: A Hyper-Heuristic for Multi-objective Problems. In: Gaspar-Cunha, A., Antunes, C.H., Coello Coello, C. (eds.) Evolutionary Multi-Criterion Optimization, 8th International Conference, EMO 2015, pp. 94–108. Springer. Lecture Notes in Computer Science Vol. 9018, Guimarães, Portugal (March 29 - April 1 2015)
46. ung H. Phan, D., Suzuki, J.: R2-IBEA: R2 Indicator Based Evolutionary Algorithm for Multiobjective Optimization. In: 2013 IEEE Congress on Evolutionary Computation (CEC'2013). pp. 1836–1845. IEEE Press, Cancún, México (20-23 June 2013), iSBN 978-1-4799-0454-9
47. Hadka, D., Reed, P.: Borg: An Auto-Adaptive Many-Objective Evolutionary Computing Framework. Evolutionary Computation 21(2), 231–259 (Summer 2013)
48. Hajela, P., Lin, C.Y.: Genetic search strategies in multicriterion optimal design. Structural Optimization 4, 99–107 (1992)
49. Helbig, M., Engelbrecht, A.P.: Dynamic Multi-Objective Optimization Using PSO. In: Alba, E., Nakib, A., Siarry, P. (eds.) Metaheuristics for Dynamic Optimization, chap. 8, pp. 147–188. Springer, Berlin, Germany (2013), iSBN 978-3-642-30664-8
50. Helbig, M., Engelbrecht, A.P.: Performance measures for dynamic multi-objective optimisation algorithms. Information Sciences 250, 61–81 (November 20 2013)
51. Hernández Gómez, R., Coello Coello, C.A.: MOMBI: A New Metaheuristic for Many-Objective Optimization Based on the $R2$ Indicator. In: 2013 IEEE Congress on Evolutionary Computation (CEC'2013). pp. 2488–2495. IEEE Press, Cancún, México (20-23 June 2013), iSBN 978-1-4799-0454-9
52. Hernández Gómez, R., Coello Coello, C.A.: Improved Metaheuristic Based on the $R2$ Indicator for Many-Objective Optimization. In: 2015 Genetic and Evolutionary Computation Conference (GECCO 2015). pp. 679–686. ACM Press, Madrid, Spain (July 11-15 2015), iSBN 978-1-4503-3472-3
53. Hernández Gómez, R., Coello Coello, C.A.: A Hyper-Heuristic of Scalarizing Functions. In: 2017 Genetic and Evolutionary Computation Conference (GECCO'2017). pp. 577 –584. ACM Press, Berlin, Germany (July 15-19 2017), iSBN 978-1-4503-4920-8.

54. Hernández Gómez, R., Coello Coello, C.A., Alba Torres, E.: A Multi-Objective Evolutionary Algorithm based on Parallel Coordinates. In: 2016 Genetic and Evolutionary Computation Conference (GECCO'2016). pp. 565–572. ACM Press, Denver, Colorado, USA (20-24 July 2016), iSBN 978-1-4503-4206-3
55. Hong, Y.S., H.Lee, Tahk, M.J.: Acceleration of the convergence speed of evolutionary algorithms using multi-layer neural networks. Engineering Optimization 35(1), 91–102 (2003)
56. Hughes, E.J.: Evolutionary Many-Objective Optimisation: Many Once or One Many? In: 2005 IEEE Congress on Evolutionary Computation (CEC'2005). vol. 1, pp. 222–227. IEEE Service Center, Edinburgh, Scotland (September 2005)
57. Hupkens, I., Deutz, A., Yang, K., Emmerich, M.: Faster Exact Algorithms for Computing Expected Hypervolume Improvement. In: Gaspar-Cunha, A., Antunes, C.H., Coello Coello, C. (eds.) Evolutionary Multi-Criterion Optimization, 8th International Conference, EMO 2015, pp. 65–79. Springer. Lecture Notes in Computer Science Vol. 9019, Guimarães, Portugal (March 29 - April 1 2015)
58. Hüscken, M., Jin, Y., Sendhoff, B.: Structure optimization of neural networks for aerodynamic optimization. Soft Computing 9(1), 21–28 (2005)
59. Igel, C., Hansen, N., Roth, S.: Covariance Matrix Adaptation for Multi-objective Optimization. Evolutionary Computation 15(1), 1–28 (Spring 2007)
60. Ishibuchi, H., Masuda, H., Tanigaki, Y., Nojima, Y.: Modified Distance Calculation in Generational Distance and Inverted Generational Distance. In: Gaspar-Cunha, A., Antunes, C.H., Coello Coello, C. (eds.) Evolutionary Multi-Criterion Optimization, 8th International Conference, EMO 2015, pp. 110–125. Springer. Lecture Notes in Computer Science Vol. 9019, Guimarães, Portugal (March 29 - April 1 2015)
61. Jaszkiewicz, A., Ishibuchi, H., Zhang, Q.: Multiobjective Memetic Algorithms. In: Neri, F., Cotta, C., Moscato, P. (eds.) Handbook of Memetic Algorithms, chap. 13, pp. 201–217. Springer, Berlin, Germany (2012), iSBN 978-3-642-23246-6
62. Jiang, S., Zhang, J., Ong, Y.S., Zhang, A.N., Tan, P.S.: A Simple and Fast Hypervolume Indicator-Based Multiobjective Evolutionary Algorithm. IEEE Transactions on Cybernetics 45(10), 2202–2213 (October 2015)
63. Jin, Y., Sendhoff, B., Körner, E.: Evolutionary Multi-objective Optimization for Simultaneous Generation of Signal-Type and Symbol-Type Representations. In: Coello Coello, C.A., Hernández Aguirre, A., Zitzler, E. (eds.) Evolutionary Multi-Criterion Optimization. Third International Conference, EMO 2005. pp. 752–766. Springer. Lecture Notes in Computer Science Vol. 3410, Guanajuato, México (March 2005)
64. Knowles, J.: ParEGO: A Hybrid Algorithm With On-Line Landscape Approximation for Expensive Multiobjective Optimization Problems. IEEE Transactions on Evolutionary Computation 10(1), 50–66 (February 2006)
65. Knowles, J., Corne, D.: Properties of an Adaptive Archiving Algorithm for Storing Nondominated Vectors. IEEE Transactions on Evolutionary Computation 7(2), 100–116 (April 2003)
66. Knowles, J., Corne, D.: Quantifying the Effects of Objective Space Dimension in Evolutionary Multiobjective Optimization. In: Obayashi, S., Deb, K., Poloni, C., Hiroyasu, T., Murata, T. (eds.) Evolutionary Multi-Criterion Optimization, 4th International Conference, EMO 2007. pp. 757–771. Springer. Lecture Notes in Computer Science Vol. 4403, Matshushima, Japan (March 2007)
67. Knowles, J.D., Corne, D.W.: Approximating the Nondominated Front Using the Pareto Archived Evolution Strategy. Evolutionary Computation 8(2), 149–172 (2000)

68. Kuhn, H.W.: The Hungarian Method for the Assignment Problem. Naval Research Logistics Quarterly 2(1–2), 83–97 (Mar 1955), http://dx.doi.org/10.1002/nav.3800020109
69. Lara, A., Sanchez, G., Coello Coello, C.A., Schütze, O.: HCS: A New Local Search Strategy for Memetic Multi-Objective Evolutionary Algorithms. IEEE Transactions on Evolutionary Computation 14(1), 112–132 (February 2010)
70. Li, B., Li, J., Tang, K., Yao, X.: Many-Objective Evolutionary Algorithms: A Survey. ACM Computing Surveys 48(1) (September 2015)
71. López Jaimes, A., Coello Coello, C.A., Chakraborty, D.: Objective Reduction Using a Feature Selection Technique. In: 2008 Genetic and Evolutionary Computation Conference (GECCO'2008). pp. 674–680. ACM Press, Atlanta, USA (July 2008), iSBN 978-1-60558-131-6
72. von Lücken, C., Baran, B., Brizuela, C.: A survey on multi-objective evolutionary algorithms for many-objective problems. Computational Optimization and Applications 58(3), 707–756 (July 2014)
73. Ma, X., Liu, F., Qi, Y., Wang, X., Li, L., Jiao, L., Yin, M., Gong, M.: A Multiobjective Evolutionary Algorithm Based on Decision Variable Analyses for Multi-objective Optimization Problems with Large-scale Variables. IEEE Transactions on Evolutionary Computation 20(2), 275–298 (April 2016)
74. Manoatl Lopez, E., Coello Coello, C.A.: IGD$^+$-EMOA: A Multi-Objective Evolutionary Algorithm based on IGD$^+$. In: 2016 IEEE Congress on Evolutionary Computation (CEC'2016). pp. 999–1006. IEEE Press, Vancouver, Canada (24-29 July 2016), iSBN 978-1-5090-0623-9
75. Mashwani, W.K., Salhi, A.: Multiobjective memetic algorithm based on decomposition. Applied Soft Computing 21, 221–243 (August 2014)
76. McClymont, K., Keedwell, E.C.: Markov Chain hyper-Heuristic (MCHH): an Online Selective Hyper-Heuristic for Multi-Objective Continuous Problems. In: 2011 Genetic and Evolutionary Computation Conference (GECCO'2011). pp. 2003–2010. ACM Press, Dublin, Ireland (July 12-16 2011)
77. Menchaca-Mendez, A., Coello Coello, C.A.: Selection mechanisms based on the maximin fitness function to solve multi-objective optimization problems. Information Sciences 332, 131–152 (March 1 2016)
78. Menchaca-Mendez, A., Coello Coello, C.A.: An Alternative Hypervolume-Based Selection Mechanism for Multi-Objective Evolutionary Algorithms. Soft Computing 21(4), 861–884 (February 2017)
79. Menchaca-Mendez, A., Hernández, C., Coello Coello, C.A.: Δ_p-MOEA: A New Multi-Objective Evolutionary Algorithm Based on the Δ_p Indicator. In: 2016 IEEE Congress on Evolutionary Computation (CEC'2016). pp. 3753–3760. IEEE Press, Vancouver, Canada (24-29 July 2016), iSBN 978-1-5090-0623-9
80. Menchaca-Mendez, A., Montero, E., Riff, M.C., Coello Coello, C.A.: A More Efficient Selection Scheme in iSMS-EMOA. In: Bazzan, A.L., Pichara, K. (eds.) Advances in Artificial Intelligence – IBERAMIA 2014, 14th Ibero-American Conference on AI, pp. 371–380. Springer. Lecture Notes in Artificial Intelligence Vol. 8864, Santiago de Chile, Chile (November 24-27 2014)
81. Miettinen, K.M.: Nonlinear Multiobjective Optimization. Kluwer Academic Publishers, Boston, Massachusetts (1999)
82. Miguel Antonio, L., Coello Coello, C.A.: Use of Cooperative Coevolution for Solving Large Scale Multiobjective Optimization Problems. In: 2013 IEEE Congress on Evolutionary Computation (CEC'2013). pp. 2758–2765. IEEE Press, Cancún, México (20-23 June 2013), iSBN 978-1-4799-0454-9

83. Miguel Antonio, L., Coello Coello, C.A.: Indicator-Based Cooperative Coevolution for Multi-objective Optimization. In: 2016 IEEE Congress on Evolutionary Computation (CEC'2016). pp. 991–998. IEEE Press, Vancouver, Canada (24-29 July 2016), iSBN 978-1-5090-0623-9
84. Mishra, B., Dehuri, S., Mall, R., Ghosh, A.: Parallel single and multiple objectives genetic algorithms: A survey. International Journal of Applied Evolutionary Computation 2(2), 21–57 (April 2011)
85. Mostaghim, S., Schmeck, H.: Distance Based Ranking in Many-Objective Particle Swarm Optimization. In: Rudolph, G., Jansen, T., Lucas, S., Poloni, C., Beume, N. (eds.) Parallel Problem Solving from Nature–PPSN X, pp. 753–762. Springer. Lecture Notes in Computer Science Vol. 5199, Dortmund, Germany (September 2008)
86. Ong, Y.S., Nair, P.B., Keane, A.J., Wong, K.W.: Surrogate-assisted evolutionary optimization frameworks for high-fidelity engineering design problems. In: Jin, Y. (ed.) Knowledge Incorporation in Evolutionary Computation, pp. 307–332. Studies in Fuzziness and Soft Computing, Springer (2004)
87. Pierret, S.: Turbomachinery blade design using a Navier-Stokes solver and artificial neural network. ASME Journal of Turbomachinery 121(3), 326–332 (1999)
88. Pires, E.J.S., Machado, J.A.T., de Moura Oliveira, P.B.: Entropy Diversity in Multi-Objective Particle Swarm Optimization. Entropy 15(12), 5475–5491 (December 2013)
89. Praditwong, K., Yao, X.: How Well Do Multi-Objective Evolutionary Algorithms Scale to Large Problems. In: 2007 IEEE Congress on Evolutionary Computation (CEC'2007). pp. 3959–3966. IEEE Press, Singapore (September 2007)
90. López-Ibáñez, M., Paquete, L., Stützle, T.: Automatic Configuration of Multi-Objective ACO Algorithms. In: Dorigo, M., Birattari, M., Caro, G.A.D., Doursat, R., Engelbrecht, A.P., Floreano, D., Gambardella, L.M., Groß, R., Şahin, E., Sayama, H., Stützle, T. (eds.) Swarm Intelligence. 7th International Conference, ANTS 2010, pp. 95–106. Springer, Lecture Notes in Computer Science Vol. 6234, Brussels, Belgium (September 8-10 2010)
91. Raquel, C., Yao, X.: Dynamic Multi-objective Optimization: A Survey of the State-of-the-Art. In: Yang, S., Yao, X. (eds.) Evolutionary Computation for Dynamic Optimization Problems, chap. 4, pp. 85–106. Springer-Verlag, Berlin, Germany (2013), iSBN 978-3-642-38415-8
92. Rasheed, K., Ni, X., Vattam, S.: Comparison of methods for developing dynamic reduced models for design optimization. Soft Computing 9(1), 29–37 (January 2005)
93. Ratle, A.: Accelerating the convergence of evolutionary algorithms by fitness landscape approximation. In: Eiben, A., Bäck, T., Schoenauer, M., Schwefel, H.P. (eds.) Parallel Problem Solving from Nature. vol. V, pp. 87–96 (1998)
94. Reyes Sierra, M., Coello Coello, C.A.: Fitness Inheritance in Multi-Objective Particle Swarm Optimization. In: 2005 IEEE Swarm Intelligence Symposium (SIS'05). pp. 116–123. IEEE Press, Pasadena, California, USA (June 2005)
95. Reynolds, R., Liu, D.: Multi-Objective Cultural Algorithms. In: 2011 IEEE Congress on Evolutionary Computation (CEC'2011). pp. 1233–1241. IEEE Service Center, New Orleans, Louisiana, USA (5–8 June 2011)
96. Reynolds, R.G.: An Introduction to Cultural Algorithms. In: Sebald, A.V., Fogel, L.J. (eds.) Proceedings of the Third Annual Conference on Evolutionary Programming, pp. 131–139. World Scientific, River Edge, New Jersey (1994)

97. Reynolds, R.G., Michalewicz, Z., Cavaretta, M.: Using cultural algorithms for constraint handling in GENOCOP. In: McDonnell, J.R., Reynolds, R.G., Fogel, D.B. (eds.) Proceedings of the Fourth Annual Conference on Evolutionary Programming, pp. 298–305. MIT Press, Cambridge, Massachusetts (1995)
98. Rodríguez Villalobos, C.A., Coello Coello, C.A.: A New Multi-Objective Evolutionary Algorithm Based on a Performance Assessment Indicator. In: 2012 Genetic and Evolutionary Computation Conference (GECCO'2012). pp. 505–512. ACM Press, Philadelphia, USA (July 2012), iSBN: 978-1-4503-1177-9
99. Rudolph, G., Agapie, A.: Convergence Properties of Some Multi-Objective Evolutionary Algorithms. In: Proceedings of the 2000 Conference on Evolutionary Computation. vol. 2, pp. 1010–1016. IEEE Press, Piscataway, New Jersey (July 2000)
100. Santana-Quintero, L.V., Arias Montaño, A., Coello Coello, C.A.: A Review of Techniques for Handling Expensive Functions in Evolutionary Multi-Objective Optimization. In: Tenne, Y., Goh, C.K. (eds.) Computational Intelligence in Expensive Optimization Problems, pp. 29–59. Springer, Berlin, Germany (2010), iSBN 978-3-642-10700-9
101. Santiago, A., Huacuja, H.J.F., Dorronsoro, B., Pecero, J.E., Santillan, C.G., Barbosa, J.J.G., Monterrubio, J.C.S.: A Survey of Decomposition Methods for Multi-objective Optimization. In: Castillo, O., Melin, P., Pedrycz, W., Kacprzyk, J. (eds.) Recent Advances on Hybrid Approaches for Designing Intelligent Systems. pp. 453–465. Springer (2014), iSBN 978-3-319-05170-3
102. Sato, H., Aguirre, H.E., Tanaka, K.: Controlling Dominance Area of Solutions and Its Impact on the Performance of MOEAs. In: Obayashi, S., Deb, K., Poloni, C., Hiroyasu, T., Murata, T. (eds.) Evolutionary Multi-Criterion Optimization, 4th International Conference, EMO 2007. pp. 5–20. Springer. Lecture Notes in Computer Science Vol. 4403, Matshushima, Japan (March 2007)
103. Schaffer, J.D.: Multiple Objective Optimization with Vector Evaluated Genetic Algorithms. In: Genetic Algorithms and their Applications: Proceedings of the First International Conference on Genetic Algorithms. pp. 93–100. Lawrence Erlbaum (1985)
104. Schoenauer, K.A.M.: Surrogate deterministic mutation. In: Artificial Evolution'01. pp. 103–115. Springer (2002)
105. Schütze, O., Esquivel, X., Lara, A., Coello Coello, C.A.: Using the Averaged Hausdorff Distance as a Performance Measure in Evolutionary Multiobjective Optimization. IEEE Transactions on Evolutionary Computation 16(4), 504–522 (August 2012)
106. Sen, P., Yang, J.B.: Multiple Criteria Decision Support in Engineering Design. Springer-Verlag, London (1998)
107. Sharma, D., Collet, P.: Implementation Techniques for Massively Parallel Multi-objective Optimization. In: Tsutsui, S., Collet, P. (eds.) Massively Parallel Evolutionary Computation on GPGPUs, pp. 267–286. Springer (2013), iSBN 978-3-642-37958-1
108. Smith, R.E., Dike, B.A., Stegmann, S.A.: Fitness inheritance in genetic algorithms. In: SAC '95: Proceedings of the 1995 ACM symposium on Applied computing. pp. 345–350. ACM Press, New York, NY, USA (1995)
109. Srinivas, N., Deb, K.: Multiobjective Optimization Using Nondominated Sorting in Genetic Algorithms. Evolutionary Computation 2(3), 221–248 (Fall 1994)
110. Sülflow, A., Drechsler, N., Drechsler, R.: Robust Multi-objective Optimization in High Dimensional Spaces. In: Obayashi, S., Deb, K., Poloni, C., Hiroyasu, T.,

Murata, T. (eds.) Evolutionary Multi-Criterion Optimization, 4th International Conference, EMO 2007. pp. 715–726. Springer. Lecture Notes in Computer Science Vol. 4403, Matshushima, Japan (March 2007)

111. Talbi, E.G., Mostaghim, S., Okabe, T., Ishibuchi, H., Rudolph, G., Coello Coello, C.A.: Parallel Approaches for Multi-objective Optimization. In: Branke, J., Deb, K., Miettinen, K., Slowinski, R. (eds.) Multiobjective Optimization. Interactive and Evolutionary Approaches, pp. 349–372. Springer. Lecture Notes in Computer Science Vol. 5252, Berlin, Germany (2008)
112. Toscano Pulido, G., Coello Coello, C.A.: The Micro Genetic Algorithm 2: Towards Online Adaptation in Evolutionary Multiobjective Optimization. In: Fonseca, C.M., Fleming, P.J., Zitzler, E., Deb, K., Thiele, L. (eds.) Evolutionary Multi-Criterion Optimization. Second International Conference, EMO 2003. pp. 252–266. Springer. Lecture Notes in Computer Science. Volume 2632, Faro, Portugal (April 2003)
113. Tušar, T., Filipič, B.: Visualization of Pareto Front Approximations in Evolutionary Multiobjective Optimization: A Critical Review and the Prosection Method. IEEE Transactions on Evolutionary Computation 19(2), 225–245 (April 2015)
114. Ulmer, H., Streicher, F., Zell, A.: Model-assisted steady-state evolution strategies. In: Proceedings of Genetic and Evolutionary Computation Conference. pp. 610–621. LNCS 2723 (2003)
115. Ulmer, H., Streichert, F., Zell, A.: Evolution startegies assisted by gaussian processes with improved pre-selection criterion. In: Proceedings of IEEE Congress on Evolutionary Computation. pp. 692–699 (2003)
116. Vrugt, J.A., Robinson, B.A.: Improved evolutionary optimization from genetically adaptive multimethod search. Proceedings of the National Academy of Sciences of the United States of America 104(3), 708–711 (January 16 2007)
117. Wagner, T., Beume, N., Naujoks, B.: Pareto-, Aggregation-, and Indicator-Based Methods in Many-Objective Optimization. In: Obayashi, S., Deb, K., Poloni, C., Hiroyasu, T., Murata, T. (eds.) Evolutionary Multi-Criterion Optimization, 4th International Conference, EMO 2007. pp. 742–756. Springer. Lecture Notes in Computer Science Vol. 4403, Matshushima, Japan (March 2007)
118. Wang, Y., Dang, C.: An Evolutionary Algorithm for Dynamic Multi-objective Optimization. Applied Mathematics and Computation 205(1), 6–18 (November 1 2008)
119. Watanabe, S., Ito, M., Sakakibara, K.: A Proposal on a Decomposition-Based Evolutionary Multiobjective Optimization for Large Scale Vehicle Routing Problems. In: 2015 IEEE Congress on Evolutionary Computation (CEC'2015). pp. 2581–2588. IEEE Press, Sendai, Japan (25-28 May 2015), iSBN 978-1-4799-7492-4
120. While, L., Bradstreet, L., Barone, L.: A Fast Way of Calculating Exact Hypervolumes. IEEE Transactions on Evolutionary Computation 16(1), 86–95 (February 2012)
121. While, L., Hingston, P., Barone, L., Huband, S.: A Faster Algorithm for Calculating Hypervolume. IEEE Transactions on Evolutionary Computation 10(1), 29–38 (February 2006)
122. Won, K.S., Ray, T.: Performance of Kriging and Cokriging based Surrogate Models within the Unified Framework for Surrogate Assisted Optimization. In: 2004 Congress on Evolutionary Computation (CEC'2004). vol. 2, pp. 1577–1585. IEEE Service Center, Portland, Oregon, USA (June 2004)

123. Zapotecas Martínez, S., Arias Montaño, A., Coello Coello, C.A.: A Nonlinear Simplex Search Approach for Multi-Objective Optimization. In: 2011 IEEE Congress on Evolutionary Computation (CEC'2011). pp. 2367–2374. IEEE Service Center, New Orleans, Louisiana, USA (5-8 June 2011)
124. Zhang, Q., Li, H.: MOEA/D: A Multiobjective Evolutionary Algorithm Based on Decomposition. IEEE Transactions on Evolutionary Computation 11(6), 712–731 (December 2007)
125. Zille, H., Ishibuchi, H., Mostaghim, S., Nojima, Y.: Mutation Operators Based on Variable Grouping for Multi-Objective Large-Scale Optimization. In: 2016 IEEE Symposium Series on Computational Intelligence (SSCI'2016). IEEE Press, Athens, Greece (6-9 December 2016), iSBN 978-1-5090-4240-1
126. Zitzler, E., Künzli, S.: Indicator-based Selection in Multiobjective Search. In: et al., X.Y. (ed.) Parallel Problem Solving from Nature - PPSN VIII. pp. 832–842. Springer-Verlag. Lecture Notes in Computer Science Vol. 3242, Birmingham, UK (September 2004)
127. Zitzler, E., Laumanns, M., Bleuler, S.: A Tutorial on Evolutionary Multiobjective Optimization. In: Gandibleux, X., Sevaux, M., Sörensen, K., T'kindt, V. (eds.) Metaheuristics for Multiobjective Optimisation. pp. 3–37. Springer. Lecture Notes in Economics and Mathematical Systems Vol. 535, Berlin (2004)
128. Zitzler, E., Thiele, L.: Multiobjective Optimization Using Evolutionary Algorithms—A Comparative Study. In: Eiben, A.E. (ed.) Parallel Problem Solving from Nature V. pp. 292–301. Springer-Verlag, Amsterdam (September 1998)
129. Zitzler, E., Thiele, L.: Multiobjective Evolutionary Algorithms: A Comparative Case Study and the Strength Pareto Approach. IEEE Transactions on Evolutionary Computation 3(4), 257–271 (November 1999)
130. Zitzler, E., Thiele, L., Laumanns, M., Fonseca, C.M., da Fonseca, V.G.: Performance Assessment of Multiobjective Optimizers: An Analysis and Review. IEEE Transactions on Evolutionary Computation 7(2), 117–132 (April 2003)